



Automatic reset wrenches

- Accuracy ex works $\pm 2\%$ except - K.315DA, K.325D $\pm 4\%$.- R.304DA $\pm 6\%$.
- For use with removable accessories, such as open end and ring end, or with ratchets.
- ISO 6789

		Capacity N.m	End fitting	Graduation N.m	Dimensions wrench only		Dimensions including case		
					L (mm)	 (kg)	Case	L (mm)	 (kg)
	R.304DA	1-5	9 x 12	0,05	185	0,290	BP.D1	420	0,77
	R.306-25D	5-25	9 x 12	0,10	254	0,41	BP.D1	420	0,9
	J.306-50D	10-50	9 x 12	1,00	347	0,89	BP.D2	585	1,54
	S.306-100D	20-100	9 x 12	1,00	437	1,05	BP.D2	585	1,75
	S.306-200D	40-200	14 x 18	1,00	515	1,26	BP.D3	805	2,22
	S.306-350D	70-350	14 x 18	2,00	725	1,79	BP.D3	805	2,75
	K.315DA	120-600	14 x 18	2,00	945	4,6	BT.121A	1050	8,8
	K.325DA	200 - 1000	\varnothing_{30}	4,00	1280	5,9	BT.K325D	1420	11,77

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [facom](#) manufacturer:

Other Similar products are found below :

[92A.5,5](#) [ARB.5.5X40](#) [ANXR10X75](#) [AEF.J6](#) [AEF.J1](#) [EH.107](#) [EH.103](#) [256.2.5](#) [MT.J3](#) [986058](#) [75.10](#) [PB.MTJ5](#) [84E.J1](#) [455B](#) [440.19](#)
[44.6X7](#) [440.21](#) [R.306-25D](#) [R.217](#) [R.5](#) [J.13LA](#) [431.LE](#) [425.E](#) [R.216](#) [601](#) [AEF.1,5X35](#) [AEX.J2](#) [AEX.9X75](#) [AEX.7X35](#) [251A.2.5](#) [HB.2B](#)
[440.20](#) [435.E](#) [432.LMT](#) [44.12X13](#) [440.5H](#) [440.22](#) [R.304DA](#) [427.MT](#) [113A.10C](#) [251A.3](#) [AEF.1,8X35](#) [75.7](#) [440.30](#) [440.18](#) [440.8](#) [R.4](#)
[J.19LA](#) [44.JE8](#) [417.PE](#)