RADIALL No.390, Yong He Road, Shanghai 200072, China			TECHNICAL DATA SHEET CABLE ASSEMBLY		IEET	PART NUMBER : R284C0351066 Issue : NA Date : NA		
Customer :	: Specification : NA				Issu	ue: NA	Date : N/A	
All dimensions are in mm								
R113.181.020	C00.10	C291.145.007						
• 250±5mm								
Connectors designation : Connector 1 : MCX Right Angle Plug Crimp Type Cable 2/50 S (R113.181.020) Connector 2 : MCX Right Angle Plug Crimp Type Cable 2/50 S (R113.181.020)								
Cable designation : Flexible Cable 2/50S (RG178)								
C291.145.007 Nominal length : Lg: 250 mm								
Cable colour : Outer diameter :		-	Brown 1.78 mm					
Accessories : HeatShrink Sleeves (9.11.95.000.10)								
High Frequency		Low Frequency						
Characteristic impedar	2 Ohms		Insulation Resistance : 1000 MOhms min					
Frequency range : DC-3GHz				Voltage Rating : 170 Veff max				
Insertion Loss : 0.87 dB max @ 3GHz & 20°C								
VSWR. : TBT								
MECANICAL CHARACTERISTICS : Recommend min. bend radius : 7 mm								
Cable crush resistance : NA								
Life (connectors) : 500 cycles								
ENVIRONMENTAL CHARACTERISTICS :					CUSTOMER'S APPROVAL			
Operating temperature	155° C		Service or					
Remark : NA					Company's stamp			
Attachment : R113.181.020-TDS,								
C291.145.007 (RG178)-TDS Cable Assembly is RoHS compliant. Date								
Peter	А	2007-5-25	Creation		Willy			
Name	Issue	Date	Modification			Checke	ed by	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for radiall manufacturer:

Other Similar products are found below :

 F760858219
 8959-1511-004
 5919-1503-000
 7101-1541-010
 7105-1561-010
 MD11-035
 81-6201-0450
 9074-9513-000
 9620-9003-151

 R113425097
 R114305000W
 R124075210
 R125055000
 R125512000W
 R141154000W
 R141572000
 R143012000
 R143235161W

 R166268000
 R176019000
 R191841001W
 R282102000
 R282744220
 R282918120
 R404770000
 R414430150
 R414520150
 R433514700

 R570022105
 R570123005
 R570363010
 R570442000
 R570E52010
 R574402410
 R585423230
 R114425000
 R125052500

 R125320020W
 R141331500W
 R162017000W
 R176404000
 R191970091
 R282750000
 R317270000
 R404110150

 R404280150
 R404755000
 R413210150
 R404755000
 R413210150
 R404110150