

# Fuse holder terminal block with screwed plug for 5 x 20 mm or 5 x 25 mm fuses

## Screw clamp

DIN 1 - DIN 3




End stop		th. 9 mm	BADL	V0	1SNA 399 903 R0200
End stop		th. 10 mm	BAM2	V2	1SNA 206 351 R1600
End stop		th. 10 mm	BAM2 V0	V0	1SNA 296 351 R0000
Rail		35 x 7,5 x 1	PR3.Z2		1SNA 174 300 R1700
Rail		35 x 15 x 2,3	PR4		1SNA 168 500 R1200
Rail		35 x 15 x 1,5	PR5		1SNA 168 700 R2200
Rail		32 x 15 x 1,5	PR1.Z2		1SNA 163 050 R0400

Other end stops, rails and accessories : see section on accessories.

### Notes

The use of some accessories may decrease the block's voltage rating. For more information, consult us.

### Accessories




1	End section	grey
2	Standard jumper bar	57 A
3	IDC jumper	
4	Fuse 5 x 20	250 V
	Fuse 5 x 25	250 V
	Fast acting according to DIN 41576.1	



R See section on markers marking method

## MB 10/12.SF...


Spacing 12 mm (.473")



12 mm block, no fusion indicator - for 5 x 20 mm or 5 x 25 mm fuses

## MB 10/12.SF...

Spacing 12 mm (.473")



12 mm block with neon fusion indicator for fuses 5 x 20 mm.

Colour	Type	Part numbers	Colour	Type	Part numbers
Grey/5x20 mm <input type="checkbox"/>	<b>MB 10/12.SF</b>	1SNA 111 033 R0300	Grey/110-220V (2) <input type="checkbox"/>	<b>MB 10/12.SFL</b>	1SNA 111 034 R0400
Grey/5x25 mm <input type="checkbox"/>	<b>MB 10/12.SF1</b>	1SNA 111 035 R0500	Grey/LED 24 V (3) <input type="checkbox"/>	<b>MB 10/12.SFD</b>	1SNA 111 037 R0700

### Characteristics

Wire size		NFC DIN	UL	CSA
Screw clamp	Rigid	0,5-16 mm <sup>2</sup>	18-6 AWG	18-6 AWG
	Flexible	0,5-10 mm <sup>2</sup>	18-6 AWG	18-6 AWG

Voltage		500 V Gr.C (1)	600 V (1)	250 V
Impulse withstand				
Pollution degree				

Current		10 A	15 A	15 A
---------	--	------	------	------

Wire size		10 mm <sup>2</sup>	6 AWG	6 AWG
Rated / Gauge				
Wire stripping length	Recomm. screwdriver	Recomm. torque	Protection	
13 mm .512"	6 mm .236"	1,2-1,4 Nm 10.6-12.3 lb.in	IP 10	

### Characteristics

Wire size		NFC DIN	UL	CSA
Screw clamp	Rigid	0,5-16 mm <sup>2</sup>	18-6 AWG	18-6 AWG
	Flexible	0,5-10 mm <sup>2</sup>	18-6 AWG	18-6 AWG

Voltage		500 V Gr.C (1)	600 V (1)	250(SFL) 24(SFD)
Impulse withstand				
Pollution degree				

Current		10 A	15 A	15 A
---------	--	------	------	------

Wire size		10 mm <sup>2</sup>	6 AWG	6 AWG
Rated / Gauge				
Wire stripping length	Recomm. screwdriver	Recomm. torque	Protection	
13 mm .512"	6 mm .236"	1,2-1,4 Nm 10.6-12.3 lb.in	IP 10	

Type	Part numbers	Type	Part numbers
FEM12S V2	th. 3 mm 1SNA 117 628 R2200	FEM12S V2	th. 3 mm 1SNA 117 628 R2200
BJS12 (2)	20 poles 1SNA 177 653 R0700		
Screw for BJS	1SNA 163 574 R2200		
Washer for BJS	1SNA 163 633 R2500		
AD2,5	1SNA 114 205 R2000	AD2,5 24 A	1SNA 114 205 R2000
FU520	0,5 A 1SNA 008 288 R1500	FU520	0,5 A 1SNA 008 288 R1500
	1 A 1SNA 008 290 R1300		1 A 1SNA 008 290 R1300
	2 A 1SNA 008 291 R0000		2 A 1SNA 008 291 R0000
	3,15 A 1SNA 008 289 R1600		3,15 A 1SNA 008 289 R1600
	5 A 1SNA 008 292 R0100		5 A 1SNA 008 292 R0100
	1,6 A 1SNA 167 546 R2200		
	2 A 1SNA 167 547 R2300		
	2,5 A 1SNA 167 548 R0400		
	4 A 1SNA 167 549 R0500		
	6,3 A 1SNA 167 550 R0200		

RC65 - RC610 Sides of block

RC65 - RC610 Sides of block

Note : (1) Insulation voltage of terminal block - operating voltage : according to fuse.  
(2) Use of these accessories requires the user to cut out the partition.

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [entrelec](#) manufacturer:*

Other Similar products are found below :

[023000012](#) [023103024](#) [023000107](#) [1SNK505310R0000](#) [011762822](#) [016511417](#) [016340320](#) [1SNK516020R0000](#) [023300421](#)

[1SNK510010R0000](#) [018731214](#) [011870703](#) [010500220](#) [011511607](#) [023300227](#) [016049626](#) [017666704](#) [1SNK508411R0000](#) [023300320](#)

[023300001](#) [016548827](#) [012511813](#) [017301610](#) [011546820](#) [010500127](#)