

► **BRADYSLEEVE™ WIRE MARKING SLEEVES**

Heat-Shrinkable White Polyolefin (B-321)

Part Number	Sleeves Per Roll	Sleeve Dimensions		Range of Wire Dia.		Approx. Wire Gauge*	Maximum Characters Per Line For Font: 2	Maximum Lines Of Text For Font: 2
		A Inch (mm)	B Inch (mm)	Min Inch (mm)	Max Inch (mm)			
0.450" Sleeve Width								
PTS-045-350-321	500	0.450 (11.43)	0.350 (8.89)	0.075 (1.91)	0.160 (4.06)	10-16	9	2
PTS-045-500-321	500	0.450 (11.43)	0.500 (12.70)	0.160 (4.06)	0.235 (5.97)	8-10	9	4
0.950" Sleeve Width								
PTS-095-350-321	500	0.950 (24.13)	0.350 (8.89)	0.075 (1.91)	0.160 (4.06)	10-16	21	2
PTS-095-500-321	500	0.950 (24.13)	0.500 (12.70)	0.160 (4.06)	0.235 (5.97)	8-10	21	4
PTS-095-750-321	250	0.950 (24.13)	0.750 (19.05)	0.335 (8.51)	0.390 (9.91)	2-4	21	7
PTS-095-1000-321	250	0.950 (24.13)	1.000 (25.40)	0.375 (9.53)	0.540 (13.72)	00-1	21	10
1.900" Sleeve Width								
PTS-190-350-321	500	1.900 (48.26)	0.350 (8.89)	0.075 (1.91)	0.160 (4.06)	10-16	44	2
PTS-190-500-321	500	1.900 (48.26)	0.500 (12.70)	0.160 (4.06)	0.235 (5.97)	8-10	44	4
PTS-190-750-321	250	1.900 (48.26)	0.750 (19.05)	0.335 (8.51)	0.390 (9.91)	2-4	44	7
PTS-190-1000-321	250	1.900 (48.26)	1.000 (25.40)	0.375 (9.53)	0.540 (13.72)	00-1	44	10

* Based on National Electric Code insulation measurement of THHN Wire.

Note: Labels are sorted in order by width, height, 3 digit material number (within part number), then die number (within part number).

► **BRADYTAG® PRINTABLE TAGS**

Polyethylene (B-109)




Diagram	Part Number	Tags Per Roll	Tag Dimensions		Maximum Characters Per Line For Font: 2	Maximum Lines Of Text For Font: 2	Applications/Description
			Inch (mm) A	Inch (mm) B			
▲	PTL-12-109	100	0.750 (19.05)	3.000 (76.20)	45	6	Product ID for harsh environments/tear resistant
▲	BPTL-12-109	1000	0.750 (19.05)	3.000 (76.20)	45	6	Product ID for harsh environments/tear resistant
▶	PTL-36-109	250	1.750 (44.45)	1.125 (28.57)	34	12	Product ID for harsh environments/tear resistant



► **ELECTRICAL COMPONENT MARKERS**

Polypropylene (B-412)

Part Number	Labels Per Roll	Label Dimensions		Maximum Characters Per Line For Font: 2	Maximum Lines Of Text For Font: 2
		Inch (mm) A	Inch (mm) B		
PTL-57-412	50 ft (15.24 m)	0.500 (12.70)	continuous	50	5

► **TERMINAL BLOCK MARKERS**

Repositional Vinyl Cloth (B-498)



Part Number	Roll Length Ft. (m)	Label Dimensions		Maximum Characters Per Line For Font: 2	Maximum Lines Of Text For Font: 2
		Inch (mm) A	Ft. (m) B		
PTLTB-498-240	30 ft (9.10 m)	0.240 (6.09)	30 ft (9.10 m)	5	N/A
BPTLTB-498-240	300 ft (91.44 m)	0.240 (6.09)	300 ft (91.44 m)	5	N/A
PTLTB-498-318	30 ft (9.10 m)	0.318 (8.07)	30 ft (9.10 m)	7	N/A
BPTLTB-498-318	300 ft (91.44 m)	0.318 (8.07)	300 ft (91.44 m)	7	N/A
PTLTB-498-375	30 ft (9.10 m)	0.375 (9.52)	30 ft (9.10 m)	8	N/A
BPTLTB-498-375	300 ft (91.44 m)	0.375 (9.52)	300 ft (91.44 m)	8	N/A

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Wire Identification](#) category:

Click to view products by [Brady](#) manufacturer:

Other Similar products are found below :

[CU6337-000](#) [CU6342-000](#) [FCA-410-12](#) [11631010](#) [1-1768037-1](#) [1-1768037-2](#) [1-1768050-0](#) [PXLK-VI](#) [Q62184-1](#) [A64304-000](#) [QMT221](#)
[HK032WE1NF038B](#) [1330-0519-10](#) [1395199-1](#) [1395200-1](#) [1395202-1](#) [DMVF050WE-300S6](#) [D-SCE-1K-2.4-50-4-CS7834](#) [1538738-1](#)
[E90935-000](#) [EC1238-000](#) [EC1465-000](#) [EC1855-000](#) [EC1859-000](#) [EC1863-000](#) [EC5415-000](#) [EC7277-000](#) [EC7352-000](#) [EC7603-000](#)
[EC7707-000](#) [EC7735-000](#) [EC7768-000](#) [EC7828-000](#) [EC7854-000](#) [EC7952-000](#) [EC8128-000](#) [1768037-8](#) [1768041-7](#) [NC-127191-10-9](#)
[HS048WE2NF038B](#) [C03232-000](#) [HTCM-SCE-14-4H-9](#) [HTMS-3/16-9](#) [HT-SCE-1/4-2.0-4](#) [HT-SCE-3/16-2.0-4](#) [HTTMS-1/2-1.50-9](#) [HTTMS-](#)
[CM-1/2-4H-9](#) [HX-SCE-19.0-50-9](#) [HX-SCE-6.4-50-4](#) [C25254-000](#)