

YAEV25-L1

BURNDY® PRODUCTS

YAEV25-L1

YAEV25-L1 : NYLN-INSLTED-RING-TONGUE



ACTIVE

RoHS
compatible[Assistant](#)[Add to Favorites](#)
[✉ Email Datasheet](#)
[🖨 Print Datasheet](#)

FCI Brings You More

[✉ > Contact our sales/technical support](#)
[📄 > Sample request](#)
[€ > Price request](#)

Specifications

[Download document](#)

Dimensional	Physical	Approvals / Certifications	Other Features
Dimensional			
Strip length (Wire)			11/16 in.
Stud Hole (Size)			1/4 in.
Tongue Angle			Straight
Tongue Width (in)			0.83 in.
Wire Shroud			No
Insulation Diameter (Max)			0.564 in.
Physical			
Conductor Size			1/0 AWG
Conductor Type			Commercial/Military Stranded Copper
Insulation Type			Nylon
Color Code			Blue
Conductor Size (Range)			1/0 AWG
Approvals / Certifications			
Military Listed			MS15036-132
UL Listed			No
CSA Certified			No
Military Specification			Class 1
Other Features			
Tongue Type			Ring
Bulk Catalog Number			Same
UPC			78181002755
Keyword			smtermHD

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Terminals](#) category:

Click to view products by [FCT Electronics](#) manufacturer:

Other Similar products are found below :

[HT-13-10](#) [71M-250-32-NB](#) [01-2065-1-0216](#) [00581P0075](#) [M10-10RX](#) [M10BCK](#) [60205-1](#) [604200-1](#) [60598-1-CUT-TAPE](#) [60617-1-C](#) [60873-1](#) [M14-516R/SK](#) [M14-6RSX](#) [M18-10FLX](#) [M18-8FBX](#) [M18-8R/LX](#) [M18BCK](#) [61314-6-C](#) [61-S](#) [61-SN-A](#) [62-NBM-A](#) [63-S](#) [640179-1](#) [640917-2-CUT-TAPE](#) [6501550002](#) [66107-2-C](#) [696683-1](#) [696834-1](#) [696861-1](#) [696931-1](#) [696999-1](#) [M8-516RK](#) [M86700006](#) [MA250DMFMX-A](#) [701-2007](#) [701-2307](#) [701-7761-03](#) [70F-110-32-PB](#) [718-N-A](#) [71M-187-20-NBL](#) [71M-250-32-NBL](#) [72F-187-20-NBL](#) [72M-250-32-NBL](#) [7310](#) [73F-250-32](#) [73F-250-32-NBL](#) [73F-250-32-NL](#) [F14-10C](#) [F-1M](#) [751-250](#)