

SPECIFICATION	
AMPS/PHASE	0.67
RESISTANCE/PHASE (Ohms)@25°C	5.6±15%
INDUCTANCE/PHASE (mH) @1KHz	4.0±20%
SPINDLE PITCH (mm) [in]	5 [0.197]
TRUST (N) [lbf]	30 [6.74]
RESOLUTION (mm/STEP)	0.025
STATIC TRUST (N) [lbf] (NO CURRENT)	13
MAX. SPEED (mm/sec.) AT 48V	100
MAX. SPEED WITH MAX. TRUST (mm/sec.) AT 48V	50
WEIGHT (Kg) [lb]	0.11 [0.242]
TEMPERATURE RISE: MAX.80°C (MOTOR STANDSTILL; FOR 2 PHASE ENERGIZED)	
AMBIENT TEMPERATURE -10°~ 50°C [14°F ~ 122°F]	
INSULATION RESISTANCE 100 MOhm (UNDER NORMAL TEMPERATURE AND HUMIDITY)	
INSULATION CLASS B 130° [266°F]	
DIELECTRIC STRENGTH 500VAC FOR 1 MIN. (BETWEEN THE MOTOR COILS AND THE MOTOR CASE)	
AMBIENT HUMIDITY MAX. 85% (NO CONDENSATION)	

Please regard the application note at www.nanotec.com for further informations.


Shaft play is adjustable at the motor.

TYPE OF CONNECTION (EXTERN)	MOTOR		
	BIPOLAR	LEADS	WINDING
PIN NO			
1	A —	BLK	A
2	A\ —	GRN	A\
3	B —	RED	B
4	B\ —	BLU	B\

WIRING DIAGRAM

FULL STEP 2 PHASE-Ex., WHEN FACING MOUNTING END (X)

STEP	A	B	A\	B\		CCW
1	+	+	-	-		
2	-	+	+	-		
3	-	-	+	+		
4	+	-	-	+		
						CW



REV	DESCRIPTION	DATE	APVD
2	NEW VALUES	05.06.10	J.W.
1	PIN-ASSIGNMENT AND NOTE	21.05.10	J.W.



L2818S0604-T5x5

SCALE	FREE	APVD	S.Ha.	15.01.10
X	±0.5	CHKD		
1PL	±0.2	DRN	J.W.	15.01.10
2PL	±0.1	SIGNATURE		DATE
ANGLE	±30'			

LINEAR ACTUATOR

DWG.NO

L2818S0604-T5x5

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [nanotec](#) manufacturer:

Other Similar products are found below :

[LSNUT-T6X2-F](#) [STF2818X0504-A](#) [SP2575M0206-A](#) [DB59C024035-A](#) [SP1518M0204-A](#) [ST6018L3008-A](#) [ZKRS485-USB](#) [SP3575M0906-A](#) [C5-01](#) [ST2818S1006-B](#) [SMCI35](#) [ST4118L1804-A](#)