Product datasheet Characteristics

XUB2BKSWM12T

photo-electric sensor - XUB - emitter - 90° -12..24VDC - M12



Main	
Range of product	OsiSense XU
Series name	General purpose single mode
Electronic sensor type	Photo-electric sensor transmitter
Sensor name	XUB
Sensor design	Cylindrical M18
Detection system	Thru beam
Material	Metal
Line of sight type	90° lateral
Type of output signal	Discrete
Supply circuit type	DC
Wiring technique	3-wire
Electrical connection	1 male connector M12, 4 pins
Product specific application	-
Emission	Infrared thru beam
[Sn] nominal sensing distance	15 m thru beam need a receiver

Complementary

Main		
Range of product	OsiSense XU	
Series name	General purpose single mode	
Electronic sensor type	Photo-electric sensor transmitter	
Sensor name	XUB	
Sensor design	Cylindrical M18	
Detection system	Thru beam	
Material	Metal	
Line of sight type	90° lateral	
Type of output signal	Discrete	
Supply circuit type	DC	
Wiring technique	3-wire	
Electrical connection	1 male connector M12, 4 pins	
Product specific application	-	
Emission	Infrared thru beam	
[Sn] nominal sensing distance	15 m thru beam need a receiver	
Complementer		
Complementary Enclosure material	Nickel plated brass	
Lens material	PMMA	
Maximum sensing distance	20 m thru beam	
Output type	Solid state	
Add on input	Test by emission breaking	
Status LED	1 LED (green) for supply on	
[Us] rated supply voltage	1224 V DC with reverse polarity protection	
Supply voltage limits	1036 V DC	
Switching capacity in mA	<= 100 mA (overload and short-circuit protection)	
Owntorning capacity in mix	ייי ווא (טיפווטמט מווט אוטוניטונטונ אוטנפטנוטוו)	

Voltage drop	1.5 V (closed state)
Current consumption	35 mA (no-load)
Delay first up	< 15 ms
Delay response	< 1 ms
Delay recovery	< 1 ms
Setting-up	Without sensitivity adjustment
Diameter	18 mm
Length	76 mm
Product weight	0.05 kg

Environment

Product certifications	UL CE CSA
Ambient air temperature for operation	-2555 °C
Ambient air temperature for storage	-4070 °C
Vibration resistance	7 gn, amplitude = +/- 1.5 mm (f = 1055 Hz) conforming to IEC 60068-2-6
Shock resistance	30 gn (duration = 11 ms) conforming to IEC 60068-2-27
IP degree of protection	IP65 double insulation conforming to IEC 60529 IP67 double insulation conforming to IEC 60529 IP69K double insulation conforming to DIN 40050

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 0821 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	

Contractual warranty

Warranty period	18 months

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Photoelectric Sensors category:

Click to view products by Schneider manufacturer:

Other Similar products are found below:

E3JM-DS70R4T-US E3L2DC4 E3RA-DN12 2M E3RA-DP12 2M E3S5LE4S E3S-AD38 E3S-CR11 5M E3SCT11D5M E3SCT11M1J03M E3T-SL14R E3T-SL24 5M E3T-ST12R E3X-CN02 E3X-CN11 5M E3X-CN21 10M E3ZM-B66 E3ZM-CL81H 2M E3Z-T62 2M NJL5303R-TE1 PB10CNT15PO PD60CNX20BP CX-491-P-J CX-491-Z XUM2BKCNL2T XUM2BKCNL2T XUM2BNANL2R Y92E-ES30M Y92E-GS08SS ZXTDS04T ZX-XC4A 4M E3E23Y2US E3JM-DS70S4-US E3RA-RN11 2M E3S5LE42M E3S-LS20XB4 5M E3TFD14N E3T-FD14R E3T-SL21 5M E3T-SL21M E3T-ST11R E3T-ST12 5M E3X-DA41-S-M1J 0.3M E3X-DAB6 E3X-DAG8 E3ZM-B86 E3ZM-CR81 2M E3ZM-CR86 E3Z-T61A-L 2M ZX-XGC2R ZX-XB1A