

1N3595



SANTA ANA, CA

For more information call: (714) 979-8220

FEATURES

- HIGH CONDUCTANCE
- EXTREMELY LOW REVERSE CURRENT
- ULTRA-STABLE OPERATION UP TO +150°C
- VOIDLESS HERMETICALLY SEALED GLASS PACKAGE
- JANS/TX/TXV TYPES AVAILABLE PER MIL-S-19500-241
- METALLURGICALLY BONDED

MAXIMUM RATINGS


Operating Temperature: -65°C to +150°C Storage Temperature: -65°C to +200°C

Surge Current: 4 Amps

ELECTRICAL CHARACTERISTICS

J/JTX/ JTXV/S	FORWARD VOLTAGE DROP V _F ** 1 _F VOLTS		FORWARD CURRENT 1 _F madc	REVERSE CURRENT (MAX) J _R ≈ 125V		REVERSE CURRENT (MAX) IR *** 30V	REVERSE RECOVERY (MAX)	JUNCTION CAPACITANCE (MAX) C © OV
	1N3595	.83	1.00	200	1.0	500	300	3.0
	.79	.92	100	1.0]	300	3.0	8.0
	.74	.88	50	1.0		300	3.0	8.0
	.65	.80	10	1.0	3μ A	300	3.0	8.0
	.60	.75	5	1.0	@	300	3.0	8.0
	.52	.68	1	1.0	150°C	300	3.0	8.0

GENERAL PURPOSE DIODES



MECHANICAL **CHARACTERISTICS**

CASE: Hermetically sealed glass case.

LEAD MATERIAL: Tinned copper

clad steel.

MARKING: Body painted, alpha

numeric.

POLARITY: Cathode band.

1N3595




FIGURE 2 Typical forward voltage VS. Forward current




FIGURE 4
POWER DERATING CURVE





FIGURE 3
REVERSE CURRENT VS.
AMBIENT TEMPERATURE



TA - AMBIENT TEMPERATURE - °C

FIGURE 5
AVERAGE RECTIFIED CURRENT
VS. AMBIENT TEMPERATURE

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Rectifiers category:

Click to view products by Microsemi manufacturer:

Other Similar products are found below:

D91A DA24F4100L DD89N1600K-A DD89N16K-K RL252-TP DLA11C-TR-E DSA17G DSEI2X30-06C 1N4005-TR BAV199-TP UFS120Je3/TR13 JANS1N6640US DD89N16K DD89N16K-A 481235F DSP10G-TR-E 067907F MS306 ND104N08K SPA2003-B-D-A01 VGF0136AB US2JFL-TP UFS105Je3/TR13 A1N5404G-G ACGRA4007-HF ACGRB207-HF RF301B2STL RF501B2STL UES1306 UES1302 BAV199E6433HTMA1 ACGRC307-HF ACEFC304-HF JANTXV1N5660A UES1106 GS2K-LTP D126A45C D251N08B SCHJ22.5K SM100 SCPA2 SCH10000 SDHD5K STTH20P035FP VS-8EWS12S-M3 VS-12FL100S10 ACGRA4001-HF MUR420GP-TP 1N5404GP-E3/54 ND89N08K