Product datasheet Characteristics

XSDA600519

inductive sensor XSD 80x80x40 - plastic - Sn60mm - 24..240VAC - terminals



Main

Main		
Range of product	OsiSense XS	, u
Series name	General purpose	ţ
Sensor type	Inductive proximity sensor	
Product specific application	-	
Sensor name	XSD	4.1
Sensor design	Form 80 x 80 x 40	1
Size	40 mm	
Body type	Fixed	
Enclosure material	Plastic	
Type of output signal	Discrete	
Wiring technique	2-wire	
[Sn] nominal sensing distance	60 mm	
Discrete output function	1 NO or 1 NC programmable	9
Electrical connection	Screw-clamp terminals	-
[Us] rated supply voltage	AC	2.
IP degree of protection	IP67	

Complementary

Detection face	5 positions turret head	9
Detector flush mounting acceptance	Non flush mountable	
Material	Plastic	.i.
Front material	Plastic	. <u>v</u>
Output circuit type	AC	ta O
Cable entry	1 entry tapped for Pg 13.5 cable gland	
Switching frequency	<= 10 Hz	
Depth	40 mm	Ē
Height	100 mm	
		ç

Width	80 mm
Product weight	0.48 kg
Environment	
Product certifications	CCC
Ambient air temperature for operation	-2570 °C
Offer Sustainability	
Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1136 - Schneider Electric declaration of conformity
	Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold
Product environmental profile	Available
	End of life manual

Contractual warranty

Product end of life instructions

Warranty period 18 months

Need no specific recycling operations

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Proximity Sensors category:

Click to view products by Schneider manufacturer:

Other Similar products are found below:

01.001.5653.1 70.340.1028.0 70.360.2428.0 70.364.4828.0 70.810.1053.0 72.360.1628.0 73.363.6428.0 9221350022 980659-1 QT-12 E2EX10D1NN E2E-X14MD1-G E2E-X2D1-G E2EX2ME2N E2E-X3D1-N 10M E2E-X4MD1-G E2FMX1R5D12M E2K-F10MC1 5M EI1204TBOSL-6 EI5515NPAP BSA-08-25-08 IC08ANC15PO-K IMM2582C 25.161.3253.0 25.332.0653.1 25.352.0653.0 25.352.0753.0 25.523.3253.0 9151710023 922FS1.5C-A4P-Z774 SC606ABV0S30 SM952A126100LE A1220EUA-T F3S-A162-U CL18 QT-08L 34.110.0010.0 TL-C2MF1-M3-E4 IA08BLF15NOM5 IA08BSF15NOM5 IA12ASF04DOM1 IMM32188C IS2 IS31SE5000-UTLS2-TR 34.110.0021.0 34.110.0022.0 CA150-120VACDC VM18VA3000Q XS508BSCBL2 XS512BLNAM12