Farnell Electronic Components Limited

Marketing & Purchasing Centre

Armley Road Leeds LS122QQ West Yorkshire
 Phone
 (0532) 790101 (25 lines)

 Dataline
 310160

 Telex
 556000

(0532) 633404

THIS DATA SHEET COVERS
THE FOLLOWING PART N°S
106-312/313
106-328 to 332
150-369 to 391.

(FEC Nos, 106-312 to 106-313

[FEC No; 106-328 to 106-332

* CORDAGE AND LEADS/CORDS

PHYSICAL CHARACTERISTICS

CONDUCTOR : 26 AWG 7 STRAND COPPER

Fax

INSULATION : PVC

JACKET : PVC

PERFORMANCE

CONDUCTOR RESISTANCE > 20 MILLIOHMS PER METER

INSULATION RESISTANCE > 100 M OHM DIELECTRIC STRENGTH > 500 VAC

MECHANICAL

PLUG PULL FORCE : 18 LBS MIN

TERMINAL CRIMPING STRENGTH : 4,4 LBS MIN

LINE C	CORD F	<u> </u>	-	1	2	3	4	5	6	7	8
4 WAY	WHITE	SHOPTH ©	150-369			BLACK	وحك	GREEN	_Yermi		
6		и	150-370	<u> </u>	WHITE	n _	'n	ч		BUE	
*8 *	BLACK	34	150-371_	_,BWE,	centre	II.	, W	u.		seow	CABY.
LINE CO	RDS-PL	NG TO SPADE				 !	-		- -		-
LINE CO	RDS-PL	LUG TO SPADE					•	-	 		
		LUG TO SOMDE	106-328			BLACK	RD	GREEN	YELLOW		
					!	BLACK	RED	Gleen "	YELLOW		
4 way	Ivory	Smeathed	106-328		WHITE	и			İ	BUE	
4 way	IVORY BLACK	Siteathed	106-328		1	81	11	0	u		



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for pro signal manufacturer:

Other Similar products are found below:

KVM-404 JR8030/25M MJ-2325 AV02019 MC34967 MC34971 ABI-049-RC SVC675S-10M 11.99.8870 PSG01592 PSG01567

PSG01546 PSG01522 PS11468 PS11199 PS11072 PS11360 PS11156 PS11147 PS11022 PSG03905 PSG00559 PSG00564 PS000177

PHONO PLG-PLG 10M AV02560 AV02595 ABM-710-RC USB-0039DBL PSG90957 PSG01495 PSG01462 PS11386 PS11028 PS11179

RP004 PSG90986 27-9650 PSG02699 USB2.0EX0104 ABS-237-RC JR8013-10M JR8009/5M LS00532 AVVCL65 LCL PSG90820

PSG01544 PS11161 PSG00562