



TECHNICAL DATA SHEET

concept


4504FE NON-PAIRED

code
version **1**
date **2004-04-27**
page **1/2**

APPLICATION

Intercom/PA Systems, Sound/Audio Systems.

CONSTRUCTION



1. Conductor

Diameter of conductor 0.75mm (AWG22)
Material stranded bare copper (7xAWG30)

2. Insulation

Material PE
Diameter over insulation 1.25 ± 0.05 mm
Wallthickness 0.25 mm

3. Overall Cabling

Colour code black-red-white-green-brown-blue

4. Outer shield

Shield Beldfoil®
Shield Material Aluminium / Polyester tape
Shield Thickness Alu 9 μ m
Shield coverage 100%
Drainwire AWG24 (7xAWG32) tinned Cu

4. Sheath

Material FRNC
Colour Grey
Nominal thickness of sheath 0.38 mm
Diameter over sheath 4.6 ± 0.30 mm

REQUIREMENTS AND TEST METHODS

Electrical:

Nominal resistance conductor 54 Ω /km
Nominal resistance shield 50 Ω /km
Nom. capacitance conductor to conductor @ 1kHz 105 pF/m
Nom. capacitance cond. to shield + other cond. @ 1kHz 185 pF/m
Testvoltage conductor-conductor 2500 VDC, 3 seconds
Testvoltage conductor-screen 2500 VDC, 3 seconds
Voltage rating 300 V RMS
Maximum continues current per conductor @ 25 °C 2.0 A per conductor @ 25 °C

**TECHNICAL DATA SHEET***concept***4504FE NON-PAIRED**code
version **1**
date **2004-04-27**
page **2/2****Mechanical and physical:**

Temperature range processing and operating	-20 to +70 °C
Temperature range storage	-30 to +70 °C
Minimum bending/setting radius	5*D/10*D
Maximum pulling tension	28 N
Halogen free according to	IEC 60754-1
Non dense smoke according to	IEC 61034-1 and 61034-2
Non corrosive gas according to	IEC 60754-2
Flame Retardant according to	IEC 60332-1

MARKING

NEW GENERATION(R) BY BELDEN 4504FE HALOGEN FREE 70C 6C22 SHIELDED + sequential meter marking.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [belden manufacturer](#):

Other Similar products are found below :

[HIPWP4LA](#) [HIPWP2LA](#) [49905A 060S2](#) [49907A 060S2](#) [8916-GRN/YEL-500](#) [8916-YEL-500](#) [8918-GRY-1000](#) [8919-DK-BLU-100](#) [8920-008-1000](#) [8920-BRN-1000](#) [8920-GRY-1000](#) [5T00UP 008500](#) [7810A-BLK-500](#) [7934A-BLK-1000](#) [7937A-BLK-1000](#) [8019-100](#) [8080](#) [8108-060-1000](#) [8125-CHR-100](#) [8132-CHR-1000](#) [8133-CHR-1000](#) [8155-CHR-1000](#) [8162-060-1000](#) [8162-CHR-1000](#) [8164-CHR-100](#) [8164-CHR-1000](#) [8185-CHR-100](#) [8205-CHR-1000](#) [8221-BLK-1000](#) [8233-010-1000](#) [8233-BLK-1000](#) [8237-BLK-500](#) [8238-BLK-500](#) [8241-006-U1000](#) [8241A-BLK-1000](#) [8241F-RED-MATTE-1000](#) [8263-BLK-U1000](#) [8279-BLK-1000](#) [8281-003-1000](#) [8281 010500](#) [83000 002100](#) [83002 0101000](#) [83003-006-500](#) [83003-VIO-500](#) [83004-RED-100](#) [83008 0091000](#) [83008-WHT-1000](#) [83010-BRN-100](#) [83010-RED-100](#) [83029 0021000](#)