

This document was generated on 01/29/2016

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0455600161

Status: Active

Overview: HandyLink™ I/O Interconnect System

Description: 0.80mm Pitch HandyLink™ Parallel Surface Mount Cradle Connector Assembly, 16

Circuit

**Documents:** 

<u>Drawing (PDF)</u>
3D Model

Product Specification PS-44828-001 (PDF)

RoHS Certificate of Compliance (PDF)

**Agency Certification** 

CSA LR19980 UL E29179

General

Product Family I/O Connectors

Series <u>45560</u>

Application Board-to-Board Comments Parallel-PCB

Component Type Plug MolexKits Yes

More Detailed Tech Information <a href="mailto:handylink@molex.com">handylink@molex.com</a>

Overview <u>HandyLink™ I/O Interconnect System</u>

Product Name HandyLink®

Type N/A

UPC 822348066148

**Physical** 

Circuits (Loaded) 16
Circuits (maximum) 16
Flammability 94V-0
Lock to Mating Part Yes

Material - Metal Phosphor Bronze

Material - Plating MatingGoldMaterial - Plating TerminationTinNet Weight2.246/gOrientationVerticalPCB LocatorNoPCB RetentionYesPCB Thickness - Recommended1.50mm

Packaging Type Embossed Tape on Reel

Panel Mount No
Pitch - Mating Interface 0.80mm
Plating min - Mating 0.051µm
Plating min - Termination 3.810µm
Polarized to Mating Part Yes
Surface Mount Compatible (SMC) N/A

Temperature Range - Operating -40°C to +85°C Termination Interface: Style Surface Mount

Wire Size AWG N/A

**Electrical** 

Current - Maximum per Contact 1.5A Shielded No Voltage - Maximum 30V

**Solder Process Data** 

Duration at Max. Process Temperature (seconds) 040



EU ELV Not Relevant

EU RoHS China RoHS

Compliant REACH SVHC Not Contained Per -ED/79/2015 (17 December 2015) Halogen-Free Status

Low-Halogen

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
Please visit the <u>Contact Us</u> section for any non-product compliance questions.

China ROHS Green Image ELV Not Relevant

Search Parts in this Series

45560 Series

Mates With 44828

Lead-freeProcess CapabilityREFLOWMax. Cycles at Max. Process Temperature003Process Temperature max. C260

**Material Info** 

**Reference - Drawing Numbers** 

Product Specification PS-44828-001 Sales Drawing SD-45560-002

This document was generated on 01/29/2016

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Telecom ICs category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

87180-066 B78476A9558A003 4C9965 RH1041W-MFP-GNL 5C3263 7J8004 SCMS7D43AY100PT1 43841-0003-CUT-TAPE

HX6106NLT 75586-0004-CUT-TAPE JC0-0201NL 0432498916 0757840156 93899-001LF 9455511103 10118067-5136210LF 69253-001

H1062 P129 T7015NLT T1231NL 432238149 428786360 432498908 441500007 446200003 432028918 432498925 428788458

443800019 443801016 754500001 757830252 757840212 757865001 950432801 760925002 133148 ST7010QNL T-1250SCT T3023NL

66010-004LF 203156 68899-002LF 73327-111LF 95672-001LF 95678-001ALF 45-5614-BU DS2174QN+ CPC1465D