

402 0247

## **Tubing and Hoses**

4-28 mm 0/D



Copper tubing to BS 2871 : Part 2 with dimensions generally to table 4

0/D-I/D mm	and the second second	4/2,8	5/3,4	6/4,4	8/6,4	10/8,4	12/9,6	16/13,6	22/19,0	28/25,0
Pressure (ba	r)*	128	ૂં 138 <sub>ાં પ્ર</sub> ા	112 ···	8. <b>81</b> .	84	ر 81 مر	_ 59 ⊊	53/ 34	200 41 No. 1
	Type	29	SO CHANGE	States (X	00000000	00 00100		and the second		
10 m coil	Annealed	CS6004010	CS 6005010	CS 6006010	C20008010	C2 00100				
3 m straight	Annealed						CS 6012003	CS 6016003	CS 6022003	CS 6028003

0/D-I/D mm	4/2,8	5/3,4	6/4,0	8/6,0	10/7,6	12/9,6	16/13,6	22/19,0 28/25,0
Pressure (bar)*	193	208	218	157	,a.1 <b>50</b> % and	122	, <b>89</b> ,	81 <sub>.00 (1</sub> 150 a 62 a
Length Type			Second Control	and only		Marin.		

3 m straight Half hard CS 7004003 CS 7005003 CS 7006003 CS 7008003 CS 7010003 CS 7012003 CS 7016003 CS 7022003 CS 7028003

<sup>\*</sup>Recommended safe working pressure at -200°C to +50°C. For higher temperatures, multiply by factor in table below.

Working temperature	Factor annealed	Half hard
+50°C to + 100°C	0,97	0,95
+100°C to +150°C	0,82	0,88
+150°C to +175°C	0,63	0,54
+175°C to +200°C	0,43	0,29



Bundy tube - Double wall brazed steel tube 3m straight (10ft)


X11.			32.3	
0/D mm	6 .	8	10	12
Pressure (bar)* @ +20°C	300	250	195	160
Length				

BU6306003 BU 6308003 BU 6210003 BU 6212003 3 m straight

\*Maximum working pressure for straight length, non-pulsating pressures, when used with compression tube fittings shown in this catalogue.









## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

## Click to view similar products for norgren manufacturer:

Other Similar products are found below:

8254200.9151.02400 B72G-2GK-AL3-RMN C01470618 C01470828 18-013-989 18-013-990 V61B413A-A213J 100201000 101250828 CS6004010 F72G-2GN-AL3 101470838 8240400.9101.23050 M/58308/01 RT/57220/M/40 18-015-013 F74G-4GN-AP3 8240400.9101.02400 C01251048 RT/57212/M/50 M/3314 101250628 101470818 RT/57220/M/80 150050038 602112128 V62C413A-A213J R07-200-RNKG V60A513A-A213J 101250818 10K510618 S/521 101251028 R72G-2GK-RMN C02260628 C01250838 101470628 C00200400 M/S2 102250628 C01470628 R07-100-RNKG C01470838 08803000000000000 101250838 101470618 18-015-989 101470828 C01251038 18-025-003