

New product in WX family: WXDP 120 Desoldering iron



Finger switch

The vacuum ON/OFF finger switch is located in the ergonomic soft grip.

Fast heat up

The tool reaches operating temperature just in 35 sec. (150°C-350°C) within 20sec..

Safety

The bayonet fitting of the solder cartridge means that it can be changed quickly and easily, without the risk of burns of the operators fingers.



No cleaning

The long length of the XDS nozzle and the disposable solder cartridge prevent the need for cleaning.

Cost saving

A motion sensor in the hand pieces senses when the tool is at rest, immediately after picking up the tool, the motion sensor signals the start of the heating process so that energy is only used when the tool is in use.



XDS Nozzle

Technical Data

Temperature range:	50 - 450°C (150 - 850°F)
Power consumption:	120 W
Heat-up time:	35 sec. (50 - 380°C)
Passende Saugdüsen:	XDS Series
Supply unit:	Weller WX Station
WXDP 120 Desoldering iron:	T0051320199
WXDP Desoldering iron with WDH 70 safety rest:	T0051320299

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [weller manufacturer](#):

Other Similar products are found below :

[SAS3210TRB](#) [0052918099](#) [0058736839](#) [5BSA](#) [0051612499](#) [005 32 566 99](#) [0054465399](#) [PTH6](#) [HE35](#) [SP40NKUS](#) [T0051388399](#)
[T0051388799](#) [T0051516199](#) [T0052920699](#) [T0053421699](#) [T0053427699](#) [T0053434699](#) [T0053638699](#) [T0058732869](#) [PPT2](#) [PSI5](#) [HEW60P](#)
[LT4X](#) [CT6E7](#) [D550](#) [D650](#) [WPA2](#) [DS209](#) [DS227](#) [RT6](#) [RTW3MS](#) [EPH101](#) [T0051390699](#) [T0051612199](#) [T0051628899](#) [T0052704299](#)
[T0052920599](#) [T0052922299](#) [T0053422699](#) [T0053429699](#) [T0053657199](#) [T0054480299](#) [T0056104699N](#) [TC208](#) [WTA3](#) [WSTA6](#) [WDH60](#)
[WPT15](#) [T0058764726](#) [51617799](#)