Batteries

DATA SHEET

Description : Flat Lithium Battery

Chemical system : Lithium Manganese Dioxide

: 3 Volts Nominal voltage

Nominal capacity : 300mAh@6.8kΩ to 2.5V

: ø24.5 x 3.0mm **Dimensions**

Shelf life : 5 years at room temperature

Average weight : 4 grams


Application : Watch, calculator, camera and

memory back up


Cross References:

IEC	JIS	Eveready	Varta	Duracell
CR2430	CR2430	ECR2430	CR2430	DL2430


Discharge Characteristics on Load








Discharge Load vs. Discharge Capacity




www.gpbatteries.com


Model No.: CR2430






Discharge Characteristics on Pulse Load (Discharge depth 40%)





The information (subject to change without prior notice) contained in this document is for reference only and should not be used as a basis for product guarantee or warranty. For applications other than those described here, please consult your nearest GP Sales and Marketing Office or Distributors.

Manufacturer reserves the right to alter or amend the design, model and specification without prior notice. Copyright@ GPI International Ltd. - All rights reserved



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for pro elec manufacturer:

Other Similar products are found below:

```
PE01004 LMP-G60BCW07-02B PSG91116 PEL00582 PEL00418 PEL00217 PEL00156 PEL00170 PEL00175 PEL00251 PE01003

PEL00581 PEL00346 PEL00350 PEL00291 PEL00153 PEL00061 PEL00199 PEL00371 PE01005 PEL00414 JR60431 PEL00417

PEL00091 PEL00075 PEL00222 PEL00144 PEL00227 PEL00151 PEL00154 PEL00281 LMP-G60E27W07-02B PSG91112 2213U 2.4A

PEL00093 PEL00223 PEL00165 PEL00051 HS-5626 1518C WHT PEL00067 PEL00221 PEL00225 PEL00157 PEL00162 PEL00163

PEL00231 PE000031 PC2213U PEL00347
```