DATA SHEET

KS07 SPRUNG SHIELD SURFACE PROBE TYPE 'K'

SPRUNG SHIELD SURFACE PROBE - Type 'K'

Description

This probe uses the straight handle for fine control. The probe is designed for the measurement of surface temperatures with wide temperature range.

Construction

Surface probe with sprung tip with thermocouple sensor attached with draught shield: Stainless Steel 316 (Food Grade)

2M curly polyurethane cable with moulded connector.

Sensor Features

TOTAL ENCAPSULATION TECHNIQUE FOR MAXIMUM STRENGTH AND DURABILITY.

This results in a solid handle as opposed to a hollow handle. This is particularly important as there is often damage to the handles caused by excess heat. With a hollow handle it is possible to puncture the outer plastic and damage the sensor irreparably.

WATERPROOF HANDLE

Due to the total encapsulation method used, all TME probe handles are completely waterproof.

TOUGH POLYURETHANE CABLE

- Polyurethane cables are used in place of the standard polyurethane for the following reasons :-
- Greater retractability
- Enhanced memory of it's curl
- Non-Toxic
- Greater mechanical strength for durability
- 12 X 0.2mm wires used internally for greater strength.
- PTFE inner insulation for strength and retractability.

HIGH ACCURACY THERMOCOUPLE MATERIAL THROUGHOUT

Type 'K' Thermocouple : Class I (±01.5°C ±0.25%)

POLYPROPYLENE HANDLES

Polypropylene is an extremely tough and durable material, commonly used for milk crates, it has good low temperature performance and a relatively high melt temperature. It performs exceptionally well under chemical attack.

WIDE AMBIENT TEMPERATURE SPECIFICATION : -30 TO 50 °C
 ► TIME RESPONSE (96% of valueon clean metal) : 3.0 Secs
 ► MEASUREMENT RANGE : -200 TO 400 °C

Cross-reference for compatible instruments

Suitable instruments for use with this probe

TME PART No	DESCRIPTION	APPLICATION
MM2000	SINGLE INPUT INSTRUMENT	HIGH ACCURACY TEMPERATURE MEASUREMENT
MM2010	MAX / MIN HOLD INSTRUMENT	HIGH ACCURACY INSTRUMENT WITH MAX, MIN AND HOLD FEATURES
MM2020	DIFFERENTIAL INSTRUMENT	DUAL INPUT INSTRUMENT FOR DIFFERENTIAL MEASUREMENTS
MM2030	THERMOCOUPLE SIMULATOR	HIGH ACCURACY SIMULATOR WITH MEASUREMENT FACILITY

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Board Mount Temperature Sensors category:

Click to view products by TME manufacturer:

Other Similar products are found below:

5962-8757102XA 66F115 MCP9808-EMS MCP98242T-BEMNY MCP9843T-BEMC EMC1063-1-ACZL-TR NCT218FCT2G
O53GAB175A-160Y OH10/62,112 3610085020002 389049M9527 TC622EAT TC6501P095VCTTR TC6501P105VCTTR
TC6501P125VCTTR MCP9802A0T-M/OT MCP9803T-M/SN MCP9843-BEST TC6501P115VCTTR TC6502P065VCTTR
ADM1023ARQZ-REEL ADM1024ARUZ-REEL ADM1032ARMZ-1RL AT30TS74-U1FMBB-T AT30TS74-U1FMAB-T AT30TS74-U1FMCB-T AT30TS74-U1FMCB-T ADT7483AARQZ-RL ADT7481ARMZ-REEL ADT7463ARQZ-REEL MCP98243T-BEMNY
MCP98243T-BE/MC 66L080-0226 MAX31820MCR+T MAX1452CAEC8H DS1780E TMP05BKSZ-REEL7 5962-8757103XA WTK-14-36/N E52-CA6D-N 4M MCP98244T-BEMNY MCP9802A5T-MOT MAX6581TG9A+T DS75S-C11+T&R S-58LM20A-I4T1U
MAX6501UKP120+T MCP98243T-BE/ST AT30TS01-MAA5M-T NCT375DR2G DS18S20-SL+T&R