

CURRENT MEASUREMENT PROBES

Flexible Current Probes

AmpFlex® Flexible Current Probes

Flexible AC current probe composed of a flexible sensor and an electronic module



Model	Measurement Range	Output	Sensor Length inches (mm*)	Max Conductor Size inches (mm*)	Catalog No.
300-24-2-10	30/300A	100/10mV/A	24 (610)	8 (190)	2112.88
1000-24-1-1	1000A	1mV/A	24 (610)	8 (190)	2112.39
1000-24-2-1	100/1000A	10/1mV/A	24 (610)	8 (190)	2112.98
1000-36-2-1	100/1000A	10/1mV/A	36 (910)	11 (290)	2113.00
3000-24-2-0.3	300/3000A	3.3/0.3mV/A	24 (610)	8 (190)	2114.87
3000-24-1-1	3000A	1mV/A	24 (610)	8 (190)	2112.46
3000-36-1-1	3000A	1mV/A	36 (910)	11 (290)	2112.48
3000-24-2-1	300/3000A	10/1mV/A	24 (610)	8 (190)	2113.05
3000-36-2-1	300/3000A	10/1mV/A	36 (910)	11 (290)	2112.00
3000-48-2-1	300/3000A	10/1mV/A	48 (1220)	15 (390)	2112.01
6000-36-2-0.1	600/6000A	1/0.1mV/A	36 (910)	11 (290)	2113.21
30000-24-2-0.1	3000/30,000A	1/0.1mV/A	24 (610)	8 (190)	2113.33

*Dimensions rounded off

**Consult factory for list and NIST Calibration prices

Consult factory for special offers and ranges/lengths not shown here.

Note: Output is safety shrouded 4mm male banana plug

FEATURES

- Models ranging from 0.5 to 30,000Arms
- Accuracy 1% of Reading
- TRMS measurements when connected to a TRMS instrument
- No core saturation or damage if overloaded
- Overrange LED for measurement circuitry
- Waterproof sensor
- 9V Alkaline battery, provides typical 150 hours of continuous operation (battery included)
- Shape memory for custom pre-shaping of sensor before use (no drooping)
- Very high frequency response
- Low phase shift for power measurements of <math><1.3^\circ</math>, 0.7° typical
- Insensitive to DC, measures only AC component on DC + AC signals
- Excellent linearity
- Lightweight

FlexProbe® Flexible Current Probe Model 24-3001

Low cost AC current measurement probe designed to plug into digital multimeters, oscilloscopes and power recorders



ACCESSORIES

Banana (female)
BNC (male) (XM-BB)

Catalog #2118.46
(optional for AmpFlex® & FlexProbe® Flexible Current Probes)



SPECIFICATIONS

MODEL	24-3001
ELECTRICAL	
Current Range	300/3000Aac
Output Signal	mV output (4000mV peak max)
Three Position Slide Switch	10mV/A 1mV/A ON/OFF
Power Source	9V Alkaline battery (included)
MECHANICAL	
Maximum Conductor Size	7.6" (193mm)
Sensor Length	24" ± 1" (610mm ± 25.4mm)
Cable Length	6.5 ft (2m)
Output Connection	Double insulated 14" (355mm) lead with safety banana plugs



FEATURES

- 24" flexible sensor fits around conductors up to 7.6" in diameter
- Dual measurement ranges of 300A and 3000Aac
- Read amperage directly on DMM display
- mV output directly proportional to the AC current measured
- Output is 10mV/A on 300A range and 1mV/A on 3000A range
- Accuracy of 1% of Reading ± 500mA
- 4% influence of conductor position in jaw
- Up to 150 hours of battery life
- Dual banana plug termination for direct input into DMMs
- Flashing LED low battery indicator
- 9V Alkaline battery, provides typical 150 hours of continuous operation (battery included)

CATALOG NO.	DESCRIPTION
2120.81	FlexProbe® Model 24-3001 (300/3000Aac, 24", 10mV/A/1mV/A, Lead)
Accessories (Optional)	
2118.46	Adapter – Banana (Female) – BNC (Male) (XM-BB)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [aemc manufacturer](#):

Other Similar products are found below :

[2118.79](#) [2118.82](#) [6417](#) [SL261](#) [MN261](#) [MN106](#) [2119.02](#) [MD301](#) [SR601](#) [MN103](#) [1017.84](#) [6610](#) [SR752](#) [MS3474W10-6P](#) [MS3456L16-10SY-LC](#) [BR07](#) [2118.73](#) [MS3475W14-4S-LC](#) [MS3456L20-14SX-LC](#) [MS3450W22-2SY-LC](#) [MS3475W14-4SW](#) [D38999/26WD5PN](#)