Item # 41DH12, Air-Seal Foot Switch



Air-Seal Foot Switch

The Air-Seal foot switch offers the benefit of isolating the electrically live snap switch from the floor, which also offers environmental protection. Other benefits include long trouble free life and application versatility. The Air-Seal foot switch series combines a foot operated air bulb mounted in our strong, steel Compact housing and a remotely locates air operated electric snap switch. The Air-Seal is available in either momentary or maintained versions, with SPDT snap switch. A 10 foot 1/8" ID PVC tubing connects the foot pedal to the remote airswitch, which is equipped with a 9/16" UNF bulkhead mount. The tubing is connected at the foot switch end using a molded on strain relief grommet providing superior pull out protection.

SPECIFICATIONS

Description	Maintained
Circuit	SPDT
Form	С
Operating Temperature Range	10 to 120 °F</th></tr><tr><th>Electrical Rating</th><th>20 A 125-250 VAC 1 H.P. 125 VAC 2 H.P. 250 VAC</th></tr><tr><th>Standards</th><th>EN 60529 Degree of Protection IPXX Master Actuator, EN 60529 Degree of Protection IP00 Snap Switch</th></tr><tr><th>Size</th><th>2 7/8 x 4 1/2 x 1 1/8 Inch</th></tr><tr><th>Weight</th><th>1/2 lbs</th></tr><tr><th>Note</th><th>The operating temperature range will vary with different lengths of tubing. Please consult the factory for details.</th></tr></tbody></table>

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for 9V Battery Snaps & Contacts category:

Click to view products by Linemaster manufacturer:

Other Similar products are found below :

 139B
 173P
 266
 491-SC36
 642-S
 1295
 12BC2202-GR
 2238
 2241
 2242
 2243
 227
 236
 237
 2410.0301-01
 262
 270
 271
 121-0626/I-GR

 121-0426/IM-GR
 121-0626/T-GR
 121-0826/T-GR
 121-1026/I-GR
 12BH617T-GR
 123-5025-GR
 12BC269-GR
 12BH615D-GR
 121

 0624/O-GR
 GEM-V36
 531-SWHOX
 971-SB
 T-91-SC3
 632-DA
 634-DA
 636-S
 632-S
 632S TWIN DIVIDER
 3C-30A2-S
 3B-30A2-S

 534-SS
 491-S
 L-2-S
 971-SO
 972-S
 606-1300-011
 606-1800-012
 616-1800-247
 6254-OB
 6289-PP
 6289-CC