Indoor Break Glass Call Points





- $\begin{tabular}{ll} \bullet & Indoor surface mounting call points available as 470Ω or 680Ω versions \\ \bullet & Unique 'Plug & Play' installation concept \\ \end{tabular}$

- Anti-tamper facility
 Enhanced aesthetics
 Fully approved to the latest standards, including EN54-11 and LPCB 166b/39 & 166b/40

 Residence of the latest standards including EN54-11 and LPCB 166b/39 & 166b/40
- Backward compatibility
 Additional transparent hinged covers available for extra protection, ideal for schools etc
- Operating Temperature: -40 to +55°C
 Voltage: 24V DC
 Dimensions (WxHxD): 89 x 93 x 58.5mm

416661.416656

		Price Each
Description	Order Code	
Call Point 470Ω	100-4630	
Call Point 680Ω	100-4631	
Accessories		
Hinged Cover	100-4632	
Hinged Cover Seals (Pk5)	100-4634	
Spare Glass (Pk10)	890-1970	
Spare Keys (Pk10)	100-4635	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Tactile Switches category:

Click to view products by KAC manufacturer:

Other Similar products are found below:

KMR633NG LFG 5GTH9202242 6426-201-11343 MJ1226 MJTP1109B MJTP1138EAUTR MJTP1230BL MJTPSHW GS6.90F300QP 11977223-0 1-1977120-4 ADTSA62NV ADTSA62RV ADTSA63KV ADTSA644NV ADTSM24NVTR ADTSMW66NV ADTSMW67RV

ATM533VTR 1571300-3 B3F-3123 B3F-6055A B3F-B32-01-KIT 1977177-8 1977266-1 2-1977223-4 2-1977223-7 ADTS644KV

ADTSA61RV ADTSA62KV ADTSA63NV ADTSA63RV ADTSA65NV ADTSM21NSVTR ADTSM25RVTR ADTSM31RVTR

ADTSM32NVTR ADTSM61YVTR ADTSM63SVTR ADTSM644KVTR ADTSMW64RV ADTSMW69NV FSMRA4JHA04

GS4.70F300QP D38999/20JJ37SA TL1105B TL1105J ATH447K2Q ATM534VTR MJ1215