

## Features

- complete probe set for measurements up to 100MHz
- attenuation: 1:1 or 1:10

## Specifications

- position x1:
  - attenuation: 1:1
  - bandwidth: DC to 60MHz
  - rise time: 5.8ns
  - input resistance: 1Mohm (input resistance scope)
  - input capacitance: 90pF + cap. scope
  - working voltage: 600Vdc incl. peak AC derating with frequency
  - position REF: tip disconnected, scope input at ground
- position x10:
  - attenuation: 1:10
  - bandwidth: DC to 100MHz
  - rise time: 2.8ns
  - input resistance: 10Mohm (if scope input = 1Mohm)
  - input capacitance: 16pF approx.
  - working voltage: 600Vdc incl. peak AC derating with frequency
  - compensation range: 10 to 35pF
- cable length: 1.4m



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [unbranded manufacturer](#):*

Other Similar products are found below :

[BL200H](#) [396.357](#) [AC-9](#) [MODEL 1000](#) [MPT-251](#) [62845](#) [20844](#) [BP00001/36 ROLLS](#) [A1319](#) [MA0510BIM-3PIN](#) [HT-328](#) [OL1000](#) [JR9235-1M BLUE](#) [195.303](#) [SB344](#) [JR9021-2M](#) [029-1039](#) [F2](#) [WATERPROOF CASE 24"](#) [CS-47](#) [MA0410B1M](#) [10HA084](#) [26.514.5026.50](#) [JR9235-1.5M RED](#) [029-0058](#) [KLEIN TOOLS SCREWDRIVER 4-IN-1](#) [JR9235-1M YELLOW](#) [S2G](#) [029-1044](#) [JR9235-0.5M YELLOW](#) [199.370](#) [WATERPROOF CASE 10.5"](#) [029-0054](#) [JR9235-0.5M BLUE](#) [JR9235-0.5M GREEN](#) [JR9235-0.5M RED](#) [WATERPROOF CASE 18"](#) [JR9235-1M RED](#) [JR9235-1M BLACK](#) [JR8001/0.5M BLACK](#) [029-1022](#) [029-0057](#) [15X24X24" SQUARE BIN LINERS, 200 PER BOX](#)