CAMBLOCK PLUS


CTBP0508

5.08mm Pitch Low Profile Rising Clamp Terminal Blocks


- 2 & 3 pole double interlocking mechanism for increased strength
- Moulded in green UL94-V0 flame retardant PA66
- Professional rising clamp terminals
- 1.5mm² (26-16AWG)
- · Guided pin alignment
- · Captive screw
- approved




SPECIFICATION		
Rating	8A/300V	
Insulation resistance	500MΩ/500V	
Withstand Voltage	AC2000V/1min	
Contact Resistance	20mΩ (max)	
Working Temperature	-40°C to 105+°C	
Mouldings	UL94-V0 Flame retardant PA66	
Pin/Terminal	Tin plated brass	
Rising Clamp	Brass, nickel plated	
Screw/Torque	M2.5 Steel, zinc plated 0.4Nm	
Recommended PCB hole size	ø1.3mm	



TYPE NO.	POLES	LENGTH
CTBP0508/2	2	10.16mm
CTBP0508/3	3	15.24mm
CTBP0508/4	4	20.32mm
CTBP0508/5	5	25.4mm
CTBP0508/6	6	30.48mm
CTBP0508/7	7	35.56mm
CTBP0508/8	8	40.64mm
CTBP0508/9	9	45.72mm
CTBP0508/10	10	50.8mm
CTBP0508/11	11	55.88mm
CTBP0508/12	12	60.96mm





X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for camden manufacturer:

Other Similar products are found below:

412689X CTBP92VE/12R CTBP9350/12 IND515205-240-T/GRN IND515205-240-T/RD IND5032405-240-T/GRN CE10.00.EI
C192SHAND CNMB/6ST/2 CNMB/4ST/2 CSACST004 CTBP9200/9 CIME/M/BE2250SS CHH64E1BL CIM/15W-DMFS CHHBAT2GY
CFTBN/2 CCB2S1/04 CHDX6-221C CHDX8-224 CHDASMP29 CHDASMP34 CHDX810DD CHDX811DD CCTTM40LR
CTBP92VJ/5S CTBP92VJ/8R CTSN431/12/M CTSN433/12/M CUABOX006 CE10.00.FM CBRPH-BLK BIM2003/13-WH/WH
RX2008/S-5-WH CBARD-CAR CRDCG0007 CNMB/4/KIT CTB5050/5 CTBP92HE/11 CTBP9358/10AO CHH66C2GY CHH456PBK
CHH451ABK CIM/9W-DMFS CIM/25W-DMFS RTM5006/16-NC-BLK IND5032405-125-T/AMB CCB1S1/03 CCD2S1/04 CCE1S1/05