



PRH.N0.3GL.AC65GZ

MECHANICAL DETAILS

Shell Style Model PR* : Free receptacle with cable collet and nut for fitting a bend relief


Keying 2 keys (beta=170; plug: female contacts, receptacle: male contacts)

Housing Material PSU (Polysulfone), gray

Cable Fixing 5.3 - 6.5 mm

Variant 2 G : Gray collet nut for bend relief

	Col	Col	Col	Col	Col	Col	Col	Col
Mm.								
In.								



PERFORMANCE DETAIL

Insert 1P.N03 : 3 High Voltage

Insulator

Specifications

Note: Increased creepage distance, pin 3 longer

Contact Type: Solder

Max. Matings: 2000

Contact Dia.: 0.9 mm (0.04in)

Bucket Dia.: 1.4 mm (0.055in)

Max. Solid 1 mm² (AWG 18)

Max. Stranded 1 mm² (AWG 18)

R (max): 4.5 mOhm

Cable type: |A|H07



OTHER CHARACTERISTICS

Shell Style/Model Libellé

F ret (min): 50 N

F ret (max): 150 N

IP Rating 50



Available Download

[P_series_catalog.pdf](#)

Related links

- [Contact](#)
- [Quote Request](#)
- [Catalogs Downloads](#)
- [Catalogs Requests](#)
- [Sample Request](#)
- [3D drawings](#)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [redel](#) manufacturer:

Other Similar products are found below :

[PKG.M0.2GL.LN](#) [PAG.M0.8GL.AC52G](#) [PAG.M0.5GL.AC52G](#) [PAG.M0.5GL.AC65N](#) [PAH.N0.3GL.LC65GZ](#) [PAG.M0.4GL.AC39G](#)

[PKG.M0.5GL.LG](#) [PKG.M0.2GL.LG](#) [PKH.N0.3GL.AG](#) [PAG.M0.2GL.AC52N](#) [PAG.M0.2GL.AC39N](#)