

Data Sheet

Weller part no. T0053368870

Description: High power station for all through hole and surface mount rework, type WR3000M ER

Comprises:

- WR3M power unit
- DSX 120 desoldering iron 120 W rated
- WDH 30 safety rest
- WP 120 soldering iron 120 W rated
- WDH 10 safety rest
- HAP 200 hot air pencil 200 W rated
- WDH 30 Safety rest

Supply voltage 230V 50Hz

Tool operating voltages 24V 50Hz (all tools)

Mains lead UK + Euro

Power rating 360W

Protection Class 1

Temperature range

- WP 120 soldering iron 50 C – 450 C heat up time to 350C – ca 14 sec
- DSX 120 desoldering iron 100 C – 450 C heat up time to 350C – ca 35sec
- HAP 200 hot air pencil 50 C – 550 C

Hot air delivery variable 0 – 15 l/min

Temperature accuracy

- Solder / Desolder tools, +/- 9C
- Hot air pencil, +/- 30C

Temperature display Digital red LCD

Temperature set up /down push buttons

USB interface for firmware downloads

ESD safe

Compliance IPC- J001

Consumables: soldering iron tips XT series

Desoldering nozzles XDS series

Hot air nozzles flat, round, DIL, and Quad

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [weller](#) manufacturer:

Other Similar products are found below :

[SAS3210TRB](#) [0052918099](#) [0058736839](#) [5BSA](#) [0051612499](#) [005 32 566 99](#) [0054465399](#) [PTH6](#) [HE35](#) [SP40NKUS](#) [T0051388399](#)
[T0051388799](#) [T0051516199](#) [T0052920699](#) [T0053421699](#) [T0053427699](#) [T0053434699](#) [T0053638699](#) [T0058732869](#) [PPT2](#) [PSI5](#) [HEW60P](#)
[LT4X](#) [CT6E7](#) [D550](#) [D650](#) [WPA2](#) [DS209](#) [DS227](#) [RT6](#) [RTW3MS](#) [EPH101](#) [T0051390699](#) [T0051612199](#) [T0051628899](#) [T0052704299](#)
[T0052920599](#) [T0052922299](#) [T0053422699](#) [T0053429699](#) [T0053657199](#) [T0054480299](#) [T0056104699N](#) [TC208](#) [WTA3](#) [WSTA6](#) [WDH60](#)
[WPT15](#) [WEL.PT-F8](#) [T0058764726](#)