	Hear ((1.3c (0.1c	ce of .5" m) or .375" m) D-holes	A complete selection of pane designers. Each panel featur fast and simple way to ide .060 inch (16 ga) cold-rolle optional cable management to tie off cable bundles and Type F, RCA, HDMI or DVI sty	res a numerical legend b ntify ports for their equi d steel and finished with bracket kit used on the re I prevent connector fatig	elow each po ipment. Our h a durable l ear of the pan	ort. This allo panels are black powde el gives a se	ws users a made with er coat. An ecure place
	-		Optional cable management bracket					+1
	-		3.48 (8.8cm)			000	00	
	6.6				• • • • • • • • • • • • • • • • • • •	000 	© © (• Lecom
- 1		Numerical leg for each port	jend ⊢		19.00(48.3cm)			1
Leom 6	69	G	1.73 (4.4cm))		000	0 0 () scom ()
17	10							
Α	В	C	D	Ε	F		G]
50 Ohm BNC	Best Seller 75 Ohm BNC	Auto-Terminating	Type F	RCA	HDMI		DV	
Insulated	Insulated	50 Ohm BNC						
Item #	Code Descri Coaxial Rack Panels			Color	1-9	10-24	25-99	100-249
PR175-16BLK PR175-16CMB	N/A 1.75" (4.4cm) Panel, 16 0.5" (1.3cm) D-Hole 4.4cm) Panel, 16 0.5" (1.3cm) D-Hole		Black Black	24.95 37.95	24.45 37.19	23.95 36.43	23.45 35.67
PR35-32BLK PR35-32CMB		8.9cm) Panel, 32 0.5" (1.3cm) D-Hole 8.9cm) Panel, 32 0.5" (1.3cm) D-Hole		Black Black	29.95 49.95	29.35 45.95	28.75 41.96	28.15 37.96
PR175B16BLK PR35B32BLK		4.4cm) Panel, 16 BNC Couplers, 50 Ol 8.9cm) Panel, 32 BNC Couplers, 50 Ol		Black Black	99.95 179.95	91.95 165.55	83.96 151.16	75.96 136.76
PR175B1675BLK PR35B3275BLK		4.4cm) Panel, 16 BNC Couplers, 75 Ol 8.9cm) Panel, 32 BNC Couplers, 75 Ol		Black Black	109.95 209.95	101.15 193.15	92.36 176.36	83.56 159.56
PR175B16CMB PR35B32CMB		4.4cm) Panel, 16 BNC Couplers, Insula 8.9cm) Panel, 32 BNC Couplers, Insula			119.95 199.95	110.35 183.95	100.76 167.96	91.16 151.96
PR175BX16GBLK PR35BX32GBLK		4.4cm) Panel, 16 BNC Auto-Terminatir 8.9cm) Panel, 32 BNC Auto-Terminatir		Black Black	129.00 229.95	118.68 211.55	108.36 193.16	98.04 174.76
PR175F16 PR35F32		4.4cm) Panel, 16 Type F Couplers, Ins 8.9cm) Panel, 32 Type F Couplers, Ins		Black Black	79.95 99.95	73.55 91.95	67.16 83.96	60.76 75.96
	Audio/Video Rack Pa							
PR175RCA16 PR35RCA32		4.4cm) Panel, 16 RCA Couplers, Grour 8.9cm) Panel, 32 RCA Couplers, Grour		Black Black	89.95 149.95	88.15 146.95	86.35 143.95	84.55 140.95
PR175HDMI16B PR35HDMI32B PR35DVIFB	F 3.50" (4.4cm) Panel, 16 HDMI Female Couple 8.9cm) Panel, 32 HDMI Female Couple 8.9cm) Panel, 16 DVI Female Adapters	ers	Black Black Black	198.98 298.98 159.00	183.06 275.06 155.82	167.14 251.14 152.64	151.22 227.22 149.46
PR-CMB		Management Bracket Kit for most L-co tains: (Qty: 6) Extension Brackets, (Qty			24.95	24.45	23.95	23.45

What is Impedance?

Impedance is a measurement of opposition to the flow of current within a cable. Two of the most common impedance values used in coaxial cable are 50 Ohms primarily used for data transmission and 75 Ohms primarily used for video transmission. In twisted pair cable, common impedance values are 100 and 120 Ohms.

Custom design and manufacturing capabilities Our product design process takes you from concept to production. <u>L-com.com/Custom</u>



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for 1-com manufacturer:

Other Similar products are found below :

FOA-550A UMC-201 CSMN50MF-5 CSMNB15MF-15 TRD815RA2BL-5 CA3A-90DA-1M CTLF3VGAMM-20 HDCAMM-3 U3A00014-03M ECF-SK-25 CSMT15MF-10 CSMT15MM-15 CSMT15MM-25 CSPL15MF-50 CSPL25MF-25 CSPL9MF-10 CSPL9MF-5 CSPL25MF-5 CSPL25MF-2.5 AL-IPEPS NB201611-10F-1 TDG1026KC5-MNL NB121005-10F TRD855SRA6DBL-10M TRD855SRA7DBL-1M TRD855SRA7DBL-10M PR175SCDLCQ24 TRG508-T4T-3M TRA5261-15F TRA5261S-1F TRA6261-1F USBBFT DGB25M CASATAL-18 CSM25MM-10 CSM37MF-10 CSUSB-100 CA3A-90RA-1M CA3A-90RMICB-1M U2A00003-3M U3A00003-05M U2A00008-12I U3A00007-075M U3A00007-1M CSMT15MF-5 CSMT15MM-50 CSPL15MF-25 LPXT-WP-PMT CSMT15MF-50 CSPL15MF-2.5