

This document was generated on 12/17/2012 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

| Status: Overview: Description: | 48025-2090 Active Magnetic Modular Jacks Modular Jack, Right Ang Ground Shield, Lead-Fre | gle, 10/100, with Integrated Magnetic and LED, 8/8, without | |
|--|--|--|---|
| Documents: <u>3D Model</u> Drawing (PDF) Product Specification P | <u>S-48025-005 (PDF)</u> | Test Summary TS-48025-010 (PDF) RoHS Certificate of Compliance (PDF) | - image - Reference only |
| Agency Certification | on | LR19980 | EU RoHS China RoHS |
| UL General Product Family Series Comments | | E107635 Modular Jacks/Plugs <u>48025</u> With LED Without Ground Shield | ELV and RoHS Compliant REACH SVHC Not Reviewed Low-Halogen Status Not Reviewed |
| Component Type Magnetic Overview Performance Category Power over Ethernet (P | oE) | PCB Jack Yes <u>Magnetic Modular Jacks</u> 5, 5e Non-PoE | Need more information on product environmental compliance? Email productcompliance@molex.com For a multiple part number RoHS Certificate |
| Product Name UPC Physical | | Magnetic Jack 822350848008 | Compliance, <u>click here</u> Please visit the <u>Contact Us</u> section for any non-product compliance questions. |
| Boot Color Color - Resin Durability (mating cycle Flammability Inverted / Top Latch Jack Height | s max) | N/A Black 750 94V-0 Yes 12.60mm | Search Parts in this Series 48025Series |
| Keying to Mating Part Lightpipes/LEDs Material - Metal Material - Plating Matin Material - Plating Termi Material - Resin | - | Yes LEDs Phosphor Bronze Gold Tin Nylon | Mates With FCC 68 Plugs |
| Net Weight Orientation PCB Locator PCB Retention PCB Thickness - Recor | nmended | 4.980/g Right Angle (Side Entry) Yes Yes 1.60mm | |
| Packaging Type Pitch - Mating Interface Pitch - Termination Inte Ports | rface | Tray 1.02mm 1.27mm 1 | |
| Positions / Loaded Con Surface Mount Compat Temperature Range - C Termination Interface: S Waterproof / Dustproof | ible (SMC) Operating | 8/8 No -40°C to +70°C Through Hole No | |

Electrical

Current - Maximum per Contact Grounding to PCB Grounding to Panel Shielded Voltage - Maximum 1.5A Yes No Panel Ground Tabs Yes 150V AC (RMS)

Material Info

Reference - Drawing Numbers

| Product Specification | |
|-----------------------|--|
| Sales Drawing | |
| Test Summary | |

PS-48025-005 SD-48025-010 TS-48025-010

This document was generated on 12/17/2012 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 RJE231881317T
 MP1010RX-1000
 MP44RX-1000
 GAX-3-66
 GAX-8-62
 93606-0253
 GD-A-44
 GDCX-PA-66-50
 GDCX-PN-64
 GDCX-PN-64

 PN-66
 GDCX-PN-66-50
 GDLX-A-66
 GDLX-A-88
 GDLX-N-66
 GDLX-S-88K
 GDTX-S-88-50
 GDX-PA-1010
 GLX-N-1010M-BLK

 GLX-N-44M
 GLX-S-88M-BLK
 GMX-N-1010
 GMX-S-1010
 GMX-S-66
 GMX-SMT2-N-1010
 GMX-SMT2-N-64-50
 GMX-SMT2-S6-88

 GMX-SMT4-N-88
 GPX-2-64
 GRT1-BT1-5
 GSGX-N-2-88
 GSX-NS2-88-3.05
 GSX-NS2-88-3.05-50
 GSX-NS-88-3.05-30
 GSX-NS-88-3.05-30

 3.05-50
 GSX-NS-88-3.68
 1-1775629-2
 GWLX-S-88-GR
 GWLX-S9-88-YG
 1300500326
 1300500227
 1300530003
 1300570002
 1324640-4

 RJ11FTVC2G
 RJ11FTVC2N
 RJFTVX2SA1G
 132764-001
 1400000
 1413176
 1413235