



## Specifications

<b>Rp-p Top Colour Layer:</b>	10E6 – 10E8 ohms meets EN 61340-5-1
<b>Rp-p Bottom Black Layer:</b>	10E5 ohms meets EN 61340-5-1
<b>Rg:</b>	10E6 to 5 x 10E7 ohms meets EN 61340-5-1
<b>Abrasion (ISO 4649, method A):</b>	less than 200E3 mm
<b>Chemical (EN 423):</b>	resistant to chemical agents normally used for maintenance
<b>Thickness:</b>	2mm (±5%)
<b>Hardness (ISO 7619):</b>	75 ± 5 shore A
<b>Weight:</b>	2.7 kg/m <sup>2</sup>
<b>Colours:</b>	light blue, light grey, beige, green

- Two-layer, static dissipative rubber
- Solder iron resistant and withstands most chemicals
- Mats supplied with four 10mm studs
- Easy to clean
- Low reflecting
- Ideal mat to use with constant monitors

Item	Description
<a href="#">228141</a>	Mat, 0.9 x 0.6m, Blue
<a href="#">228151</a>	Mat, 0.9 x 0.6m, Grey
<a href="#">228157</a>	Mat, 0.9 x 0.6m, Green
<a href="#">228156</a>	Mat, 0.9 x 0.6m, Beige
<a href="#">228116</a>	Mat, 1.2 x 0.6m, Blue
<a href="#">228121</a>	Mat, 1.2 x 0.6m, Green
<a href="#">228126</a>	Mat, 1.2 x 0.6m, Grey
<a href="#">228131</a>	Mat, 1.2 x 0.6m, Beige

Item	Description
<a href="#">228071</a>	Roll, 1.0m x 1 linear m, Grey
<a href="#">228072</a>	Roll, 1.0m x 1 linear m, Blue
<a href="#">228073</a>	Roll, 1.0m x 1 linear m, Beige
<a href="#">228074</a>	Roll, 1.0m x 1 linear m, Green
<a href="#">228076</a>	Roll, 1.22m x 1 linear m, Blue
<a href="#">228091</a>	Roll, 1.22m x 1 linear m, Green
<a href="#">228096</a>	Roll, 1.22m x 1 linear m, Grey
<a href="#">228106</a>	Roll, 1.22m x 1 linear m, Beige

Item	Description
<a href="#">228246</a>	Roll, 1.22 x 10m, Blue
<a href="#">228251</a>	Roll, 1.22 x 10m, Green
<a href="#">228256</a>	Roll, 1.22 x 10m, Grey
<a href="#">228261</a>	Roll, 1.22 x 10m, Beige
<a href="#">228241</a>	Roll, 1.0 x 10m, Grey
<a href="#">228242</a>	Roll, 1.0 x 10m, Blue
<a href="#">228243</a>	Roll, 1.0 x 10m, Beige
<a href="#">228244</a>	Roll, 1.0 x 10m, Green

EN 61340-5-1 paragraph 5.2.2 Working surfaces and storage racks  
 “All working surfaces and storage racks on which unprotected ESDS may be placed shall be capable of being connected to EPA ground and shall have a point-to-point resistance and resistance to EPA ground in accordance with table 1 (Rp greater or equal to 1 x 10E4, less than or equal to 1 x 10E9 ohms, and Rg greater or equal to 7,5 x 10E5 to less than or equal to 1 x 10E9 ohms).”

Tolerance: 5mm±

Specifications and procedures subject to change without notice.

# Vermason

## Rubber Bench Matting 2mm

VERMASON LTD.  
 UNIT C, 4TH DIMENSION, FOURTH AVENUE, LETCHWORTH,  
 HERTS, SG6 2TD UK  
 PHONE: +44 (0) 1462-672005, FAX: +44 (0) 1462-670440  
 E-MAIL: [Service@Vermason.co.uk](mailto:Service@Vermason.co.uk), INTERNET: [Vermason.co.uk](http://Vermason.co.uk)

**Drawing Number**  
 228071

**DATE:**  
 June 2010

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [AntiStatic Control Products](#) category:*

*Click to view products by [Vermason](#) manufacturer:*

Other Similar products are found below :

[13505](#) [13870](#) [14404](#) [20-053-0017](#) [2229](#) [2231](#) [3039](#) [37061](#) [39792](#) [42470](#) [XON-ASB4X30](#) [XON-ASB4X6](#) [XON-ASB6X30](#) [09813](#) [09857](#)  
[XON-ASB8X10](#) [XON-ASB6X10](#) [19695](#) [09037](#) [68101](#) [68103](#) [73741](#) [13515](#) [13869](#) [13868](#) [13485](#) [13457](#) [13245](#) [13332](#) [13205](#) [13135](#) [91070](#)  
[8031](#) [8523](#) [13080](#) [13215](#) [157](#) [ROLL BEIGE 1.0](#) [VERAX1R-300R](#) [17260](#) [66051](#) [12550](#) [19863](#) [09121](#) [73831](#) [13340](#) [13338](#) [04541](#) [19696](#)  
[16104](#) [SPI-20686](#)