19" CABINETS

Attachment Set



• Nickel-plated M6 x 15mm locking bolt with combi slotted/pozi head, PA washer, M6 caged nut with stainless-steel cage

Pack of 4

TYPE NO. CAX000001 SDESCRITPTION

Attachment set

Front Guides Mounting



• Attached to rack by two anchoring points with M6 bolts.

- Made of steel, 2mm thick
- · Zinc plated coating
- 1 Pair of guides and assembly hardware

TYPE NO.

SDESCRITPTION

Front guide Mounting CAXEMG001

LX Wheel Kit



- Set of 4 double rotating wheels with rubber rolling band or polyamide.
- Bracket made of stamped steel, with double roll of balls
- Maximum dynamic load acceptable per set: 2400N/240 Kg)

DESCRITPTION

CLX000001 LX Wheel Kit

Cable Guides Clamps



TYPE NO.	DESCRITPTION	
CAX19CGC1	1U Guide	
CAX19CGC2	211 Guide	

- · Manufactured in steel
- Standard finish: Epoxy paint simillar to RAL 9004
- Pack quantity x1

UNIVERSAL **ENCLOSURES**

> HAND HELD CASES

HEAVY DUTY ENCLOSURES

> DIN RAIL BOXES

INTERFACE

CONTROL STATIONS

DIECAST & METAL BOXES

DESKTOP & INSTRUMENT CASES

> POTTING BOXES

ENCLOSURES

CABINETS

DEVELOPMENT BOARDS

> CUSTOM SIZED ENCLOSURES

> > CUSTOM **SERVICES**



19" CABINETS

Side Mount Tray

UNIVERSAL **ENCLOSURES**

HAND

HELD CASES

HEAVY DUTY ENCLOSURES

DIN RAIL BOXES

INTERFACE SUPPORTS

CONTROL STATIONS

DIECAST & METAL BOXES

DESKTOP & INSTRUMENT

CASES

POTTING BOXES

ENCLOSURES

19" CABINETS



TYPE NO.	WIDTH	DEPTH
CAXSMT350	424mm	350mm
CAXSMT550	424mm	550mm

- · Manufactured in steel, 1.5mm thick.
- Easy assembly is attached to the rack at four anchoring points with M6 bolts
- Attachment points adaptable to variations in the depth of the 19" sections
- Recommended maximum static load: 60 Kg
- Standard ventilation slots
- Colour epoxy paint, anthracite RAL 7016
- One tray with mounting hardware

Cantilever Tray

TYPE NO.	U	DEPTH
CAX2TY180	2U	180mm
CAX2TY280	2U	280mm
CAX2TY350	2U	350mm
CAX2TY400	2U	400mm

- Manufactured in steel, 1.5mm thick.
- 19" assembly with four anchoring points on the front sections
- Recommended maximum static load: 10/20 Kg
- Standard ventilation slots
- Front fastening height 2U
- One tray with mounting hardware
- Standard depths 180, 280, 350, 400mm
- Grey graphite expoxy paint, anthracite RAL 7016
- 1 tray (screws not included)

Cantilever Telescopic Tray

TYPE NO.	U	DEPTH
CAXCTT280	2U	280mm



- · Ideal for holding keyboards
- · Manufactured in steel, 1.5mm thick
- 19"assembly with four anchoring points on the front sections
- · Recommended maximum static load- 10kg
- Standard ventilation slots
- · Front fastening height 2U
- Standard depths 280mm
- · Finish: Black epoxy paint
- · Telescopic guide rails nickel plated
- 1 Tray, 1 pair telescopic guides, 1 front handle

Clip-on Support Guides





CUSTOM	
SIZED	
ENCLOSURES	

CUSTOM SERVICES



TYPE NO.	DEPTH
CAXCSG345	345mm
CAXCSG545	545mm

- · Made of steel, 2mm thick
- · Quick attachment to the rack, without bolts
- Zinc plated coated
- · 1 pair of guides





X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for camden manufacturer:

Other Similar products are found below:

412689X CTBP92VE/12R CTBP9350/12 IND515205-240-T/GRN IND515205-240-T/RD IND5032405-240-T/GRN CE10.00.EI

C192SHAND CNMB/6ST/2 CNMB/4ST/2 CSACST004 CTBP9200/9 CIME/M/BE2250SS CHH64E1BL CIM/15W-DMFS CHHBAT2GY

CFTBN/2 CCB2S1/04 CHDX6-221C CHDX8-224 CHDASMP29 CHDASMP34 CHDX810DD CHDX811DD CCTTM40LR

CTBP92VJ/5S CTBP92VJ/8R CTSN431/12/M CTSN433/12/M CUABOX006 CE10.00.FM CBRPH-BLK BIM2003/13-WH/WH

RX2008/S-5-WH CBARD-CAR CRDCG0007 CNMB/4/KIT CTB5050/5 CTBP92HE/11 CTBP9358/10AO CHH66C2GY CHH456PBK

CHH451ABK CIM/9W-DMFS CIM/25W-DMFS RTM5006/16-NC-BLK IND5032405-125-T/AMB CCB1S1/03 CCD2S1/04 CCE1S1/05