




PRELIMINARY

FEATURES

- Pressure ranges 250 and 500 Pa (1 and 2 inch H₂O)
- Pressure sensor based on thermal micro-flow measurement
- Calibrated and temperature compensated
- Linear 0.5...4.5 V output
- High flow impedance up to 200 kPa/(ml/s)
- RoHS compliant
- Sensortronics PRO services

MEDIA COMPATIBILITY

Dry air and other non-corrosive gases



SPECIFICATIONS

Maximum ratings

Supply voltage V_s 4.75 ... 5.25 V_{DC}

Output current 1 mA

Lead specifications

Average preheating temperature gradient 2.5 K/s

Soak time ca. 3 min

Time above 217°C 50 s

Time above 230°C 40 s

Time above 250°C 15 s

Peak temperature 260°C

Cooling temperature gradient -3.5 K/s

Temperature ranges

Compensated 0 ... +70 °C

Operating -20 ... +80 °C


Storage -40 ... +80 °C

Humidity limits (non-condensing) 97 %RH

Vibration¹ 20 g

Mechanical shock² 500 g

ELECTRICAL CONNECTION



Specification notes:

1. Sweep 20 to 2000 Hz, 8 min, 4 cycles per axis, MIL-STD-883, Method 2007.
2. 5 shocks, 3 axes, MIL-STD-883E, Method 2002.4.



PRELIMINARY

PRESSURE SENSOR CHARACTERISTICS

Part no.	Operating pressure	Proof pressure ⁶	Burst pressure ⁶
LBAS250U...	0...250 Pa/0...2.5 mbar (1 inch H ₂ O)	2 bar (30 psi)	2 bar (30 psi)
LBAS250B...	0...±250 Pa/0...±2.5 mbar (±1 inch H ₂ O)		
LBAS500U...	0...500 Pa/0...5 mbar (2 inch H ₂ O)		
LBAS500B...	0...±500 Pa/0...±5 mbar (±2 inch H ₂ O)		

PERFORMANCE CHARACTERISTICS⁵

(V_S=5.0 V_{DC}, T_A=20°C, P_{Abs}=1 bara, calibrated in air, output signal is **ratimetric** to V_S for all LBA...8... devices and **non ratimetric** to V_S for all LBA...6... devices)

Characteristics		Min.	Typ.	Max.	Unit
Non-linearity			±(1.5 % of reading + 0.2 %FSO)	±(2.0 % of reading + 0.2 %FSO)	
Thermal effects	Offset	5...55 °C		±25	mV
		0...70 °C		±40	
	Span	5...55 °C		±1.75	%
		0...70 °C		±2.5	
Total accuracy ³	5...55 °C			±(1.5 % of reading + 1.5 %FSS)	
	0...70 °C			±(3.5 % of reading + 1.5 %FSS)	
Offset warm-up shift			±1	±5	mV
Offset long term stability ⁷			±0.3		% p.a.
Current consumption (no load)			4	5	mA
Response time (t ₆₃)			1-2		ms
Power-on time				10	

Unidirectional devices

Characteristics	Min.	Typ.	Max.	Unit
Zero pressure offset ⁴	0.47	0.50	0.53	V
Full scale span ⁴	3.94	4.00	4.00	
Full scale output		4.50		

Bidirectional devices

Characteristics	Min.	Typ.	Max.	Unit
Zero pressure offset ⁴	2.47	2.50	2.53	V
Full scale span ⁴	3.94	4.00	4.00	
Output	at max. specified pressure		4.50	
	at min. specified pressure		0.50	

Specification notes (cont.):

3. Total accuracy is the combined error from offset and span calibration, linearity, pressure hysteresis and temperature effects.
4. Min. and Max. values are calculated for 5...55 °C temperature range.
5. The sensor is calibrated with a common mode pressure of 1 bar absolute. Due to the mass flow based measuring principle, variations in absolute common mode pressure need to be compensated according to the following formula:

$$\Delta P_{\text{eff}} = \Delta P_{\text{sensor}} \times \frac{1 \text{ bara}}{P_{\text{abs}}}$$

ΔP_{eff} = True differential pressure
 ΔP_{sensor} = Differential pressure as indicated by output voltage
 P_{abs} = Current absolute common mode pressure

6. The max. common mode pressure is 2 bar.
7. Figure based on accelerated lifetime test corresponding to 1 year of life.




LBA Series

Low differential pressure sensors

PRELIMINARY

OUTLINE DRAWING



ORDERING INFORMATION

Options	Series	Pressure range		Calibration		Housing		Output		Grade	
	LBA	S250	250 Pa (1 inch H ₂ O)	B	Bidirectional	F	DIP, 2 ports same side	6	0.5...4.5 non ratiometric	S	High
		S500	500 Pa (2 inch H ₂ O)	U	Unidirectional			8	0.5...4.5 ratiometric		
Example:	LBA	S250		B		F		8		S	

Sensortech PRO services:

- Extended warranty period of 2 years
- Advanced logistics models for supply inventory and short delivery times
- Technical support through application engineers on the phone or at your site
- Fastest possible technical response for design and QA engineers
- ... plus other services on request

Sensortech reserves the right to make changes to any products herein. Sensortech does not assume any liability arising out of the application or use of any product or circuit described herein, neither does it convey any license under its patent rights nor the rights of others.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [first sensor manufacturer](#):

Other Similar products are found below :

[AD1100-9-TO52-S1](#) [QP50-6-18U-SM](#) [WS7.56 PCBA2](#) [3001481](#) [3004862](#) [PS100B-7-CERPINE](#) [PS1-2-TO52UV](#) [WS7.56-TO5](#) [QP50-6](#)
[SD2-DIAG](#) [3001032](#) [Cte7001gy0](#) [PC1-6-TO52-S1](#) [PC10-7-TO5](#) [PC0.55-5-TO52S1](#) [PC5-7-TO8I](#) [QP50-6-SM](#) [3001411](#) [5000001](#) [PC10A-](#)
[5B-TO5](#) [PS7-6B-TO5](#) [QP5.6-TO5](#) [3001212](#) [AD800-9-TO52-S1](#) [AD500-9-400M-TO5](#) [HCLA0075EB](#) [PC2-6-TO52-S1](#) [AD500-1.3G-TO5](#)
[QP50-6-TO8](#) [PS7-5B-TO5](#) [PS3.6-5-TO5](#) [PC5-2-TO5](#) [PC5-6B-TO5](#) [AD500-8-S1](#) [PS7-5-TO5](#) [HMAB010UZ7H5](#) [X100-7-SMD](#)
[LMIS250BB3S](#) [PS100-6B-CER-2 PIN](#) [PS1.0-6B-TO52S1.3](#) [5000041](#) [PR33-2-TO8](#) [PS0.9-5-TO52-S1](#) [LMIS500BB3S](#) [QP10-6-TO5](#) [DL100-](#)
[7-PCBA3](#) [PC2-6B-T052-SI](#) [PS1.0-5B-TO52S1.3](#) [DL100-7-SMD](#) [QP5.8-6-TO5](#) [PS1.0-5](#)