



CONNECTORS

RECTANGULAR POWER CONNECTORS



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

V.35,SKT ASY,RA,34P,W/BDLK

AMP | SKT

213574-2

TE Internal Number: 213574-2

Alias ID: 2-42935-4092

Not EU RoHS or ELV Compliant

[Find Compliant Alternatives](#)

Product Type **Connector Assembly**

Housing Type **Receptacle**

Connector System **Cable-to-Board**

Applies To **Printed Circuit Board**

Number of Positions **34**

Product Drawings

CONNECTOR ASSEMBLY, SOCKET, 34 POSITION, RIGHT ANGLE, WITH BOARDLOCKS, M SERIES

PDF
English

CAD Files

Customer View Model

3D_STP.ZIP
English

Customer View Model

2D_DXF.ZIP
English

Customer View Model

3D_IGS.ZIP
English

3D PDF

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Product Type

Connector Assembly

Housing Type

Receptacle

Contact Type

Socket, Tab

Configuration Features

Number of Positions

34

PCB Mounting Orientation

Right Angle

Body Features	Thread Size	6-32 UNC-2A, 6-32 UNC-2B
Contact Features	Contact Retention	With
	Contact Termination Area Plating Material	Tin-Lead
	Contact Termination Area Plating Thickness	2.54 μm [100 μin]
	Contact Retention Type	Locking Spring
Termination Features	Termination Method to Wire/Cable	Solder
	Termination Method to PC Board	Through Hole - Solder
	Termination Post/Tail Length	3.05 mm [.12 in]
Mechanical Attachment	Mating Alignment	With
	Mating Retention	With
	PCB Mount Retention	With
	Mating Retention Type	Jackscrews - Fixed
	PCB Mount Retention Type	Boardlocks
	Panel Mount Retention	Without
	Strain Relief	Without
	Mating Alignment Type	Guide Hole
Housing Features	UL Flammability Rating	UL 94V-0
	Housing Color	Black
	Housing Material	Phenolic - GF
Dimensions	Length	50.8 mm [2 in]
	Height	23.24 mm [.915 in]
	Width	19.05 mm [.75 in]
Usage Conditions	Sealed Condition	Not Sealed
	Shielded	No
Operation/Application	Connector System	Cable-to-Board
	Applies To	Printed Circuit Board
	Operating Temperature	-55 – 150 °C [-67 – 302 °F]
	Circuit Application	Signal
Packaging Features	Packaging Method	Tray, Tray/Box

Other

For Use With

Standard Connectors

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Rack & Panel Connectors](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[00170420102](#) [00171420202](#) [00171440002](#) [008026165000265](#) [00-8219-072-000-112P44](#) [008219072000112P5](#) [00-8223-096-580-102](#) [02-014-013-5200-000](#) [00-8129-015-610-108](#) [613467-000](#) [CTJ112E01E-513](#) [CTJ116E03A-513](#) [M81714/63-22S L/C](#) [M81714/65-12-1](#) [66020-2](#) [CW8958-000](#) [699886-000](#) [D250-50632](#) [70.400.3240.0](#) [70.955.2453.3](#) [733753-000](#) [F22831-000](#) [780-522-DPX34RG8-02](#) [MMA25-0341D1](#) [8660-501](#) [87.060.0053.0](#) [900709N001](#) [QRP4-12P-C\(01\)](#) [QR/P6-6S-C\(01\)](#) [AC-600003-004](#) [1218600-1](#) [D-659-0061](#) [DMC-MD 24 C-T](#) [1-445717-6](#) [1484398-2](#) [1484399-2](#) [1484469-2](#) [MR-34MG](#) [1484225-1](#) [1484398-1](#) [1604997-2](#) [1663130-1](#) [1663767-7](#) [1663767-8](#) [MTC100-BF1-P31CS015](#) [MTC100-KT2-0083](#) [MTC100-KT2-0123-003](#) [MTC100-YA1-005](#) [MTCB1X-105-XXX](#) [MTCPQKT1P2PGDC](#)