

Product Catalog

For Web Assistance: (800) 323-0198



Company Profile
and History



Product
Quote Form



Find a
Distributor



Contact Us

Product Index



Hookup Wire

Braided Stranded Copper Wire

Multiconductor

Tubing

Coaxial Cable

Check the Items You'd Like to Add to Your Quote or Order

Braidless Silicone Wire

HIGH-VOLTAGE HIGH-TEMPERATURE ELECTRONIC WIRE

*ABRASION RESISTANT SILICONE UL STYLE 3239

Standard Putups:

- 100ft.
- 500ft.
- 1000ft.
- bulk.

See color chart 8 in Technical Section. Consult factory for availability of other colors.

| DESCRIPTION | | | | FEATURES & APPLICATIONS | | | | |
|---|-----|-----------|----------------------------|--|---------------|------------|----------|--|
| <ul style="list-style-type: none"> • Conductors: Fully annealed tinned copper per ASTM B-33. Also available - nickel plated or pure nickel conductor. • Insulation: Specially formulated abrasion resistant extruded silicone rubber. | | | | <ul style="list-style-type: none"> • Superior chemical resistance. *Corona radiation and ozone resistant. *Recommended for stoves, heaters, furnaces, dryers, motors, therapeutic devices, signs, lighting fixtures, power supplies, radar installations, Xenon flash tubes, and special electronic devices where high temperatures are incurred. | | | | |
| CHARACTERISTICS | | | | APPROVALS | | | | |
| <ul style="list-style-type: none"> • Temperature: 150C. • Voltage Rating: Excellent dielectric strength. See chart below. | | | | <ul style="list-style-type: none"> • Recognized under the components program of Underwriters' Laboratories, Inc. UL Style 3239 (see chart below for UL recognized items), 150C. | | | | |
| Part Number | AWG | Stranding | Nom. Dia. of Conductor in. | Nom. Insulation Thickness in. | Nom. O.D. in. | DC Voltage | UL Style | |
| <input type="checkbox"/> 392240 | 22 | 7/30 | .030 | .040 | .114 | 10KV | 3239 | |
| <input type="checkbox"/> 392245 | 22 | 7/30 | .030 | .045 | .124 | 15KV | 3239 | |
| <input type="checkbox"/> 392250 | 22 | 7/30 | .030 | .050 | .134 | 20KV | 3239 | |
| <input type="checkbox"/> 392262 | 22 | 7/30 | .030 | .062 | .158 | 25KV | 3239 | |
| <input type="checkbox"/> 392275 | 22 | 7/30 | .030 | .075 | .185 | 30KV | 3239 | |
| Part Number | AWG | Stranding | Nom. Dia. of Conductor in. | Nom. Insulation Thickness in. | Nom. O.D. in. | DC Voltage | UL Style | |
| <input type="checkbox"/> 392297 | 22 | 7/30 | .030 | .097 | .230 | 40KV | 3239 | |
| <input type="checkbox"/> 392299 | 22 | 7/30 | .030 | .150 | .330 | 50KV | None | |
| <input type="checkbox"/> 392040 | 20 | 10/30 | .038 | .040 | .120 | 10KV | 3239 | |
| <input type="checkbox"/> 392045 | 20 | 10/30 | .038 | .045 | .131 | 15KV | 3239 | |
| <input type="checkbox"/> 392050 | 20 | 10/30 | .038 | .050 | .140 | 20KV | 3239 | |
| Part Number | AWG | Stranding | Nom. Dia. of Conductor in. | Nom. Insulation Thickness in. | Nom. O.D. in. | DC Voltage | UL Style | |
| <input type="checkbox"/> 392062 | 20 | 10/30 | .038 | .062 | .165 | 25KV | 3239 | |
| <input type="checkbox"/> 392075 | 20 | 10/30 | .038 | .075 | .191 | 30KV | 3239 | |
| <input type="checkbox"/> 392097 | 20 | 10/30 | .038 | .097 | .235 | 40KV | 3239 | |
| <input type="checkbox"/> 392099 | 20 | 10/30 | .038 | .150 | .338 | 50KV | None | |
| <input type="checkbox"/> 391840 | 18 | 16/30 | .047 | .040 | .131 | 10KV | 3239 | |
| Part Number | AWG | Stranding | Nom. Dia. of Conductor in. | Nom. Insulation Thickness in. | Nom. O.D. in. | DC Voltage | UL Style | |
| <input type="checkbox"/> 391845 | 18 | 16/30 | .047 | .045 | .140 | 15KV | 3239 | |
| <input type="checkbox"/> 391850 | 18 | 16/30 | .047 | .050 | .146 | 20KV | 3239 | |
| <input type="checkbox"/> 391862 | 18 | 16/30 | .047 | .062 | .175 | 25KV | 3239 | |
| <input type="checkbox"/> 391875 | 18 | 16/30 | .047 | .075 | .200 | 30KV | 3239 | |
| <input type="checkbox"/> 391897 | 18 | 16/30 | .047 | .097 | .245 | 40KV | 3239 | |
| Part Number | AWG | Stranding | Nom. Dia. of Conductor in. | Nom. Insulation Thickness in. | Nom. O.D. in. | DC Voltage | UL Style | |
| <input type="checkbox"/> 391899 | 18 | 16/30 | .047 | .150 | .350 | 50KV | None | |
| <input type="checkbox"/> 391640 | 16 | 26/30 | .058 | .040 | .141 | 10KV | 3239 | |
| <input type="checkbox"/> 391645 | 16 | 26/30 | .058 | .045 | .150 | 15KV | 3239 | |

| | | | | | | | | |
|--------------------------|--------------------|------------|------------------|-----------------------------------|--------------------------------------|----------------------|-------------------|-----------------|
| <input type="checkbox"/> | 391650 | 16 | 26/30 | .058 | .050 | .161 | 20KV | 3239 |
| <input type="checkbox"/> | 391662 | 16 | 26/30 | .058 | .062 | .185 | 25KV | 3239 |
| | Part Number | AWG | Stranding | Nom. Dia. of Conductor in. | Nom. Insulation Thickness in. | Nom. O.D. in. | DC Voltage | UL Style |
| <input type="checkbox"/> | 391675 | 16 | 26/30 | .058 | .075 | .212 | 30KV | 3239 |
| <input type="checkbox"/> | 391697 | 16 | 26/30 | .058 | .097 | .255 | 40KV | 3239 |
| <input type="checkbox"/> | 391699 | 16 | 26/30 | .058 | .150 | .376 | 50KV | None |
| <input type="checkbox"/> | 391440 | 14 | 41/30 | .074 | .040 | .155 | 10KV | 3239 |
| <input type="checkbox"/> | 391445 | 14 | 41/30 | .074 | .045 | .165 | 15KV | 3239 |
| | Part Number | AWG | Stranding | Nom. Dia. of Conductor in. | Nom. Insulation Thickness in. | Nom. O.D. in. | DC Voltage | UL Style |
| <input type="checkbox"/> | 391450 | 14 | 41/30 | .074 | .050 | .175 | 20KV | 3239 |
| <input type="checkbox"/> | 391462 | 14 | 41/30 | .074 | .062 | .204 | 25KV | 3239 |
| <input type="checkbox"/> | 391475 | 14 | 41/30 | .074 | .075 | .225 | 30KV | 3239 |
| <input type="checkbox"/> | 391497 | 14 | 41/30 | .074 | .097 | .272 | 40KV | 3239 |
| <input type="checkbox"/> | 391499 | 14 | 41/30 | .074 | .150 | .380 | 50KV | None |
| | Part Number | AWG | Stranding | Nom. Dia. of Conductor in. | Nom. Insulation Thickness in. | Nom. O.D. in. | DC Voltage | UL Style |
| <input type="checkbox"/> | 391240 | 12 | 65/30 | .092 | .040 | .170 | 10KV | 3239 |
| <input type="checkbox"/> | 391245 | 12 | 65/30 | .092 | .045 | .184 | 15KV | 3239 |
| <input type="checkbox"/> | 391250 | 12 | 65/30 | .092 | .050 | .196 | 20KV | 3239 |
| <input type="checkbox"/> | 391262 | 12 | 65/30 | .092 | .062 | .218 | 25KV | 3239 |
| <input type="checkbox"/> | 391275 | 12 | 65/30 | .092 | .075 | .246 | 30KV | 3239 |
| | Part Number | AWG | Stranding | Nom. Dia. of Conductor in. | Nom. Insulation Thickness in. | Nom. O.D. in. | DC Voltage | UL Style |
| <input type="checkbox"/> | 391297 | 12 | 65/30 | .092 | .097 | .289 | 40KV | 3239 |
| <input type="checkbox"/> | 391299 | 12 | 65/30 | .092 | .150 | .396 | 50KV | None |
| <input type="checkbox"/> | 391040 | 10 | 105/30 | .112 | .040 | .200 | 10KV | 3239 |
| <input type="checkbox"/> | 391045 | 10 | 105/30 | .112 | .045 | .206 | 15KV | 3239 |
| <input type="checkbox"/> | 391050 | 10 | 105/30 | .112 | .050 | .220 | 20KV | 3239 |
| | Part Number | AWG | Stranding | Nom. Dia. of Conductor in. | Nom. Insulation Thickness in. | Nom. O.D. in. | DC Voltage | UL Style |
| <input type="checkbox"/> | 391062 | 10 | 105/30 | .112 | .062 | .244 | 25KV | 3239 |
| <input type="checkbox"/> | 391075 | 10 | 105/30 | .112 | .075 | .270 | 30KV | 3239 |
| <input type="checkbox"/> | 391097 | 10 | 105/30 | .112 | .097 | .312 | 40KV | 3239 |
| <input type="checkbox"/> | 391099 | 10 | 105/30 | .112 | .150 | .420 | 50KV | None |
| <input type="checkbox"/> | 390845 | 8 | 133/29 | .166 | .045 | .256 | 15KV | None |
| | Part Number | AWG | Stranding | Nom. Dia. of Conductor in. | Nom. Insulation Thickness in. | Nom. O.D. in. | DC Voltage | UL Style |
| <input type="checkbox"/> | 390862 | 8 | 133/29 | .166 | .062 | .290 | 25KV | None |
| <input type="checkbox"/> | 390897 | 8 | 133/29 | .166 | .097 | .360 | 40KV | None |
| <input type="checkbox"/> | 390645 | 6 | 133/27 | .210 | .045 | .300 | 15KV | None |
| <input type="checkbox"/> | 390662 | 6 | 133/27 | .210 | .062 | .340 | 25KV | None |
| <input type="checkbox"/> | 390462 | 4 | 133/25 | .268 | .062 | .392 | 25KV | None |
| | Part Number | AWG | Stranding | Nom. Dia. of Conductor in. | Nom. Insulation Thickness in. | Nom. O.D. in. | DC Voltage | UL Style |
| <input type="checkbox"/> | 390262 | 2 | 259/26 | .336 | .062 | .460 | 25KV | None |

50KV ratings are theoretical. 200C constructions available upon request. Standard color: White.

If you wish to add the products to your quote or complete your quote check one of these buttons

[Add Items and Continue](#)

[Add Items and Generate Quote](#)

[Generate Quote](#)

[Home](#) | [Profile](#) | [Catalog](#) | [Quote Form](#) | [Representatives](#) | [Contact](#)
 Copyright 1997-2001, Dearborn Wire and Cable, Inc.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [alpha manufacturer](#):

Other Similar products are found below :

[6387-SL001](#) [F2213/64-BK103](#) [2924 GR001](#) [2924 YL005](#) [2916 WH005](#) [2918 BL005](#) [2934 BK001](#) [2924 BL005](#) [2920 BK005](#) [2920 OR001](#)
[2918 SL005](#) [2928 BK005](#) [2920 OR005](#) [2922 GR005](#) [2918 RD001](#) [2916 RD005](#) [2918 WH001](#) [2932 BK001](#) [2936 VI005](#) [2926 BK005](#) [2936](#)
[BR005](#) [2936 GR001](#) [2934 WH005](#) [2926 GR001](#) [2922 GR001](#) [2930 SL005](#) [2936 BL005](#) [2936 SL005](#) [2932 WH005](#) [2936 WH001](#) [2918](#)
[RD005](#) [2916 BL005](#) [2920 YL005](#) [2926 SL005](#) [2916 GR005](#) [2934 WH001](#) [2920 BL005](#) [2920 SL005](#) [2924 GR005](#) [2924 VI005](#) [2920 VI005](#)
[2926 OR005](#) [2934 GR001](#) [2932 OR005](#) [2916 GR001](#) [2934 BK005](#) [2928 OR005](#) [2918 OR005](#) [2922 OR005](#) [2930 OR005](#)