Ultraslim Trackball Keyboard G84-4400

This high-quality compact keyboard is designed for all applications where reliability, reduced space requirements and low height are of great importance. Useful for IT and industrial usage, medical facilities and for portable systems. Equally suitable for 19 inch rack-mounted drawers.



Facts & Features

- Single keys with Gold Crosspoint contacts (Cherry ML Modules)
- Designed for continuous use more than 20 Mio. key presses
- Robust and reliable with precise key actuation
- Integrated 16 mm Trackball plus 2 mouse buttons
- Ultra slim only 19.6 mm overall height
- Lightweight
- Usable with standard drivers of the operating system
- Ideal for industrial usage with space limitations and for 19" applications
- USB or PS/2 version
- Also available without housing for OEM

Agency Approvals

 CE, VDE/ÜG (EN60950), cURus FCC, VCCI, BSMI, C-Tick, GOST-R Designed for MS WindowsTM XP

Delivery Volume

- 1 Keyboard
- 1 Printed Manual

System Requirements

- PS/2: Plugs for Keyboard and Mouse
- USB: USB plug and supporting operating system

Technical Data

- Interface: USB (1.1 or higher) or 2x PS/2
- Number of Keys:
 83 = internat. layout without WindowsTM keys
 84 = european layout without WindowsTM keys
 Integrated Numeric Keypad
- Cable Length: approx. 1.75 m
- Weight: approx. 563 g (keyboard) approx. 720 g (with packaging)
- <u>Dimensions:</u>
 approx. 370 x 139 x 19,6 mm (keyboard)
 approx. 400 x 195 x 32 mm (packaging)
- Current Input (3 LEDs on):

USB: typ. 36 mA

PS/2: typ. 24 mA (keyboard) typ. 11 mA (trackball)

Reliability:

MCBF > 10⁹ operations

MTBF > 100.000 hours

- Storage Temperature:
 -20 ℃ to +60 ℃
- Operating Temperature:
 0 ℃ to +50 ℃
- Operating life time of individual keys:
 > 20 Mio. operations
- Packaging Unit:
 21 keyboards per master carton
 12 master cartons per pallet (252 pcs.)

Warranty

2 vears



Order Description

Order Number	Colour	Interface
G84-4400LUBxx-0	light grey	USB
G84-4400LUBxx-2	black	USB
G84-4400LPBxx-0	light grey	2 x PS/2
G84-4400LPBxx-2	black	2 x PS/2

The xx in the order number defines the country version:

Possible european layouts:

ΒE Belgium CH Switzerland DE Germany DK Denmark ES Spain FR France GB **UK-English** HU Hungary ΙT Italy NO Norway PLPoland PO Portugal

SF Sweden / Finland

SK Slovakia

TS Czech Republic

TQ Turkey

Possible international layouts:

EU US English with €

JK Japan

KR US-English / Korea RB US-English / Cyrillic RC US-English / China

(Other country versions upon request)

Cherry GmbH Cherrystraße 91275 Auerbach/Opf. Germany

Phone: +49 9643 18 0 Internet: <u>www.cherry.de</u>

Sales: +49 1805 243779 (+49 1805 CHERRY)

E-Mail: <u>sales@cherry.de</u> Fax: +49 9643 18 1545

The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice.

Technical data relates to product specifications only. Features may differ from

Technical data relates to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.

© 2008 Cherry GmbH, Last update: Jul 17, 2008_V11



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Input Devices category:

Click to view products by ZF Cherry manufacturer:

Other Similar products are found below:

80260-08 M11L0A1 M11L0B1M M21L0H1PX M41C091P100 80260-00 81521-08 FKB4720-103 84250-26 84980-04 84S-AC1-000 C10O0C1P JD-0700EU-2 JM-0800-2 JOY-THUMB JW-T0100 89498-13 89758-05 89886-26 89941-00 FQ-XT G3-A1AM151NNNN G80-3000LSCEU-2 M11C011B TH500P00D4 MJ0FGGRY JM-0800-0 KBCV-4100W MR2110R5BB 60C22-M7-4-020S 67A-DF-3C-060C 84S-BB1-004 81601-26 G8011900LPMUS0 G844420LUBEU0 G84-4700LUCUS-0 89701-26 81485-26 84105-13 V400-W24 5M V400-W23 5M G84-5200LCMEU-2 M11F061P 84Z2029-100 4P182F1D0100 M41L091M M41L091P 60A00-8-050C 84Z2029-78 XD2CF1111