

## 3M™ Polyimide Film Tape 5413 Amber, 1/2 in x 36 yd 2.7 mil, 18 per case Boxed



The 3M™ Polyimide Film Tape 5413 consist of a Kapton® polyimide film and silicone adhesive. It is designed for high temperature applications. Temperature use range is -100° to 500°F (-73°C to 260°C)

3M Id : 70-0160-3920-1  
GTIN(UPC/EAN) : 0 00 21200 16172 8

### Additional Information

3M™ Polyimide Film Tape 5413, used as mask for protection of gold fingers of printed circuit boards during wave solder or solder dip process, release surface in fabrication of parts cured at elevated temperatures

### Characteristics

<b>Adhesive Material</b>	Silicone
<b>Adhesive Type</b>	Silicone Adhesive
<b>Backing Material</b>	Kapton® polyimide film
<b>Length</b>	36 Linear Yard
<b>Magnetic Holder</b>	Polymide Film
<b>Size</b>	0.50 in. x 36 yd. (1.2 cm x 33 m)
<b>Tape Length</b>	36 yd. (33 m)
<b>Tape Type</b>	Polymide Film
<b>Tape Width</b>	0.5 in (1.2 cm)
<b>Temperature Range</b>	-100F - 500F (-73C - 260C)
<b>Thickness</b>	2.7 Milli-inch (mil)
<b>Width</b>	1/2 Inch

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [3m manufacturer](#):*

Other Similar products are found below :

[SC401U](#) [98-0003-3071-6](#) [00-054007-70220-7](#) [00-054007-34717-0](#) [021200-40230](#) [6840-2X50-GRAY](#) [D2550-6002-AR](#) [701-W](#) [7993MP-2CIRCLE-100](#) [FDV14-187C](#) [8124/14](#) [812510-100](#) [8125/17](#) [813216](#) [8204-3LFM](#) [8425-8](#) [MNG14BCX](#) [FP301-1-6"-Clear](#) [FV14-6C](#) [920102-01-25-R](#) [923835-BK-C](#) [927739-40](#) [929835-01-28-RK](#) [929836-09-16](#) [929974-01-40-R](#) [951240-2520-AR-PR](#) [960X/980X](#) [98-0003-3075-7](#) [HF36564-100](#) [HF625/26-30](#) [1/2-5-5430](#) [1/2-5-850S](#) [1/2-5-3431](#) [12X12-6-4056B](#) [12X12-6-433](#) [12X12-6-4930](#) [13-500-NB](#) [14526-EZ5B-300-02C](#) [1-4-4658F](#) [14520-EZAB-300-0EC](#) [DSTK9013-3420](#) [DSTK9015-3402](#) [14T50-SZWB-100-0NC](#) [152244-0110-GB](#) [1-5-3437](#) [1-5-4496W](#) [1-5-4943F](#) [1-5-363](#) [1-5-5451](#) [1-5-421](#)