



Actual size

testo Ltd.
Newman Lane
Alton
Hampshire
GU34 2QJ

Tel: 01420 544 433
Fax: 01420 544 434
Email: info@testo.co.uk
Internet: www.testo.co.uk

1.3^{m/s}

21.4^{°C}

testo 410-2



testo 410-2





Innovative Pocket-Sized Measurement Technology

Measuring instruments for heating, air conditioning and ventilation.

Testo, the leading manufacturer of portable measurement technology, provides pocket-sized measuring instruments for fast and tough everyday use:

- Air and surface temperature
- Humidity and temperature
- Material moisture, humidity and temperature
- Differential pressure
- Absolute pressure
- rpm
- Light intensity
- Air flow velocity, temperature, humidity

Sensors that fulfil the highest demands, such as Testo's own patented humidity sensor, guarantee reliable and stable measurements.

All instruments are very handy, small and easy to use. The backlit display and the Auto-Off function complete the instrument.

Always included:
Protective cap, wrist strap and belt holder – indispensable additions for practical use.

Great technology can be this small!



· 50 YEARS OF TESTO

· More innovative than ever

· 50 innovations in our anniversary year



INNOVATION 2007



Testo 810 - Air and surface temperature in one instrument



- Surface temperature IR measurement with 1-point laser spot marking and 6:1 optics
- Air temperature measurement
- Display of differential temperature e.g. between window and air
- Hold function and max./min. values

Technical data

Surface temperature:

Measuring range: -30 to 300 °C

Resolution: 0.1 °C

Accuracy: ± 2.0 °C
(-30 to +100 °C)
 $\pm 2\%$ of m.v.
(remaining range)

Optics: 6:1

Air temperature:

Measuring range: -10 to 50 °C

Resolution: 0.1 °C

Accuracy: ± 0.5 °C

Units: °C/°F

Oper. temp.: -10 to 50 °C

Battery type: Alkaline (2 x AAA)

Battery life: 50 h. (average, without display illumination)

Dimensions

(incl. protective cap): 119 x 46 x 25 mm

Included in delivery:

Calibration protocol · Wrist strap
Belt holder · Protective cap · Batteries

Part no. 0560 0810



Testo 610 - Air temperature and humidity measurement



- Long-term drift-free Testo humidity sensor
- 2.5 %rh accuracy with calibration protocol
- Including dewpoint calculation and wet bulb
- Hold function and max./min. values

Technical data

Temperature

Measuring range:	-10 to 50 °C
Resolution:	0.1 °C
Accuracy:	± 0.5 °C
Units:	°C/°F

Humidity

Measuring range:	0 to 100 %rh
Resolution:	0.1 %rh
Accuracy:	± 2.5 %rh (5 to 95 %rh)
Units:	%rh, wet bulb, dewpoint
Oper. temp.:	10 to 50 °C
Battery type:	Alkaline (2 x AAA)
Battery life:	200 h. (average, without display illumination)

Dimensions

(incl. protective cap): 119 x 46 x 25 mm

Included in delivery:

Calibration protocol · Wrist strap
Belt holder · Protective cap · Batteries

Part no. 0560 0610



Testo 606 - Material moisture, air temperature and humidity



- Available in two models:
 - Testo 606-1** material moisture
 - Testo 606-2** material moisture, air temperature and humidity
- Measurement of wood moisture e.g. beech, spruce, larch, oak, pine and maple
- Air temperature and humidity for monitoring drying processes
- Curves for cement screed, concrete, plaster, anhydrite, cement mortar, lime and brick
- Hold and auto-test functions

Technical data

Material moisture

Measuring range: 0 to 90%

Resolution: 0.1

Accuracy: $\pm 1\%$ (conductivity)

Air humidity (606-2 only):

Measuring range: 0 to 100%rh

Resolution: 0.1%rh

Accuracy: $\pm 2.5\%$ rh (5 to 95%rF)

Units: %rh, wet bulb, dewpoint

Air temperature (606-2 only)

Measuring range: -10 to 50°C

Resolution: 0.1°C

Accuracy: $\pm 0.5\text{ }^{\circ}\text{C}$

Units: °C/°F

Oper. temp.: -10 to 50 °C

Battery type: Alkaline (2 x AAA)

Battery life: 606-1: 200 h.

606-2: 130 h.

(average, without display illumination)

Dimensions

(incl. protective cap): 119 x 46 x 25 mm

Included in delivery:

Calibration protocol · Wrist strap

Belt holder · Protective cap · Batteries

606-1: Part no. 0560 6060

606-2: Part no. 0560 6062



Testo 510 - Differential pressure measurement



- Measuring range of 0 to 100 mbar
- Temperature compensation
- Magnetic base for hands free instrument mounting
- Flow velocity measurement with Pitot tube
- Air density compensation

Technical data

Pressure

Measuring range: 0 to 100 mbar

Resolution: 0.0 1 mbar

Accuracy:

± 0.03 mbar (0 to 0.30 mbar)

± 0.05 mbar (0.31 to 1.00 mbar)

$\pm (0.1 \text{ mbar} + 1.5\% \text{ of m.v.})$

(1.01 mbar to 100 mbar)

Units: hPa, mbar, Pa,
mmH₂O, mmHg,
inH₂O, inHg, psi,
m/s, fpm

Oper. temp.: 0 to 50 °C

Battery type: Alkaline (2 x AAA)

Battery life: 500 h. (average,
without display
illumination)

Dimensions

(incl. protective cap): 119 x 46 x 25 mm

Included in delivery:

Calibration protocol · Wrist strap
Belt holder · Protective cap · Batteries

Part no. 0560 0510



Testo 511 - Absolute pressure, barometric pressure and altitude



- Absolute pressure accuracy ± 3 mbar
- Calculation of barometric pressure
- Barometric altitude measurement

Technical data

Pressure

Measuring range: 300 to 1,200 mbar

Resolution: 0.1 mbar

Accuracy: ± 3.0 mbar

Units: hPa, mbar, Pa,
mmH₂O, mmHg,
inH₂O, inHg, psi, m, ft

Oper. temp.: 0 to 50 °C

Battery type: Alkaline (2 x AAA)

Battery life: 500 h. (average, without
display illumination)

Dimensions

(incl. protective cap): 119 x 46 x 25 mm

Included in delivery:

Calibration protocol · Wrist strap
Belt holder · Protective cap · Batteries

Part no. 0560 0511



Testo 460 - Optical rpm measurement



- Optical rpm measurement with LED spot marking
- Max./min. values

Technical data

Measuring range:	100 to 29,999 rpm
Resolution:	0.1 rpm (100 to 999.9 rpm) 1 rpm (1,000 to 29,999 rpm)
Accuracy:	± (0.02 % of m.v.) + 1 digit
Units:	rpm, rps
Oper. temp.:	0 to 50 °C
Battery type:	Alkaline (2 x AAA)
Battery life:	20 h. (average, without display illumination)
Dimensions (incl. protective cap):	119 x 46 x 25 mm

Included in delivery:
Calibration protocol · Wrist strap
Belt holder · Protective cap · Batteries

Part no. 0560 0460



Testo 540 - Lux meter



- Sensor is adjusted to the spectral sensitivity of the eye
- Hold reading function
- Max./min. values

Technical data

Measuring range:	0 to 99,999 Lux 1 Lux (0 to 19,999 Lux) 10 Lux (20,000 to 99,999 Lux)
Accuracy:	± 3% (compared to reference)
Units:	Lux, Footcandle
Oper. temp.:	0 to 50 °C
Battery type:	Alkaline (2 x AAA)
Battery life:	20 Std. (average, without display illumination)
Dimensions (incl. protective cap):	133 x 46 x 25 mm

Included in delivery:

Calibration protocol · Wrist strap
Belt holder · Protective cap · Batteries

Part no. 0560 0540



Testo 410 - Wind or air flow, temperature and humidity



- Available in two models:
 - Testo 410-1** wind or air flow and temperature
 - Testo 410-2** wind or air flow, temperature and humidity
- Integrated 40 mm vane
- Timed mean value calculation
- Hold function and min./max. values
- Windchill calculation for outdoor areas

Technical data

Flow velocity

Measuring range: 0.4 to 20 m/s

Resolution: 0.1 m/s

Accuracy: $\pm (0.2 \text{ m/s} + 2\% \text{ of m.v.})$

Units: m/s, km/h, fpm, mph, knots, perceived

temperature °C/°F (windchill), Beaufort

Temperature

Measuring range: -10 to 50 °C

Resolution: 0.1 °C

Accuracy: $\pm 0.5 \text{ °C}$

Units: °C/°F

Humidity (testo 410-2 only):

Measuring range: 0 to 100 %rh

Resolution: 0.1 %rh

Accuracy: $\pm 2.5 \text{ %rh}$ (5 to 95 %rh)

Units: %rh, wet bulb, dewpoint

Oper. temp.: -10 to 50 °C

Battery type: Alkaline (2 x AAA)

Battery life: testo 410-1: 100 h.
testo 410-2: 60 h.
(average, without display illumination)

Dimensions

(incl. protective cap): 133 x 46 x 25 mm

Included in delivery:

Calibration protocol · Wrist strap
Belt holder · Protective cap · Batteries

410-1: Part no. 0560 4101

410-2: Part no. 0560 4102

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Testo manufacturer:](#)

Other Similar products are found below :

[206 PH1](#) [TESTO 316-1 0632 0316](#) [TESTO 470 0563 0470](#) [TESTO 770-1 0590 7701](#) [TESTO 905-T1 0560 9055](#) [0572 0500](#) [0590 0016](#) [0602 4592](#)
[0590 0008](#) [0590 0018](#) [0602 0645](#) [0635 1025](#) [0628 0020](#) [TESTO 435-2 0563 4352](#) [TESTO 605I 0560 1605](#) [TESTO 755-2](#) [0590 7552](#) [TESTO 770-2](#)
[0590 7702](#) [TESTO 869 + TESTO 745](#) [TESTO 869 + TESTO 750-3](#) [465](#) [410-2](#) [460](#) [0572 6172](#) [0590 0001](#) [0614 2272](#) [TESTO 417 0560 4170](#) [0609](#)
[7072](#) [TESTO 174-H SET](#) [TESTO 176-T4](#) [TESTO 176-P1](#) [TESTO 830-T2](#) [TESTO 103](#) [TESTO 905-T1](#) [TESTO 108-2](#) [TESTO 905I](#) [TESTO 108](#)
[0563 4403](#) [0590 7703](#) [TESTO 435-3 0560 4353](#) [TESTO 735-1 0560 7351](#) [TESTO 760-3 0590 7603](#) [TESTO 770-3 0590 7703](#) [0590 0013](#) [0602 4892](#)
[TESTO 635-2 0563 6352](#) [TESTO 750-3 0590 7503](#) [TESTO 760-1 0590 7601](#) [816-1](#) [TESTO 174-T SET](#) [TESTO 605-H1](#)