

# Customer Specification PART NO. GRP-130-1/8

#### Construction

1) Tubing Type	WrappableSleeving	
2) Tubing Material	Flame Retardant Braided PET	
3)Nominal Supplied ID(In)	0.125	
4) Nominal Wall Thickness +/- 0.005(In)	0.024	
5) Ends per Carrier Alternating	1/3	
9) Color(s)	BLACK , ORANGE	

## Applicable Specifications

1) UL	UL-94-0	
	UZKX2	
2)CSA	5836 01	
	FT2	

#### Environmental

1) EU Directive 2002/95/EC(RoHS):		
	All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment. Consult Alpha Wire's web site for compliance Date of Manufacture.	
2) REACH Regulation (EC 1907/2006):		
	This product does not contain any of the 16 substances listed on the European Union's REACH Substance of Very High Concern (SVHC) candidate list in excess of 0.1% mass of the item.	
3) California Proposition 65:	The outer surface materials used in the manufacture of this part meet the requirements of California Proposition 65.	

# Properties

Physical & MechanicalProperties				
1) Temperature Range	-70 to 125°C			
2) Melt Temperature	250°C			
3)Tensile Strength	6 psi, Min	ASTM D638		
Electrical Properties				
Chemical Properties				
1) Corrosion(0°C,16hrs)	no corrosion	AMS-DTL-23053		
2) Water Absorption	0.10% Max	ASTM D570		
3) Fungus Resistance	Pass	AMS-DTL-23053		
4) Halogen Free	Yes			
5) Lead Free	Yes			

#### Other

Packaging		
a) 200 FT		
b)50 FT		
	Packages may contain a Maximum of 3 lengths, 20 ft Minimum Length	

www.alphawire.com

Alpha Wire | 711 Lidgerwood Avenue, Elizabeth, NJ 07207 Tel: 1-800-52 ALPHA (25742)

Although Alpha Wire ("Alpha") makes every reasonable effort to ensure there accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha had been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.



Alpha Wire | 711 Lidgerwood Avenue, Elizabeth, NJ 07207 Tel: 1-800-52 ALPHA (25742), Web: www.alphawire.com

### **RoHS CERTIFICATE OF COMPLIANCE**

To Whom It May Concern:

Alpha Wire Part Number: GRP-130-1/8

GRP-130-1/8, RoHS-Compliant Commencing With9/24/2010Production

This document certifies that the Alpha part numbers cited above are manufactured in accordancewith Directive 2002/95/EC of the European Parliament and of the Council of 27 January 2003, better known as the RoHS Directives, with regards to restrictions of the use of certain hazardoussubstances used in the manufacture of electrical and electronic equipment. The reader is referred to these Directives for the specific definitions and extents of these Directives. **No Exemptions arerequired for RoHS Compliance on this item.** 

Substance	Maximum Control Value
Lead	0.1% by weight (1000 ppm)
Mercury	0.1% by weight (1000 ppm)
Cadmium	0.01% by weight (100 ppm)
Hexavalent Chromium	0.1% by weight (1000 ppm)
Polybrominated Biphenyls (PBB) Polybrominated Diphenyl Ethers (PBDE)	0.1% by weight (1000 ppm)
Including Deca-BDE	0.1% by weight (1000 ppm)

The information provided in this document and disclosure is correct to the best of Alpha Wire'sknowledge, information and belief at the date of its release. The information provided is designed only as a general guide for the safe handling, storage, and any other operation of the productitself or the one that it will become part of. The intent of this document is not to be considered awarranty or quality specification. Regulatory information is for guidance purposes only. Productusers are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Authorized Signatory for the Alpha Wire Company:

Dave Watson, Director of Engineering & QA

9/14/2012

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Non-Heat Shrink Tubing and Sleeves category:

Click to view products by Alpha manufacturer:

Other Similar products are found below :

601203-000 CTA-0053 8429-9 8445-7.5 8450 120-116-1-1-09BE 120-116-1-1-09BF 120-116-1-1-09BP 120-116-1-1-12BE 120-116-1-1-12BP 120-123-06 120-123-10 120-125-12BL 120-125-12R 120-125-20R 120-126-09 120-126-09BL 120-126-12 120-126-12BL 120-126-52 120-126-52BL 120-104-12 120-105-1-1-06BE 120-105-1-1-06CE 120-116-1-1-06BP 120-116-1-1-10BP 120-116-1-1-12BF 120-123-12 120-125-09 120-125-12 120-125-12Y 120-125-52BL 120-S002-12 120-S001-09 120-S002-09 121-101-1-56BFC 121-101-1-1-64BFC RAY-90-3.0(100) 20675-2 8S42-100FR-CS8184 SAS-115-1-1048-1X SAS-160-1-1048-1X RAY-103-10.0(100) RAY-103-4.0(100) 4627-S 3-1991136-0 561-SL1000PP 561-SL250FRPP 561-SL375NYGY 561-SL375PE