



Integrity® Tacky Roller Foam

Integrity Foam Roller can be applied to a variety of clean room surfaces and equipment.

ADHESIVE PROPERTIES

180 Degree peel adhesion, PSTC No. 1 (OZ/IN)	Adhesive Type
17 OZ (initial - 24 hours at room temperature)	Aqueous based acrylic

FILM PROPERTIES

GAUGE	TYPE	ELONGATION	TENSILE	COLOUR
3mil (nominal)	Low Density PE	350% MD	3800 (psi) MD	Clear
		600% TD	2300 (psi) TD	



For roller handle see stock code 600-0424 & 600-0425

FOAM PROPERTIES

1/16" PE Foam

PRODUCT CODES	SIZE	
600-0422		Each
600-0420		Each

Call +44 (0) 1473 836205 Email info@integritycleanroom.com (2) /integrity_eu (in /company/integrity-cleanroom





IMPORTANT NOTICE: This data sheet and its contents (the "Information") belong to the Integrity or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Integrity assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Integrity was aware of the possibility of such loss or damage arising) is excluded. © Integrity. PAGE 1 INTEGRITY FOAM ROLLERS | 4 DECEMBER 2014 2:13 PM



























X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for integrity manufacturer:

Other Similar products are found below:

 $600-3033\ 600-4002\ 600-4001\ 600-0520\ 600-0230\ 600-0420\ 600-0220\ 600-4003\ 600-0501\ 600-0660\ 600-5008\ 600-0010\ 600-0012$