

www.mikrobest.pl

Multifunction time ralay. Multiscale. Multivoltage. 1 relay output DPDT

10000


General characteristics

- Electronic time relay, multiscale, multivoltage.
- 1 relay output with 2 changeover contact (DPDT)
- Green LED indicator for relay state
- Modular DIN 35mm

	Order code TRAm-C	Time of scale range 0,25s-12m	Rated auxiliary supply voltage V 24 V AC/DC 230 V AC	Qty per pkg 1
Function				
 On delay (Power on) When the input voltage U is applied,timing delay t begins. Relay contacts R change state after time delay is complete. Contacts R return to their shelf state when input voltage U is removed. Interval (Power off) When the input voltage U is applied,relay contacts R change state. immediately and timing cycle begins. When the time delay is compete,contacts return to shelf state. When input voltage U is removed,contacts will also return to their shelfstate. Repeat Cycle(Starting off)) When the input voltage U is applied,time delay t begins. When the input voltage U is applied,time delay t begins. When the input voltage U is applied,time delay t begins. When the input voltage U is applied,time delay t begins. When the input voltage U is applied,time delay t begins. When the input voltage U is applied,time delay t begins. When the input voltage U is applied,relay contacts R change state for time delay t. Repeat Cycle(Starting on) When the input voltage U is applied,relay contacts R change state immediately and time delay t begins. When the input voltage U is applied,relay contacts R change state immediately is complete, contacts return their shelf state for time delay t. This cycle will repeat until input voltage U is removed. 	6	$R = \frac{U}{t}$		TRAm-C 11 12:10 12:1
Time rangers		x1m x8s x1s x0,25	/ 79	TRAm-C TRAm-C x1 x1 x8 x8 x8 x8 x8 x8 x1 x1 x1 x1 x1 x1 x1 x1 x1 x1

Technical parameters

Supply terminals:	A1 - A2 230VAC C1 - A2 24V AC/DC
Supply voltage tolerance:	0,8 - 1,1 %
Consumption:	max 8VA
Current rating:	8A/250V AC1
Time deviation:	8A/24V DC1 5%
Protection degree:	5% IP20
Dimensions:	90 x 35 x 45mm



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Timers category:

Click to view products by Mikrobest manufacturer:

Other Similar products are found below :

 79237785
 H3DS-GL AC24-230/DC24-48
 H5AN-4DM DC12-24
 H5CN-XDNM AC100-240
 H5CN-YAN AC100-240
 H5CX-L8S-N AC100-240

 240
 H3AMNSCAC100240
 H3AM-NSR-B AC100-240
 H3CA-8 DC12
 H3CR-A8-302 DC24
 H3CR-F AC24-48/DC12-48
 H3CR-G8EL

 AC200-240
 H5AN-4D DC12-24
 81506944
 88225029
 H5S-YB4-X
 H3CR-A-301 AC100-240/DC100-125
 H3CR-AS AC24-48/DC12-48

 H3DK-GE AC240-440
 H3RN-2 AC24
 H3RN-21 AC24
 H3CR-H8RL AC/DC24 M
 H3CR-H8RL AC100-120 S
 H3CR-G8EL-31 AC100-120

 H3CR-H8RL AC100-120 M
 H3CR-HRL AC100-120 M
 H3CR-A8-301 AC24-48/DC12-48
 H3CR-H8RL AC/DC24 S
 H7AN-2D DC12-24

 H5CN-XANS DC12-48
 H3CA-8 DC110
 H7AN-W4DM DC12-24
 H7AN-4DM DC12-24
 H7AN-RT6M AC100-240

 H3CA-8H AC200/220/240
 MTR17-BA-U240-116
 PM4HSDM-S-AC240VS
 PM4HSDM-S-AC240VSW
 PO-405
 600DT-CU
 H3Y-2-B DC24

 30S
 PM4HF8-M-DC24V
 PM4HS-H-DC12VSW
 H3Y-2-B AC100-120 10S
 H3Y-2-B AC100-120 30S
 H3C-R
 H3CR-A8-301 24-48AC/12

 48DC
 H3CR-A8E 24-48AC/DC
 H3CR-F8 100-240AC/100-125DC
 H3CR-F8 100-240AC/100-125DC
 H3CR-F8 100-240AC/100-125DC