

## NOT for Patient-Care Rooms - UL1363 Hospital-Grade Surge Protector with 6 Hospital-Grade Outlets, 10 ft. Cord, 1050 Joules

### MODEL NUMBER: SPS610HGRA











### **Highlights**

- 6 hospital-grade outlets
- 1050 joule rating
- 10-ft. cord with molded right-angle hospital-grade plug
- All metal housing

### Package Includes

- SPS610HGRA Surge Suppressor
- Instruction manual with warranty information

#### Description

Our SPS610HGRA surge suppressor provides 6 hospital-grade outlets and protection from damaging surges and spikes with the added benefit of a convenient right-angle hospital-grade plug. The new design provides another option for convenient outlets outside the patient care area, including those tight spaces.

#### **Features**

- 1050-joule AC surge suppression rating
- Rugged all-metal housing withstands years of use without loss of ground path continuity
- 6 NEMA5-15R Hospital-Grade AC outlets
- 10-ft. AC cord with integrated, molded right angle Hospital-Grade NEMA 5-15PHG plug
- · Keyhole mounting tabs and flanges
- Switch safety cover prevents accidental shutoff
- 15A electrical capacity with built-in resettable circuit breaker
- 120 volt, 50/60Hz electrical compatibility
- Certified by UL (USA) and cUL (Canada)
- UL1449 3rd Edition listed
- Automatic shutoff cuts power to outlets when the protection circuit has been compromised

# **Specifications**

ОШТРИТ	
Frequency Compatibility	50 / 60 Hz
Output Receptacles	(6) 5-15R-HG
Output (Watts)	1800





Circuit Breaker (amps)	15	
Transformer Accommodation	Supports 1 large transformer plug accessories without covering remaining outlets	
Right-Angle Outlets	No	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V (110-125V)	
Input Connection Type	NEMA 5-15P-HG Hospital-Grade	
Input Cord Length (ft.)	10	
Input Cord Length (m)	4.6	
Voltage Compatibility (VAC)	120	
Maximum Surge Amps	19500	
Right-Angle Plug	Yes	
USER INTERFACE, ALERTS & CONTROLS		
Diagnostic LED Details	LINE POWER PRESENT (green)	
SURGE / NOISE SUPPRESSION		
AC Suppression Joule Rating	1050	
AC Suppression Response Time	< 1 ns	
Protection Modes	Includes full normal mode surge suppression	
Clamping Voltage (RMS)	140	
DATALINE SURGE SUPPRESSION		
Telephone/DSL Protection	No	
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	
PHYSICAL		
Shipping Dimensions (hwd / in.)	2.25 x 15 x 6	
Shipping Dimensions (hwd / cm)	5.7 x 38.1 x 15.24	
Shipping Weight (lbs.)	3.5	
Shipping Weight (kg)	1.59	
Unit Dimensions (hwd / in.)	1.5 x 13.75 x 2.5	
Unit Dimensions (hwd / cm)	3.81 x 34.9 x 6.35	
Unit Weight (lbs.)	3.2	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Unit Weight (kg)	1.45	
Material of Construction	Metal	
Integrated Keyhole Mounting Tabs	Includes keyhole mounting tabs and flanges	
Receptacle Color	White	
Color (AC Line Cord)	Gray	
CERTIFICATIONS		
UL1449 3rd Edition (AC Suppression)	UL1449 3rd Edition (Series Number: AGIB12015SL)	
UL1363 (Power Tap)	UL1363 (Series Number: AGIB12015SL)	
cUL / CSA (Canada)	cUL (Series Number: AGIB12015SL)	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Power Outlet Strips category:

Click to view products by Tripp Lite manufacturer:

Other Similar products are found below:

G20IG606 1301430288 1301530208 1302100069 1301430321 1301530054 1447B163 1585T16A1RA UL602CB-6 UL7408-6 ULHC4-15

V20IG606 UL2063BD TSB 1301530203 4748.03 4309 UL7208-15 3083 3050F 3090 1301530132 1301530117 1301530164 1301530050

1301530141 1301430252 1301530179 1301530065 1301350158 1301530052 1301530068 1301530120 HB0B1L4BT08W1

VB0D2B2BM30P1 HA0A1D0CA10E1 HA0A1M2CM10E1 HA1A1D0CA10E1 VB0B1L2BN24H1 PN1A1C0BA10E1 HA0B1E0CA1081

HA0D2U0CA1081 HA0D2A0CA1081 HA1D2U0CA1081 HA1D2A0CA1081 HB1B2J0AA10M1 LZ1D2A0FA0AJ1 LZ1D2P0FA0AL1

VB0B1L4CN48M1 MA002