



ALL APN ■ AND UPC ● CODE NUMBERS SHOWN ARE PRECEDED BY THE MANUFACTURER APN OR UPC I.D. NUMBER ■ 9337103 & ● 037103.

Weller products have been serving the scientifc, industrial and do-it-yourself markets since 1945. The Australian plant at Albury/Wodonga manufactures a full range of soldering and desoldering tools and aids that are designed to comply with Australian standards and the requirements of local conditions. Industry demands that soldering tools are extremely efficient with minimal maintenance. The technology gained in meeting these requirements has been incorporated throughout the consumer products as well.

BENEFITS:

- Iron is ready to use from new. No tip preparation by the purchaser required.
 Good thermal conductivity with corrosion protection for longer life.
- 3. Heats up quickly. Rugged long life element.
- 4. Minimal deterioration over long periods.
- 5. User comfort even after long periods of use.
- 6. The right iron available for the right job to give the best results.
- 7. Safe to use.



Marksman Soldering Irons (Line Voltage)

All irons blister packaged on hang-up card. SP250D also with stand. SP15D & SP25D - Nickel Plated. SP40D, SP80D, SP120D, SP175D & SP250D Iron plated.

	Material Number	Description Watt / Volt / Hertz	APN/UPC	Shelf Pack
SP15D (15 watt)	SP15D	15 Watt / 240 Volt / 50 Hertz	473686	3
	Letter Market	Pencil grip. Light duty soldering iron. 210mm long. 400°C tip temperature. Replaceable screw-in tip. Recommended Use: Electronic or transistor kit work. Printed circuit board work where a fine tip is required.		
SP25DAU (25 watt)	SP25DAU	25 Watt / 240 Volt / 50 Hertz	475901	3
Weller materiasis		Pencil grip. 210mm long. 400°C tip temperature. Replaceable screw-in tip. Recommended Use: Light home and hobby iron suitable for printed circuit board work, light electrical soldering. SP25DK for Woodburning.		
SP40DAU (40 watt)	SP40DAU	40 Watt / 240 Volt / 50 Hertz	475925	3
		Pencil grip. Weighs only 56g. 209mm long. Replaceable 6.35mm (diameter) tip. Recommended Use: Suitable for general home soldering of electrical wiring and connections.		
SP80DAU (80 watt)	SP80DAU	80 Watt / 240 Volt / 50 Hertz	475932	3
		Pencil grip. Weighs only 113g. 238mm long. Replaceable 9.52mm (diameter) tip. Recommended Use: Medium wattage iron for electrical soldering. Suitable for light alloy or metal soldering. SPG80D for leadlight soldering.		
SP120DAU (120 watt)	SP120DAU	120 Watt / 240 Volt / 50 Hertz	474539	3
		Medium duty soldering iron. Weighs only 283g. 289mm long. Replaceable 12.70mm (diameter) tip. Recommended Use: Heavy electrical connections and light sheetmetal work.		
SP175DAU (175 watt)	SP175DAU	175 Watt / 240 Volt / 50 Hertz	474676	3
		Heavy duty soldering iron. Weighs 435g. 317mm long. Replaceable 15.87mm (diameter) tip. Recommended Use: Suitable for very heavy cable and medium gauge sheetmetal. eg.: guttering.		
SP250D (250 watt)	SP250D	250 Watt / 240 Volt / 50 Hertz	476625	3
		Heavy duty soldering iron. Weighs 510g. 350mm long. Replaceable 20mm (diameter) tip. Recommended Use: Heavy sheetmetal assembly.		
FEATURES:				
Pre-tinned tip. Electroplated copper tips. Ceramic filled element. Stainess Steel metal components. Stay cool handle material and design.				
6. A range of 10 wattage sizes and kits.				,

7. Fully approved by Electrical Authority.



ALL APN ■ AND UPC • CODE NUMBERS SHOWN ARE PRECEDED BY THE MANUFACTURER APN OR UPC I.D. NUMBER ■ 9337103 & • 037103.

Marksman Soldering Irons (Line Voltage)





WHK30AU



- 15 piece set, including 12 tips, ideal for wood burning, sculpting, adding accents, stencil cutting, pattern transfers, hot knife cutting, embossing and branding
- 30 Watt short barrel Woodburning Iron
- Set contains 6 Woodburning tips, Hot Knife Tip with Blade Chuck, Pattern Transfer Tip, 3 Branding Tips, Iron Stand and complete Project Book
- Boxed in plastic presentation case

SPG80DAU







WLC80D

TB100AU

Temperature Controlled Irons - Magnastat®

W60D	60 Watt - (Temp. controlled)	<u>^</u>	474089	3
W100D	100 Watt - (Temp. controlled)		474263	3
T0056107599	W201D 230V Magnastat® Tool		4003019029563	

- Industrial Soldering Pencils, ideal for electronic work
- Magnastat Controlled

Therma-Boost Soldering Tool

	_		
TB100AU	30W-130W/230V	■ 002121	5

 Therma-Boost trigger gives added bursts of power when needed (130W Therma-Boost, 30W Std) Kit includes Therma-Boost heat tool, six multiple use tips, stand and instructions

Woodburning Tips





Woodburning Tips (for SPW25DK)

MT5	Conical (2 per card)	303020	1
MT8	Chisel (2 per card)	478063	1
МТ9	Knife edge (2 per card)	478070	1

Tips for Marksman Irons



MT05AU	Tip 2mm/3/32 Spade - SP15D 2 Per Card	■ 472795	1
MT10	Tip 6mm/1/4 Chisel - SP40D 2 Per Card	473617	1
MTG30	Tip 13mm/1/2 Chisel - SP120D	477905	1
MTG40	Tip 16mm/5/8 Chisel - SP175D	478674	1
MT50	Tip 19mm/3/4 Chisel - SP250D	480156	1

Tips for SP25D Marksman Iron



MT1	Tip 4mm/5/32 Cone 2 Per Card	472177	1
MT2	Tip 4mm/5/32 S/driver 36•50 2 Per Card	472412	1
МТЗ	Tip 4mm/5/32 Chisel 2 Per Card	472504	1

Iron Plated Tips for Marksman Irons





MTG20	Straight Tip 10mm/3/8 S/driver - SP80D	476595	1
MTG21	Straight Tip 6mm/1/4 S/driver - SP80D	476601	1
MTG22	Beading Tip	■ 300869	1

ALL APN ■ AND UPC ● CODE NUMBERS SHOWN ARE PRECEDED BY THE MANUFACTURER APN OR UPC I.D. NUMBER ■ 9337103 & ● 037103.

Magnastat Controlled Station



Material Number	Description	APN/UPC	Shelf Pack
WTCPTD	Soldering Station	476441	1

Consists of:

- TC202DT2 230V Power Unit
- TC201B 42 Watt 24V Pencil
- PH1201 Stand
- 1.6mm 700°F/371°C tip
- Soldering Tips PT Series available (refer Cooper Tools Electronic Catalogue)

Temperature Controlled Station



T0056806599	WHS40 Soldering Station - 40W/230V	4003019418107	1
T0056828599	WHS40D Soldering Station - 40W/240V - Digital	4003019412952	1

- 3.5mm straight nickel tip
- Ergonomic contoured handle Hot-iron holder

- Tip-cleaning sponge
 40W, 18V low voltage
 Connector for iron lead
 LED optical
- Temperature control dial (200°C-450°C)
 Mains 230V
- Meets Australian and European safety and approval CE

T0054311399	2mm Tip	
T0054311599	3.5mm Tip	

Electronically Controlled Station



WES51D	Soldering Station	■ 339661	1

An economical soldering station with High-End Performance. Ideal for continuous production soldering.

- Analogue temperature controlTemperature lockout

- Automatic shut off
 Slim comfortable pencil reduced operator fatigue
 Temperature range 150°C-450°C
 Max. power output 50W

- Assembled in Australia
 Soldering station consists of:
 WES51DPU 230V Power Unit
 PES51 50 Watt 24V Pencil
 PH50 Holder

- Soldering Tips ET Series available (refer Cooper Tools Electronic Catalogue)

Pyropens



WPA2	Piezo ignition (self) lighting	■ 590437	1
Kit includes: • 1 x WPT-2 sold • 1 x WHC-52 hof • Metal kit box See Cooper Tools			
			_

WSTA3	Soldering, hot blow and torch flame	472283	1
	facilities		

- Kit includes:
 1 x soldering tip
 1 x hot blow tip
- Torch ejector tightening barMetal Kit box.

See Cooper Tools Electronic Catalogue for Tool Selection.

WSTA6	Jnr pocket size with auto ignition	5012535052657	1
-------	------------------------------------	---------------	---

- Fitted with pocket clip
 Suitable for soldering and hot blow applications
 1 x WPT-01 tip

See Cooper Tools Electronic Catalogue for Tool Selection

WSTA5	Jumbo. (self igniting)	■ 370701	1
WOIAJ	Julibo, (Seli julililia)	370701	

- Soldering temperature range 250°-500°C
 1 x 72-01-02 tip
 1 x hot blow tip
 Torch ejector with tightening bar

Metal Kit box.
See Cooper Tools Electronic Catalogue for Tool Selection.



ALL APN ■ AND UPC • CODE NUMBERS SHOWN ARE PRECEDED BY THE MANUFACTURER APN OR UPC I.D. NUMBER ■ 9337103 & • 037103.

Weller Portasol



Material Number	Description	APN/UPC	Shelf Pack
P1C	Port. Cord/1 refill gas pow. Soldering tool Carded	• 593368	6


- Does not require cords, batteries or cartridges
- Patented soldering tool has a catalytic converter that provides a powerful yet safe flameless combustion
- Refills with butane fuel Weller® BR2000
- Tank holds gas for 90 minute operation
- Ideal for a wide variety of soldering and desoldering jobs at work or at home
- Develops 850°F/454°C



Port. Cord/1 refill gas pow. Soldering tool Carded P1KC • 593382 4

- Safety cut off switch when cap replaced
- Flint-spark ignitor in cap
- Packed in a rugged plastic case
- Adjustable temperature control regulates the power (the equivalent of 10-60 watts) to quickly heat the
- Kit contains Portasol® P1 soldering tool, 3/32"/2.4mm iron-plated soldering tip, hot knife accessory, hot blower accessory, blow torch accessory, cleaning sponge and safety stand

• 169372



TIPS FOR P1C and P1KC

T1AU	1.0mm (1/32") Soldering Tip	• 593412	5
T2AU	2.4mm (3/32") Soldering Tip	• 593429	5
T3AU	3.2mm (1/8") Soldering Tip	• 593436	5
T4AU	4.8mm (3/16") Soldering Tip	• 593443	5
T5AU	Blow Torch Tip	• 593450	5
T6AU	Hot Blower Tip	• 593467	5
T7AU	Hot Knife Tip	• 593399	5

Butane Soldering



PSI100K Butane Powered Soldering Iron • 06097	6 6
---	-----

- Piezo Ignition Self Lighting
- Kit includes:
- 1 x soldering, hot blow and cutting tip
- Torch flame facility
- Equivalent to 10 to 60 Watts.
- Tip includes:

P2KC

PSI-6, PSI-8, PSI-9, PSI-10

Refer to Electronic Catalogue for Tip Selection Chart.

Full range of PSI Tips are available.



P2KC	Butane Powered Soldering Iron

Multi-purpose Heat tool

- Soldering Iron Blow Torch
- **Hot Air Tool**
- Hot Knife

Piezo Ignition, Cordless and totally portable.
Refills in 20 secs with standard quality butane lighter fuel.

- Adjustable temperature control 15-75 watts
- Anti-static
- Catalytic combustion provides safe flameless combustion
- Iron plated tips
- Kit includes tips PPT12, PPT10, PPT9, PPT5.





TIPS FOR P2KC

PPT5	Double Flat Tip 1.0mm	5099681780054	1
PPT6	Double Flat Tip 2.4mm	5099681780061	1
PPT7	Double Flat Tip 3.2mm	5099681780078	1
PPT8	Double Flat Tip 4.8mm	5099681780085	1
PPT9	Hot Blower Tip	5099681780092	1
PPT10	Hot Knife Tip	5099681780108	1




ALL APN ■ AND UPC ● CODE NUMBERS SHOWN ARE PRECEDED BY THE MANUFACTURER APN OR UPC I.D. NUMBER ■ 9337103 & ● 037103.

Dual Heat Battery Powered Cordless Soldering Tool







- Dual Heat gives two different working temperatures 454°C and 510°C
- Long lasting iron plated conical shape tip
- Solders up to 180 solder joints per battery charge
- Heating element in tip for super-fast heat-up, heats to working temperature in only 15 seconds
- LED work light illuminates your work in low light
- Ideal for field work where electricity is not available
- Perfect tool for light duty soldering jobs where portable is necessary



BP10	Conical Soldering Tip	• 215442	1
BP11	Chisel Soldering Tip	• 215688	1

Blow Torch



ML100	Butane Powered Magna Lite	• 212559	8
	Blow Torch		

- Applications include heat shrinking of tubing, fusing rope ends, un-freezing locks, camping, rist aid, laboratory work and boating, etc.
 Piezo electronic ignition system for reliable ignition every time
 Blue LED light illuminates work in dark conditions
 Adjustable flame height
 Refillable with Weller BR200 butane

- Nozzle cover prevents accidental ignition
- Keyring lanyard

- Handy portable torch for industrial maintenance, tool and die shops, automotive repairs, etc.
- Applications include soldering, brazing, heat shrink tubing, frozen locks, fusing rope ends, camping, boating, labs and more
 Waterproof Piezo electronic ignition system for fast and reliable ignition every time
 Adjustable flame height and length, and level of heat output (up to 1,300°C/2,400°F)
 Flame lock-on allows hands-free operation

- Up to 60 minutes continuous use

Magna-Lite Butane Soldering Iron



ML500MP

Magna-Lite Butane Soldering Iron

• 220912

- Applications include soldering, heat shrink tubing, electrical, electronics, field service repair
- Waterproof piezo ignition for fast, reliable ignition Adjustable flame height
- Temperature adjustable from 400°C to 510°C 30 minute run time

- Also operates as a torch when soldering tip is removed Refills with standard butane gas (Weller BR200)

Portable Soldering Iron



WPSI12V

12 Volt Portable Soldering Iron

329471

- 42 Watt Battery Powered, with temperature control Powered by a 12 Volt, 7.2 amp hour sealed lead acidity battery
- Fitted with an automotive cigarette lighter plug for direct connection to other 12 Volt power sources 21 types of PT series tips available in 315°C,

- S71'C & 427'C
 Battery life of 2-8 hours dependant on usage
 Fluoro yellow carry pack with high visability
 reflective strip, carry strap & soldering tool stand
 3 stage automative battery charger included

NB: Butane Gas: The WELLER BR200 is suitable for P1-C, P-1KC & PP1K, ML100.

Butane Gas





BR200

Butane Gas Refiller 200gms

473600

12

Soldering Stands



PH1260	suits SP15D, SP25D, SP40D	474010	1
PH12100	suits W100D, SP80D	474027	1



ALL APN ■ AND UPC • CODE NUMBERS SHOWN ARE PRECEDED BY THE MANUFACTURER APN OR UPC I.D. NUMBER ■ 9337103 & • 037103.

Solder



Material Number			Shelf Pack
RC40AU	60/40 Alloy Rosin Core 1.6mm	473853	10

De-Soldering Pump



WDS	De-soldering Pump	■ 332167	50

- High Suction Power
- Ideal for PC Board Repairing
- Lightweight
- · Easy to clean cylinder

Weller Cable Ties





Available in black and natural.

Most popular sizes from
100mm to 550mm.

Packs of 25 or 100 pieces.
The black cable ties are
UV resistant, which prolongs useful life
under sunshine/outdoor applications.



WA350 - Weller Cable Ties Assortment Pack -Resealable Container

	Quantity	Colour	Size	Tensile Strength
ı	x 100	Natural	100mm x 2.5mm Ties	8kg
ı	x 100	Coloured	100mm x 2.5mm Ties	8kg
ı	x 50	Natural	200mm x 4.8mm Ties	18kg
ı	x 50	Coloured	200mm x 4.8mm Ties	18kg
ı	x 50	Coloured	280mm x 4.8mm Ties	22kg

Material Number	Description	Pack Qty	APN/UPC	Shelf Pack
WB425	Black 100mm x 2.5mm	25	485009	50
WB4100	Black 100mm x 2.5mm	100	485061	50
WN425	Natural 100mm x 2.5mm	25	■ 485207	50
WN4100	Natural 100mm x 2.5mm	100	■ 485269	50
WB625	Black 150mm x 3.6mm	25	485016	50
WB6100	Black 150mm x 3.6mm	100	485078	50
WN625	Natural 150mm x 3.6mm	25	485214	50
WN6100	Natural 150mm x 3.6mm	100	■ 485276	50
WB825	Black 200mm x 4.8mm	25	■ 485023	50
WB8100	Black 200mm x 4.8mm	100	■ 485085	50
WN825	Natural 200mm x 4.8mm	25	■ 485221	50
WN8100	Natural 200mm x 4.8mm	100	■ 485283	50
WB1225	Black 300mm x 4.8mm	25	485030	50
WB12100	Black 300mm x 4.8mm	100	■ 485092	50
WN1225	Natural 300mm x 4.8mm	25	■ 485238	50
WN12100	Natural 300mm x 4.8mm	100	■ 485290	50
WB1425	Black 370mm x 4.8mm	25	■ 485047	50
WB14100	Black 370mm x 4.8mm	100	485108	50
WN1425	Natural 370mm x 4.8mm	25	■ 485245	240
WN14100	Natural 370mm x 4.8mm	100	■ 485306	50
WB1525	Black 380mm x 7.6mm HD	25	■ 485252	150
WB15100	Black 380mm x 7.6mm HD	100	485313	40
WA350	350 piece Cable Tie Assortment	350	485405	25
WB5100HD	Black 120mm x 4.8mm HD	100	485122	50
WB12100HD	Black 300mm x 7.6mm HD	100	485139	50
WB18100HD	Black 450mm x 8.0mm HD	100	■ 485146	35
WB22100HD	Black 550mm x 8.0m HD	100	485153	25

8 Piece 1000V Insulated Screwdriver Set





SD8SET 8 Piece Screwdriver Set 4003019117222

Consists of:
Phillips® PH 1 x 100 / PH 2 x 100
Pozidrive PZ 1 x 100 / PZ 2 x 100
Slotted 2,5 x 80 / 4,0 x 100 / 6,5 x 150
Main Tester 140

- Insulated according Norm 1000V 06 IEC 60900:2004
- VDE / GS certificated
- Co-moulded handles for maximum comfort
- Blades made of 8660 steel

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Weller manufacturer:

Other Similar products are found below:

XPE700 ST-4 ST-3 0054005799 0058744845 0054465399 6120 7324 PL138 PTH6 HE35 DXV80 NTD T0051387699 T0051607599

T0052916199 T0053418699 T0053427699 T0053434699 T0053638699 T0054486299 T0058732869 PSI5 HEW60P LT4X CT6E7

51314700 WHP80 WTA1 WTA4 DS227 DX120 RT6MS RTW3MS SP40NUS T0051302699 T0051390699 T0051628899 T0052704299

T0053429699 T0053438699 T0053439699 T0053657199 T0054480299 T0058744730 TC208 CT5AA8 WPT15 WLSK200

WEL.51361699