ESD MERCATOR SOUTH DENES GREAT YARMOUTH NORFOLK NR30 3PX

## COMPACT IN-LINE RS232 TO TTL CONVERTER

**APPLICATION** 

: Primarily designed for use with the Itron CU range of VFD modules which support serial input but it is also suitable for any application where RS232 needs to be converted to TTL levels.

**ELECTRICAL RATINGS** 

ENVIRONMENTAL SPECIFICATIONS

Absolute Maximum Ratings

Power Supply Voltage : VCC +10.0 VDC MAX RS232 Input Voltage : VIN  $\pm$  30VDC MAX


Baud Rate

: 19,200bps MAX

Operating temperature : -10 to +55°C Storage temperature : -20 to +70°C Operating humidity : 20 to 85% R.H.

## TYPICAL OPERATING CONDITIONS

PARAMETER		SYMBOL	MIN	TYP	MAX	UNIT	CONDITION
SUPPLY VOLTAGE		vcc	45	5.0	5.5	VDC	
OUTPUT VOLTAGE	Н	VOH	2.6	4	-	VDC	10H = 300uA
	ب	VOL	-	02	0.45	VDC	IOL = 1.6mA
SUPPLY CUPPENT		icc	-	20	26	mA	VCC = 5.0V
THROUGH CURRENT			-	-	3	Α	



## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for noritake manufacturer:

Other Similar products are found below:

GU140X16J-7000B EFP127X098B07A GU160X80E-7900B GU256X64D-7000 GU128x18F-K612A2 GU140X32F-7003B

EFP105X067B07A CU20049-UW2A CU24043-Y100 GU140X16G-7000B CU24043-Y1A GU126X64F-K612A4 GT800X480A-C903P

GU256X16M-K612C5 GTWX101VLB00P GE256X64C-7933B GTWV070C3A00PA GU256X128E-3900B GT800X480A-C903PA

CU22042-Y1A GU256X128D-3900B GTWQ043C3A00PA EFP164X104B07A GU128X8T-K612C5 TKU016CT-A100

GTWV050C3A00PA GU128X64-800B GTWX101VHA00P CU16025-UW2J GU128X32D-7003 GU256X64F-9900 CU20025-UW1J

CU40026-TW200A CU22042-Y100 GU256X64E-3900B GTWV050VHB00P GT800X480A-1303P GU140X16G-7806A GU140X32F-7003

GU140X32F-7806A CU16025-UX6J GU256X64C-3900B CU20025-UX1J CU20045SCPB-T31A GTWV070VHA00P GU256X64D-3900B

GU256X128C-3900B CU20049-UW2J CU16029-UW1J GU280X16G-7000