


## 2 x 5mm Rectangular LED Lamps

## DESCRIPTION AND FEATURES



These rectangular LED lamps provide a 2 x 5mm lighted surface area. Stackable in X or Y direction, these lamps are typically used as legend backlighting, illuminated push buttons, panel indicators and bar graph meters. The High Efficiency Red and Yellow lamps are produced with GaAsP/GaP and the High Efficiency Green lamp is produced with GaP/GaP.

## ELECTRO-OPTICAL CHARACTERISTICS AND RATINGS

PART NUMBER	CMD53123	CMD54123	CMD57123
Output Color	Yellow	H.E.Green	H.E.Red
Diffusion	Diffused	Diffused	Diffused
Package Color	Yellow	Green	Red
Test Current (mA)	20	20	20
Forward Voltage Typ. (V)	2.1	2.2	2.0
Forward Voltage Max. (V)	4.0	4.0	4.0
Luminous Intensity Min. (mcd)	1.0	1.0	1.0
Luminous Intensity Typ. (mcd)	4.0	4.0	4.0
Luminous Intensity Max. (mcd)	-	-	-
Peak Wavelength (nm)	585	562	635
Viewing Angle 20 1/2 (degrees)	100	100	100
Power Dissipation (mW)	120	120	120
Operating Temperature (°C)	-55 to +100	-55 to +100	-55 to +100
S torage Temperature (°C)	-55 to +100	-55 to +100	-55 to +100
Peak Forward Current Max.(1ms pulse width 300pps)(mA)	90	90	90
Reverse Voltage (IR=100μA) (V)	5	5	5
Lead Solder Time @ 260°C	5	5	5

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for cml manufacturer:

Other Similar products are found below:

19050257 18602357 1860623W3A 19010351 19300133 192A0255 19211252 19050253 19241354 195A1350 SK-3-2500 6346002505R
6275AL 19041051 19010053 19180351 19272351 19040351 19051357 19050357 19010350 19000352 T000205 1860325W3D 19000353
SK-2-2500 19410132M 192A1355 7632 18600M51 19051257 19210363 19272350 1512145UR3 T000015 1927235WA 190403Z2
19211253 19740135 192D0000 19240354 192D0230 1511A35W3A 1860245W3 W643 19272352 19080350 190A2351 18606232
1512135UG3