

RO514

Article Number: 590-05140

Rite-On Self-Laminating Label Dispenser, .75" X .375" X 1.25", Vinyl, White, 200/RL



Download drawing



Download spec sheet

Base Data

Local Order Number RO514

Type RO514

Color White (WH)

- Features and Benefits**
- Compact to easily fit in pants or shirt pockets.
 - Dispenser can be reloaded over and over, making it cost effective to use.
 - Dispenser edge allows easy removal of label liner.
 - Dispenser protects labels from dirt and moisture before use, extending the life and quality of the labels.

Color Marking Field White (WH)

Product Description HellermannTyton's Rite-On Markers are made from a flexible vinyl film and used to mark wire and cable. The self-laminating labels have a clear tail which seals the legend under clear vinyl, maintaining the quality of the labels. The Rite-On markers are packaged in a reusable dispenser made from high impact plastic which is resistant to oils and grease.

Mounting method Identification ETIM Pasting / Stick

Short Description Rite-On Self-Laminating Label Dispenser, .75" X .375" X 1.25", Vinyl, White, 200/RL

Product Dimensions

Length L (Imperial) 0.375 "

Length L (Metric) 9.52 mm

Fixation Method Pasting / Stick

Self adhesive (Yes/No) Yes

Variant Roller form

Width W (Imperial) 0.75 "

Width W (Metric) 19.05 mm

Height H (Imperial) 0.375 "

Height H (Metric) 9.52 mm

Height H2 (Imperial) 1.25 "

Height H2 (Metric) 31.75 mm

Bundle Diameter Min. (Imperial) 0.15 "

Bundle Diameter Min. (Metric) 3.89 mm

Bundle Diameter Max. (Imperial) 0.263 "

Bundle Diameter Max. (Metric) 6.68 mm

Outside Diameter Min. (Imperial) 0.153 "

Outside Diameter Min. (Metric) 3.89 mm

Outside Diameter Max. (Imperial) 0.263 "

Outside Diameter Max. (Metric) 6.68 mm

Logistics and Packaging

Quantity Per EA
Package Quantity 200
Package Quantity (Metric) 200
Carton Quantity 1
Weight (Metric) 0.1 kg

Material and Specifications

Material Type 100, Vinyl (PVC), white (WH), self laminating
Material Shortcut 100
Adhesive Shortcut Acrylic
Adhesive Acrylic
Adhesive Operating Temperature -51°F to +200°F (-46°C to +93°C)
Operating Temperature -40°F to +176°F (-40°C to +80°C)
ROHS Compliant Yes

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Wire Identification](#) category:

Click to view products by [Hellermann](#) manufacturer:

Other Similar products are found below :

[CU6337-000](#) [CU6342-000](#) [FCA-410-12](#) [11631010](#) [1-1768037-1](#) [1-1768037-2](#) [1-1768050-0](#) [PXLK-VI](#) [Q62184-1](#) [A64304-000](#) [QMT221](#)
[HK032WE1NF038B](#) [1330-0519-10](#) [1395199-1](#) [1395200-1](#) [1395202-1](#) [DMVF050WE-300S6](#) [D-SCE-1K-2.4-50-4-CS7834](#) [1538738-1](#)
[E90935-000](#) [EC1238-000](#) [EC1465-000](#) [EC1855-000](#) [EC1859-000](#) [EC1863-000](#) [EC5415-000](#) [EC7277-000](#) [EC7352-000](#) [EC7603-000](#)
[EC7707-000](#) [EC7735-000](#) [EC7768-000](#) [EC7828-000](#) [EC7854-000](#) [EC7952-000](#) [EC8128-000](#) [1768037-8](#) [1768041-7](#) [NC-127191-10-9](#)
[HS048WE2NF038B](#) [C03232-000](#) [HTCM-SCE-14-4H-9](#) [HTMS-3/16-9](#) [HT-SCE-1/4-2.0-4](#) [HT-SCE-3/16-2.0-4](#) [HTTMS-1/2-1.50-9](#) [HTTMS-](#)
[CM-1/2-4H-9](#) [HX-SCE-19.0-50-9](#) [HX-SCE-6.4-50-4](#) [C25254-000](#)