



## FEATURES

- D-Ring fastening is ideal for bundling trays and IC tubes
- Adjustable, releasable and reusable - easy to install
- Low charging hook and loop material meets EN 61340-5-1
- Operating Temperature: 300°F (149°C) max
- Melting Temperature: 459°F (237°C)
- Straps should be tested regularly to make sure they retain their properties
- Made in America

Item #	Description	Farnell Part #
VER-28324	Cable Control, Non-Stretch D-Ring, 19mm x 510mm	1677228



Made in the  
United States of America

Unless otherwise noted all tolerances are +/- 10%

Special manufactured items are not returnable for credit

<b>Customer Approval</b>	<b>Date</b>	<b>CABLE CONTROL,LOW CHARGING, NON-STRETCH D-RING,19MM X 510MM, FARNELL PART #1677228</b>	
<b>Vermason</b>	VERMASON UNIT C, 4TH DIMENSION, FOURTH AVENUE, LETCHWORTH, HERTFORDSHIRE, SG6 2TD, UNITED KINGDOM PHONE: +44 (0) 1462-672005, FAX: +44 (0) 1462-670440 E-MAIL: Service@Vermason.co.uk, INTERNET: Vermason.co.uk		<b>DRAWING NUMBER</b>  VER-28324
			<b>DATE</b>  April 2013

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Wire Identification](#) category:*

*Click to view products by [Vermason](#) manufacturer:*

Other Similar products are found below :

[CU6337-000](#) [CU6342-000](#) [FCA-410-12](#) [11631010](#) [1-1768037-1](#) [1-1768037-2](#) [1-1768050-0](#) [PXLK-VI](#) [Q62184-1](#) [A64304-000](#) [QMT221](#)  
[HK032WE1NF038B](#) [1330-0519-10](#) [1395199-1](#) [1395200-1](#) [1395202-1](#) [DMVF050WE-300S6](#) [D-SCE-1K-2.4-50-4-CS7834](#) [1538738-1](#)  
[E90935-000](#) [EC1238-000](#) [EC1465-000](#) [EC1855-000](#) [EC1859-000](#) [EC1863-000](#) [EC5415-000](#) [EC7277-000](#) [EC7352-000](#) [EC7603-000](#)  
[EC7707-000](#) [EC7735-000](#) [EC7768-000](#) [EC7828-000](#) [EC7854-000](#) [EC7952-000](#) [EC8128-000](#) [1768037-8](#) [1768041-7](#) [NC-127191-10-9](#)  
[HS048WE2NF038B](#) [C03232-000](#) [HTCM-SCE-14-4H-9](#) [HTMS-3/16-9](#) [HT-SCE-1/4-2.0-4](#) [HT-SCE-3/16-2.0-4](#) [HTTMS-1/2-1.50-9](#) [HTTMS-](#)  
[CM-1/2-4H-9](#) [HX-SCE-19.0-50-9](#) [HX-SCE-6.4-50-4](#) [C25254-000](#)