Fast Response Thermocouples

SA1 Series

MEETS OR EXCEEDS
SPECIAL LIMITS (SLE)


With Self-Adhesive Backing

- ✓ Self Adhesive Backing for Easy Installation
- ✓ Better Than 0.3 Second **Response Time**
- ✓ 1 m (40") or 2 m (80") Color-Coded PFA **Insulated Leads**
- ✓ Rated to 175°C (350°F) Long Term
- Available in J, K, T, and E Calibrations

To Order Visit newportUS.com/sa1 for Pricing and Details			
Model No.	Description, "L" Dimension, Termination		
SA1-(*)	Thermocouple, 1 m (40") long, stripped ends**		
SA1-(*)-72	Thermocouple, 2 m (80") long, stripped ends**		
SA1-(*)-120	Thermocouple, 3 m (120") long, stripped ends**		
SA1-(*)-SRTC	SA1-(*) with molded strain relief and SMP male connector		

^{*} Specify J, K, T or E thermocouple type.


Ordering Example: SA1-K, pkg of 5 self-adhesive Type K thermocouples, 30 AWG PFA insulation, 1 m (40") long.












175°C (350°F) Temperature Rating

With Miniature Connector and Spool Caddy





Conveniently

To Order Visit newportUS.com/sa1 for Pricing and Details				
Model No.	Wire Gauge	Length m (in)	Insulation	
SA1-J-SC	30	1 (40)	PFA	
SA1-K-SC	30	1 (40)	PFA	
SA1-T-SC	30	1 (40)	PFA	
SA1-E-SC	30	1 (40)	PFA	
SA1-J-72-SC	30	2 (80)	PFA	
SA1-K-72-SC	30	2 (80)	PFA	
SA1-T-72-SC	30	2 (80)	PFA	
SA1-E-72-SC	30	2 (80)	PFA	

Note: 2 m (80") is the longest length available with spool caddy. Ordering Example: SA1-K-SC, package of 5 self-adhesive Type K thermocouples, 30 AWG PFA insulation, 1 m (40") long.

^{**} For a male straight M8 plug add "M8-S-M" to the model number for additional cost. For a male straight M12 plug add "M12-S-M" to the model number for additional cost.

^{**} For a male right-angled M8 plug add "M8-R-M" to the model number for additional cost. For a male right-angled M12 plug add "M12-S-M" to the model number for additional cost.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for newport manufacturer:

Other Similar products are found below:

BDS1 BDT1 WTK-14-36/N 5TC-TT-J-24-72 TXDIN70 OTP-U-F 5SC-TT-K-30-36 WTK-8-24/N MSS-08 TPJ-U-F OTP-U-M 5TC-TT-J-24-50/N 5SC-TT-T-30-72 SMTC-AL-P SMPW-CC-T-M MPJ-K-F-ROHS