

Indoor Break Glass Call Points



- Indoor surface mounting call points available as 470Ω or 680Ω versions
- Unique 'Plug & Play' installation concept
- Anti-tamper facility
- Enhanced aesthetics
- Fully approved to the latest standards, including EN54-11 and LPCB 166b/39 & 166b/40
- Backward compatibility
- Additional transparent hinged covers available for extra protection, ideal for schools etc
- Operating Temperature: -40 to +55°C
- Voltage: 24V DC
- Dimensions (WxHxD): 89 x 93 x 58.5mm

416661.416656

Description	Order Code	Price Each
Call Point 470Ω	100-4630	
Call Point 680Ω	100-4631	
Accessories		
Hinged Cover	100-4632	
Hinged Cover Seals (Pk5)	100-4634	
Spare Glass (Pk10)	890-1970	
Spare Keys (Pk10)	100-4635	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Switch Hardware](#) category:

Click to view products by [KAC](#) manufacturer:

Other Similar products are found below :

[893102000](#) [LZZ1A](#) [0098.9234](#) [61-9707.7](#) [61-9771.0](#) [M2PA-5011](#) [635401](#) [6PA104](#) [6PA113](#) [6PA147-E6](#) [6PA148-E6](#) [6PA32](#) [6PA9](#) [700106](#)
[700109](#) [700201A56](#) [700303A56](#) [700701264](#) [700C1GRY](#) [700C2GRN](#) [704-6001](#) [704.960.4](#) [704.960.9](#) [704.965.1](#) [704.965.2](#) [704.965.6](#)
[704.966.0](#) [7089-3](#) [71M1048](#) [757200264](#) [778000A56](#) [79215938](#) [MHU35](#) [MHU37](#) [825.003.011](#) [825.005.011](#) [825.053.011](#) [825.055.011](#)
[826.000.071](#) [827.020.011](#) [827.400.021](#) [835.900.023](#) [MML52C10C](#) [MML52E10C](#) [MML72EEK](#) [MML92HGH](#) [MML93K](#) [84211M02CNNS](#)
[84211M02LGRS](#) [84211M02LNNX3](#)