

20 MHz/10MHz/7MHz/4MHz DDS FUNCTION GENERATOR



SFG-2100 Series (20/10/7/4 MHz)



SFG-2000 Series (20/10/7/4 MHz)



FEATURES

- * DDS Technology and FPGA Chip Design
- * Frequency Range: 0.1Hz~4/7/10/20 MHz
- * High Frequency Accuracy : ±20ppm
- * High Frequency Stability : ±20ppm
- * Frequency Resolution : 100mHz
- * Low Distortion Sine Wave : -55dBc, 0.1Hz ~ 200kHz
- * Front Panel Setting Save/Recall with 10 Groups of Setting Memories
- * Built-in 9 Digits, 150MHz/High Resolution Counter (SFG-2100 Series Only)
- * INT/EXT AM/FM Modulation (SFG-2100 Series Only)
- * LIN/LOG Sweep Mode (SFG-2100 Series Only)

Based on the Direct Digital Synthesized (DDS) technology and unique FPGA design, the SFG-2000/2100 Series Function Generators are built with exceptionally high performance far exceeding that of any conventional function generators at a very competitive price. Stable output frequency, low distortion, and fine frequency resolution are the most remarkable characteristics of this product series.

The SFG-2000/2100 Series include four members in each family at 4MHz, 7MHz, 10MHz and 20MHz bandwidth (perivd), The SFG-2100 Series have additional functions of Sweep, AM/FM modulation, and External Counter. As a result of the ±20ppm stability level and output waveform accuracy, The SFG-2000/2100 Series well fit into a wide variety of applications, such as signal generator for experiment labs, reference signal for PLL (Phase Locked Loop), and calibration and adjustment source for electronic devices.

SPECIFICATIONS		SFG-2000 Series				SFG-2100 Series			
MAIN		SFG-2004	SFG-2007	SFG-2010	SFG-2020	SFG-2104	SFG-2107	SFG-2110	SFG-2120
Frequency	Range(For Sine, Square)	0.1Hz~4MHz	0.1Hz~7MHz	0.1Hz~10MHz	1Hz~20MHz	0.1Hz~4MHz	0.1Hz~7MHz	0.1Hz~10MHz	1Hz~20MHz
	Range(For Triangle)	0.1Hz~1MHz (1Hz~1MHz for SFG-2020/2120)							
Resolution	Stability	±20 ppm							
	Accuracy	±20 ppm							
Output Function	Aging	±5 ppm / year							
	Amplitude Range	Sine, Square, Triangle							
Impedance	Attenuator	2mV ~ 10Vpp (into 50Ω load)							
	DC Offset	50Ω ±10%							
Duty Control	Range Resolution	-20dB±1dBx2							
	Display	<-5V ~ +5V (into 50Ω load)							
SINE WAVE	Harmonics Distortion	20% to 80%, 2Hz~1MHz (Square wave only)							
	Flatness(Relative to 1kHz)	9 digits LED display							
TRIANGLE WAVE	Linearity	≥98%, 0.1Hz~100kHz; ≥95%, 100kHz~1MHz							
	Symmetry	±1% of period + 4ns, 0.1Hz~100kHz							
SQUARE WAVE	Rise or Fall Time	≤25ns at maximum output. (into 50Ω load)							
	CMOS OUTPUT	Level							
TTL OUTPUT	Level	4Vpp±1Vpp~15Vpp±1Vpp adjustable; Rise or Fall Time ≤120ns							
	Fan Out	≥3Vpp							
SWEEP OPERATION	Rise and Fall Time	20 TTL load							
	Rate Time Mode	≤25ns							
AMPLITUDE MODULATION	Depth & Modulation	100:1 ratio max. and adjustable(*)							
	Frequency	1Sec~30Sec adjustable(**)							
FREQUENCY MODULATION	Carrier BW	Lin./Log. switch selector							
	EXT Modulation Sensitivity	0~100%; 400Hz(INT), DC~1MHz(EXT)							
FREQUENCY COUNTER	Deviation & Modulation	100Hz~5MHz(-3dB)							
	Frequency	≤10Vpp for 100% modulation							
FREQUENCY COUNTER	EXT Modulation Sensitivity	≥±50kHz, center at 1MHz, 400Hz fixed(INT), 1kHz fixed(EXT)							
	Range Accuracy	≤10Vpp for 10% modulation (center at 1kHz)							
Input Impedance	Time base	5Hz~150MHz							
	Resolution	Time base accuracy ±1 count							
Sensitivity	Resolution	±20ppm (23°C ±5°C) after 30 minutes warm up							
	Sensitivity	100nHz							
Sensitivity	Resolution	for 1Hz; 0.1Hz for 100MHz							
	Sensitivity	1MΩ/150pf							
Sensitivity	Resolution	≤35mVrms (5Hz~100MHz)							
	Sensitivity	≤45mVrms (100MHz~150MHz)							

NOTE: 1.(*) In order to get the maximum sweep span, the sweep time needs to be tuned on when adjusting the sweep span.
2.(**) When the sweep time is too long, the stop frequency will reach and stay at the maximum frequency of the instrument until the end of the sweep cycle.



SFG-2100 Series

Rear Panel



SPECIFICATIONS		SFG-2000 Series				SFG-2100 Series			
		SFG-2004	SFG-2007	SFG-2010	SFG-2020	SFG-2104	SFG-2107	SFG-2110	SFG-2120
STORE/RECALL FUNCTION		10 groups of panel settings							
POWER SOURCE		AC115V±10%, AC230V+10%/-15%, 50/60Hz							
DIMENSION & WEIGHT		266(W)x107(H)x293(D) mm; Approx. 3.1kg				266(W)x107(H)x293(D) mm; Approx. 3.2kg			

ORDERING INFORMATION	
SFG-2004	4MHz DDS Function Generator
SFG-2007	7MHz DDS Function Generator
SFG-2010	10MHz DDS Function Generator
SFG-2020	20MHz DDS Function Generator
SFG-2104	4MHz DDS Function Generator with Counter, Sweep & AM, FM Modulation
SFG-2107	7MHz DDS Function Generator with Counter, Sweep & AM, FM Modulation
SFG-2110	10MHz DDS Function Generator with Counter, Sweep & AM, FM Modulation
SFG-2120	20MHz DDS Function Generator with Counter, Sweep & AM, FM Modulation
ACCESSORIES:	
User manual x 1, Power Cord x 1	
GTL-101 test lead x 1 (SFG-2000 Series)	
GTL-101 test lead x 2 (SFG-2100 Series)	

SELECTION GUIDE		4MHz		7MHz		10MHz		20MHz	
FREQUENCY RANGE	MODEL	SFG-2004	SFG-2104	SFG-2007	SFG-2107	SFG-2010	SFG-2110	SFG-2020	SFG-2120
DUTY		✓	✓	✓	✓	✓	✓	✓	✓
TTL/CMOS		✓	✓	✓	✓	✓	✓	✓	✓
DC OFFSET		✓	✓	✓	✓	✓	✓	✓	✓
LIN/LOG SWEEP		✓	✓	✓	✓	✓	✓	✓	✓
AM/FM MODULATION		✓	✓	✓	✓	✓	✓	✓	✓
EXT COUNTER		✓	✓	✓	✓	✓	✓	✓	✓

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Frequency Counters](#) category:

Click to view products by [GW Connect](#) manufacturer:

Other Similar products are found below :

[MFG-2120MA](#) [3.060.200.383](#) [HK47.C.10-80VDC](#) [3.130.251.071.056](#) [3.220.401.085](#) [3.223.401.351](#) [3.240.201.075](#) [3.241.201.075](#)
[3.242.201.075](#) [3.245.201.351](#) [TFG-3610E](#) [TG5012A](#) [AX-DG105](#) [AX-DG2010AF](#) [3.100.200.383](#) [HMF2525](#) [3.130.251.075.056](#)
[3.130.251.351.056](#) [BZ1224](#) [BZ220A](#) [3.220.401.351](#) [3.240.201.351](#) [3.241.201.351](#) [3.242.201.351](#) [3.245.201.075](#) [3.474.901.075](#)
[3.474.901.084](#) [3.474.911.373](#) [DDS-3X25](#) [0.170.000.075](#) [0.135.200.373](#) [TFG-3620E](#) [0.170.000.351](#) [TGF4162](#) [TGF4242](#) [GFG-3015 + RS232](#)
[HK30.G.48.230VAC/50HZ](#) [HK30.G.48.24VAC/50HZ](#) [0.135.200.302](#) [1803D](#) [53220A/903](#) [1856D](#) [GFG-8215A](#) [GFG-8250A](#) [BG4017-1248](#)
[BW4018-23050](#) [BW4018-2450](#) [BW7089-23050](#) [190.004](#) [190.003](#)