



MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE)

12 MODII HD SRRA B/A .100CL,LF

AMPMODU | AMPMODU Headers

6-146304-2

TE Internal Number: 6-146304-2

Always EU RoHS/ELV Compliant

Applies To **Printed Circuit Board**

Connector Style **Plug**

Centerline **2.54 mm [.1 in]**

Number of Positions **12**

Header Type **Breakaway**

Product Drawings

[HEADER ASSEMBLY, MOD II, BREAKAWAY, HIGH TEMPERATURE,RIGHT ANGLE, SINGLE ROW, .100 C/L , W/.025 SQUARE POSTS](#)

PDF
English

CAD Files

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Applies To

Printed Circuit Board

Connector Style

Plug

PCB Mounting Orientation

Right Angle

Connector Type

Header

Row-to-Row Spacing

2.54 mm [.1 in]

Stabilizers

Without

Strain Relief

Without

| | | |
|----------------------------|---|------------------------------------|
| | Strain Relief | Without |
| | Board Standoff | Without |
| | Product Type | Connector |
| | Gasket | Without |
| Configuration Features | Number of Positions | 12 |
| | Number of Rows | 1 |
| | Keyed | No |
| | Selectively Loaded | No |
| Electrical Characteristics | Dielectric Withstanding Voltage | 750 V |
| Body Features | Header Type | Breakaway |
| | Post Size | .64 mm [.025 in] |
| Contact Features | Contact Protection | Without |
| | Contact Shape | Square |
| | Contact Type | Pin |
| | Contact Base Material | Phosphor Bronze |
| | Contact Mating Area Plating Thickness (µin) | 30 |
| | Solder Tail Contact Plating Material | Tin-Lead over Nickel |
| | Contact Mating Area Plating Material | Gold |
| Termination Features | Termination Post Length | 3.05 mm [.12 in] |
| | Termination End Plating Thickness (µin) | 100 – 200 |
| | Termination End Plating Material | Tin |
| | Termination Method to PC Board | Surface Mount, Through Hole |
| Mechanical Attachment | PCB Mounting Style | Through Hole |
| | PCB Mount Retention | Without |
| | Panel Mount Retention | Without |
| | Mating Connector Lock | Without |
| Housing Features | Centerline | 2.54 mm [.1 in] |
| | Housing Color | Black |
| | Housing Material | Thermoplastic |

| | | |
|-----------------------|--|------------------------------|
| Dimensions | PCB Thickness (Recommended) | 1.6 mm [.063 in] |
| | Mating Post Length | 5.84 mm [.23 in] |
| Usage Conditions | Operating Temperature Range (°C) | -65 – 105 |
| | High Temperature Housing | Yes |
| Operation/Application | High Speed Serial Data Connector | No |
| Industry Standards | UL Flammability Rating | UL 94V-0 |
| | Approved Standards | CSA LR7189, UL E28476 |
| Packaging Features | Packaging Quantity | 25 |
| | Packaging Method | Tray |
| Product Compliance | Statement of Compliance PDF | |
| | VIEW ALL PRODUCT COMPLIANCE | |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [000-34000](#) [0009482033](#) [0009507031](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [647662-1](#) [65039-019ELF](#) [65817-002LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67016-026LF](#) [67046-001LF](#) [67095-007LF](#) [67230-005LF](#)