


Description: Bluetooth, WiFi Antenna

PART NUMBER: W3092

Series: The Blue Dot



Features:

- Chip Antenna
- Frequency:2400MHz~2483MHz
- Low profile
 2.0mm(Length) x 1.2mm(Width)
 x 0.55mm(Thickness)

Applications:

- WLAN
- 802.11b/g
- Bluetooth
- Zigbee, ISM 2.4GHz

All dimensions are in mm / inches

Issue: 1639

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION

This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden. For more information:

Pulse Worldwide Headquarters 12220 World Trade Drive San Diego, CA 92128 USA Tel:1-858-674-8100 Pulse/Larsen Antennas 18110 SE 34th St Bldg 2 Suite 250 Vancouver, WA 98683 USA Tel: 1-360-944-7551 Europe Headquarters Pulse GmbH & Do, KG Zeppelinstrasse 15 Herrenberg, Germany Tel: 49 7032 7806 0 Pulse (Suzhou) Wireless Products Co, Inc. 99 Huo Ju Road(#29 Bldg,4th Phase Suzhou New District Jiangsu Province, Suzhou 215009 PR China Tel: 86 512 6807 9998



Description: Bluetooth, WiFi Antenna

Series: The Blue Dot

PART NUMBER: W3092

ELECTRICAL SPECIFICATIONS

Frequency	2400-2483	MHz	
Nominal Impedance	50	Ω	
VSWR	3	max	
Gain (Typ.)	0.89	dBi	
Efficiency(Typ.)	50	%	
Polarization	Lir	Linear	



Description: Bluetooth, WiFi Antenna

Series: The Blue Dot

PART NUMBER: W3092

MECHANICAL SPECIFICATIONS

Weight 0.005 g

Size 2.0x1.2x0.55 mm

ENVIRONMENTAL SPECIFICATIONS

Operating temperature -40/+105 ° C

High temperature resistance 150 ° C, 1000 hours

Low temperature resistance -40 ° C, 1000 hours

Humidity 85%R.H. 85±5 ° C, 1000 cycles

Soldering heat resistance 260 ° C 10s

Thermal shock -40/+105 ° C

Storage condition

At warehouse 0-30 °C, <60%R.H., shoule be used<1 year


On board -40 ~85 ° C, <85%R.H




Description: Bluetooth, WiFi Antenna


Series: The Blue Dot **PART NUMBER: W3092**

MECHANICAL DRAWING











PulseLARSEN

Description: Bluetooth, WiFi Antenna


Series: The Blue Dot

PART NUMBER: W3092

OTHER SPECIFICATIONS

Recommended PCB layout(Unit:mm)

PCB size(L X W X T): 110 X 55 X 1mm










Description: Bluetooth, WiFi Antenna

Series: The Blue Dot

PART NUMBER: W3092

OTHER SPECIFICATIONS

PCB top side layout



Issue: 1639

RŏHS






Description: Bluetooth, WiFi Antenna

Series: The Blue Dot

PART NUMBER: W3092


OTHER SPECIFICATIONS

PCB bottom side layout



*Clearance 8mm × 2.7mm : All metallization should be removed from all PCB layers.

Recommended matching circuit










Description: Bluetooth, WiFi Antenna

Series: The Blue Dot

PART NUMBER: W3092

OTHER SPECIFICATIONS

Recommended reflow soldering



Time

Α	1 st rising temperature	The normal to Preheating temperature	30s to 60s	
В	Preheating	140°C to 160°C	60s to 120s	
С	2 nd rising temperature	Preheating to 200°C	20s to 40s	
D	Main heating	if 220℃	50s∼60s	
		if 230°C	40s∼50s	
		if 240℃	30s∼40s	
		if 250℃	20s~40s	
		if 260°C	20s~40s	
Е	Regular cooling	200°C to 100°C	1℃/s ~ 4℃/s	

^{*}reference: J-STD-020C

(1) Soldering gun procedure

Note the follows, in case of using solder gun for replacement.

- (a) The tip temperature must be less than 350°C for the period within 3 seconds by using soldering gun under 30 W.
- (b) The soldering gun tip shall not touch this product directly.

(2) Soldering volume

Note that excess of soldering volume will easily get crack the body of this product.

Issue: 1639

ROHS



Series: The Blue Dot


TECHNICAL DATA SHEET

Description: Bluetooth, WiFi Antenna

PART NUMBER: W3092

CHARTS

VSWR







Description: Bluetooth, WiFi Antenna


PART NUMBER: W3092

Series: The Blue Dot

CHARTS

Efficiency

Efficiency vs Frequency measured with demo board





Series: The Blue Dot

TECHNICAL DATA SHEET


Description: Bluetooth, WiFi Antenna

PART NUMBER: W3092

CHARTS

Peak Gain

Peak Gain vs Frequency measured with demo board






Description: Bluetooth, WiFi Antenna


PART NUMBER: W3092

Series: The Blue Dot

CHARTS



Radiation pattern XY Plane



2400MHz

Avg (dBi) = -4.07 Peak (dBi) = -2.05 Avg -3 (deg) = 285

2450MHz

Avg (dBi) = -3.89 Peak (dBi) = -1.39 Avg -3 (deg) = 265

2480MHz

Avg (dBi) = -3.32 Peak (dBi) = -1.32 Avg -3 (deg) = 265

─2400MHz **─**2450MHz **─**2500MHz

Phi Angle (°)

Power (dBm)




Description: Bluetooth, WiFi Antenna

PART NUMBER: W3092


Series: The Blue Dot

CHARTS



Radiation pattern

ZX Plane








Description: Bluetooth, WiFi Antenna

PART NUMBER: W3092


Series: The Blue Dot

CHARTS



Radiation pattern









Description: Bluetooth, WiFi Antenna


Series: The Blue Dot
PART NUMBER: W3092

PACKAGING

Taping Package and Label Marking: (unit: mm)


(1) Quantity/Reel: 5000pcs/Reel

(2) Carrier tape dimensions



Type	Α	В	С	D	E	F	L	W
ACA2012				1	4.00± 0.10			1.55± 0.10

(3) Taping reel dimensions



Α	178.0±2.0
В	2.0±0.5
С	13.0±0.5
D	21.0±0.8
Ε	62.0±1.5
F	9.0±0.5
G	13.0±1.0

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antennas category:

Click to view products by Pulse manufacturer:

Other Similar products are found below:

CCT FM1 ABFT AD-NM-SMAF 001-0021 CTC110 MAF94149 EXE902SF MMCX-SMA-100 PDQ24496-91NF GAN30084EU 930-033-R A08-HABUF-P5I AAF95035 DG-ANT-20DP-BG-B APAMPGJ-141 1513563-1 OF86315-FNF OP24516DS-91NM A09-HASM-7 EXE902MD EXE902SM SPDA17806/2170LAR APAMPG-117 GPS1575SP26-004 GPS15MGSMA CMD69273P-30NF CMQ69273-30NF RD2458-5-OTDR-NM RD2458-5-RSMA TRAB24/49003 W4120ER5000 W6102B0100 YE572113-30RSMM 108-00014-50 SPDA17RP918 OP24516SX-91NM OP24516SX-91RSMM CMQ69273P-30NF CMS69273-30NF CMS69273P-30NF TRAB24003N TRAB8213NP TRAB8903 A09-Y8NF A09-Y11NF A09-HSM-7 A09-F8NF-M A09-F5NF-M