



# POWER CONTACTS



✓ Active

↓ **PRODUCT DRAWING**  
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

## III+ SKT,18-14,15AU/FL,LP

AMP | Type III+

66360-3

TE Internal Number: 66360-3

Always EU RoHS/ELV Compliant

Product Type **Contact**

Wire/Cable Size (AWG) **18 – 16**

Wire/Cable Size (mm<sup>2</sup>) **.8 – 1.31**

Circuit Application **Signal**

Contact Type **Socket**

### Product Drawings

[SOCKET ASSEMBLY, LOOSE PIECE, TYPE III+](#)

PDF  
English

### CAD Files

[Customer View Model](#)

2D\_DXF.ZIP  
English

[3D PDF](#)

PDF  
3D

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

### Catalog Pages/Data Sheets

[Signal Contacts](#)

PDF  
English

[AMP Circular Connectors For Commercial Signal & Power Applications](#)

PDF  
English

[M\\_SERIES\\_PIN\\_AND\\_SOCKET\\_CONNECTORS](#)

PDF  
English

### Product Specifications

Application Specification

[Type III+ \(Size 16\) Contacts](#)

PDF  
English

Engineering Report

[Evaluation Testing Of PdNi And Au Plated Type III+ Multimate Contacts](#)

PDF  
English

### Product Environmental Compliance

TE Material Declaration

[MD\\_66360\\_3\\_04082014024\\_data](#)

Instruction Sheets

Instruction Sheet (U.S.)

[Selection Of Multimate Pin And Socket Contacts](#)  
 PDF  
 English

[Selection Of Multimate Pin And Socket Contacts](#)  
 PDF  
 Japanese

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Product Type	Contact
Electrical Characteristics	Test Current (A)	<b>13</b>
Contact Features	Contact Type	<b>Socket</b>
	Contact Base Material	<b>Brass</b>
	Contact Mating Area Plating Material	<b>Gold</b>
	Contact Mating Area Plating Thickness (µin)	<b>15</b>
	Contact Termination Area Plating Material	<b>Tin over Nickel</b>
	Contact Termination Area Plating Finish	<b>Matte</b>
	Contact Size	<b>16</b>
Termination Features	Wire/Cable Size (AWG)	<b>18 – 16</b>
	Wire/Cable Size (mm <sup>2</sup> )	<b>.8 – 1.31</b>
	Termination Type	<b>Crimp</b>
Dimensions	Accepts Wire Insulation Diameter Range	<b>2.03 – 2.54 mm [.08 – .1 in]</b>
Operation/Application	Circuit Application	<b>Signal</b>
Identification Marking	Color Code	<b>Violet</b>
Packaging Features	Packaging Method	<b>Carton, Loose Piece</b>
	Packaging Quantity	<b>1000</b>
Other	Comment	<b>Insertion Tool No. 91002-1 (for Insulation Dia. 1.78 [.07] or less), No. 200893-2 (for Insulation Dia. .09 [2.29] max.) Extraction Tool No. 305183., Overall insulation crimp</b>

diameter, including crimp barrel, must not exceed 3.18 [.125].

For Use With

CPC Connectors, G Series Connectors, M Series Connectors

Wire/Cable Type





Discrete Wire

Product Compliance

[Statement of Compliance PDF](#)

[VIEW ALL PRODUCT COMPLIANCE](#)

## CUSTOMERS ALSO BOUGHT

POWER CONTACTS	CHASSIS PANEL MOUNT RESISTORS	SINGLE PHASE FILTERS	CIRCULAR POWER CONNECTORS
			
III+ PIN, 18-14, 15AU/FL, LP 66361-3	THS25 150R 5% THS25150RJ	15EHZ1=F8356 3-1609037-1	CPC RECPT SEALED SIZE 23-37 206151-4
<a href="#">Save to List</a> <a href="#">Find Similar Products</a>	<a href="#">Save to List</a> <a href="#">Find Similar Products</a>	<a href="#">Save to List</a> <a href="#">Find Similar Products</a>	<a href="#">Save to List</a> <a href="#">Find Similar Products</a>

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Standard Circular Contacts](#) category:*

*Click to view products by [TE Connectivity](#) manufacturer:*

Other Similar products are found below :

[M24308/4-14F](#) [12110600010](#) [129591AU](#) [1000B BULK](#) [RFM26W-1D28](#) [RM20M13D28](#) [RM24M9D28](#) [MS3474W10-6P L/C](#) [164-901-CD](#)  
[1900ND02P2B00A](#) [192900-0082](#) [192900-0356](#) [ST-JL05-16S-C3-100](#) [T01-CRIMP-S03](#) [APK-SA16A07-002](#) [CONT-JL05-08S-C2-10](#)  
[RC16M-23T](#) [RFD26L-1D28](#) [M85049/124S13W](#) [JN1-22-20S-R-PKG100](#) [031-50565](#) [031-50794](#) [SJS861301M](#) [CF16SC18RF](#) [CONT-JL05-](#)  
[08P-C1-10](#) [ST-JL05-16P-C1-100](#) [ST-JL05-16S-C1-100](#) [ST-JL05-20P-C1-100](#) [ST-JN5-S-C1B-2500-\(A534G\)](#) [82911466K](#) [82911467NK](#)  
[84690-0106](#) [M81714/67-21](#) [M24308/2-11F](#) [HN0201600031](#) [M85049/118S20W](#) [031-50969-010](#) [T3P16FC3LZ](#) [ST-JL05-16S-C2-3500](#) [ZP-](#)  
[4016-10NF](#) [HN0201600022](#) [M24308/2-290F](#) [T3P22MC1LY](#) [CONT-JL05-08P-C2-10](#) [M24308/2-283Z](#) [CONT-JL05-12P-C1-10](#)  
[RM20M12G8D28](#) [031-50676](#) [12115010110](#) [SAM12C-03G03](#) [CAP-DACMDPC2](#)