




# CRIMP RINGS & SPADES



Active

PRODUCT DRAWING  
English

3D PDF

TE CONNECTIVITY (TE)

## PIDG R 22-16 COMM 22-18 MIL 6

PIDG | PIDG

51863-1

TE Internal Number: 51863-1  
Mil-Spec: MS25036-102

Always EU RoHS/ELV Compliant

Terminal Shape **Ring Tongue**

Stud Diameter **3.68 mm [ .145 in ]**

Tongue Thickness **.79 mm [ .031 in ]**

Heavy Duty **No**

Wire Insulation Diameter (Max) (in) **.125**

### Product Drawings

[TERMINAL, RING TONGUE, PIDG WIRE SIZE: 22-16 AWG](#)

PDF  
English

### CAD Files

[3D PDF](#)

PDF  
3D

[Customer View Model](#)

2D\_DXF.ZIP  
English

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

### Product Environmental Compliance

TE Material Declaration

[MD\\_51863-1\\_05022015532\\_dmtec](#)

PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

### Product Type Features

Barrel Type

**Closed Barrel**

Wire/Cable Type

**Regular Wire**

Insulated

**Yes**

Insulated Wire Support

**Yes**

Support Style

**Insulation Support**





	Stud Size	<b>6, M3.5</b>
	Shape Code	<b>RING-041</b>
	Barrel Style	<b>Standard</b>
	Wire/Cable Composition	<b>Solid or Stranded</b>
Configuration Features	Terminal Angle	<b>Straight</b>
	Number of Holes	<b>1</b>
Electrical Characteristics	Voltage (Max) (V)	<b>300</b>
Body Features	Plating Material	<b>Copper, Tin</b>
	Insulation Sleeve Material	<b>Nylon</b>
	Insulation Sleeve Color	<b>Red</b>
	Weight per Piece (g)	<b>.722</b>
Contact Features	Terminal Shape	<b>Ring Tongue</b>
	Terminal Orientation	<b>Straight</b>
	Class	<b>2</b>
Dimensions	Stud Diameter	<b>3.68 mm [ .145 in ]</b>
	Tongue Thickness	<b>.79 mm [ .031 in ]</b>
	Wire Insulation Diameter (Max) (in)	<b>.125</b>
	Wire Insulation Diameter	<b>2.03 – 3.18 mm [ .08 – .125 in ]</b>
	Wire Size (AWG)	<b>22 – 16</b>
	Wire Size (mm <sup>2</sup> )	<b>.3 – 1.42</b>
	Wire Size (CMA)	<b>509 – 3260</b>
	Barrel Inside Diameter (in)	<b>.28</b>
	Overall Length	<b>19.86 mm [ .782 in ]</b>
Operation/Application	Heavy Duty	<b>No</b>
Industry Standards	Government Qualified	<b>Yes</b>
Packaging Features	Packaging Method	<b>Tape Mounted</b>
	Packaging Quantity	<b>5000</b>

Product Compliance

[Statement of Compliance](#)  
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

## CUSTOMERS ALSO BOUGHT

SPLICES	RECTANGULAR CONNECTOR LOCKING	HOOK UP WIRE	CRIMP RINGS & SPADES
 <p data-bbox="153 696 344 757">SPLICE, N CE 22-10 2-35653-1</p> <p data-bbox="153 853 379 927"><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	 <p data-bbox="464 719 737 792">AMP POWER DBL LOCK 1P PLATE 316770-1</p> <p data-bbox="464 875 691 949"><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	 <p data-bbox="775 696 1007 757">55PC0811-16-9CS2502 55PC0811-16-9CS2502</p> <p data-bbox="775 853 1002 927"><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	 <p data-bbox="1086 696 1334 757">PIDG 16-14 R 5/16; TAPE 2-328998-1</p> <p data-bbox="1086 853 1313 927"><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Terminals](#) category:*

*Click to view products by [TE Connectivity](#) manufacturer:*

Other Similar products are found below :

[HT-13-10](#) [71M-250-32-NB](#) [01-2065-1-0216](#) [00581P0075](#) [M10-10RX](#) [M10BCK](#) [60205-1](#) [604200-1](#) [60598-1-CUT-TAPE](#) [60617-1-C](#) [60873-1](#) [M14-516R/SK](#) [M14-6RSX](#) [M18-10FLX](#) [M18-8FBX](#) [M18-8R/LX](#) [M18BCK](#) [61314-6-C](#) [61-S](#) [61-SN-A](#) [62-NBM-A](#) [63-S](#) [640179-1](#) [640917-2-CUT-TAPE](#) [6501550002](#) [66107-2-C](#) [696683-1](#) [696834-1](#) [696861-1](#) [696931-1](#) [696999-1](#) [M8-516RK](#) [M86700006](#) [MA250DMFMX-A](#) [701-2007](#) [701-2307](#) [701-7761-03](#) [70F-110-32-PB](#) [718-N-A](#) [71M-187-20-NBL](#) [71M-250-32-NBL](#) [72F-187-20-NBL](#) [72M-250-32-NBL](#) [7310](#) [73F-250-32](#) [73F-250-32-NBL](#) [73F-250-32-NL](#) [F14-10C](#) [F-1M](#) [751-250](#)