



PCB D-SUB CONNECTORS



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE)

15 MSFL PLUG RA 318 (IN,FM,BL)

AMPLIMITE | Standard

747841-4

TE Internal Number: 747841-4

Alias ID: 27-01518-01

Not EU RoHS or ELV Compliant

[Find Compliant Alternatives](#)

Connector Style **Plug**

Centerline **2.74 mm [.107 in]**

Number of Positions **15**

Number of Rows **2**

Shell Size **2**

Product Drawings

[PLUG ASSEMBLY, SIZE 2, 15 POSITION, RIGHT ANGLE, FRONT METAL SHELL, .318 SERIES, BOARDLOCKS, AMPLIMITE HD-20](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
3D

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Product Specifications

Product Specification

[AMPLIMITE HD-20 PCB Mounted Connector](#)

PDF
English

Application Specification

[AMPLIMITE Right-Angle Front Metal Shell Connectors](#)

PDF
English

Qualification Test Report

[Connector, AMPLIMITE HD-20, Printed Circuit Board Mounted](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_747841-4_04222014210_dmtec](#)

PDF
English

Product Type Features	Connector Style	Plug
	Shell Size	2
	Profile	Standard
	PCB Mounting Orientation	Right Angle
	Grounding Straps	With
	Shell Type	Front Metal Shell
	Footprint	8.08 mm [.318 in]
	Grounding Indents	With
	Applies To	Printed Circuit Board
	Sealed	No
	Grounded	Yes
	Product Type	Connector
	Shielded	Yes

Configuration Features	Number of Positions	15
	Number of Rows	2
	Preloaded	Yes

Body Features	Plastic	No
	Color Code	None
	Eyelet Plating Material	Tin over Copper Flash
	Shell Plating Material	Tin
	Insert Material	Chromate
	Shell Material	Steel
	Eyelet Material	Brass
	Post Size	.66 mm [.026 in]

Contact Features	Contact Shape	Round
	Solder Tail Contact Plating Material	Tin-Lead over Nickel
	Contact Base Material	Brass
	Contact Mating Area Plating Thickness (µin)	30
	Contact Mating Area Plating Material	Gold Flash over Palladium Nickel, Gold

Termination Features	Termination Post Length	3.18 mm [.125 in]
	Grounding Clips	Without

Mechanical Attachment	PCB Mounting Style	Through Hole
	PCB Mount Retention	With
	PCB Mount Retention Type	Boardlocks
	Mating Connector Lock	With
	Mating Connector Lock Type	Threaded Insert, 4-40 UNC
	Panel Mount Retention	Without
	Boardlock Material	Copper Alloy
	Mounting Hole Diameter	3.18 mm [.125 in]
	Boardlock Plating Material	Tin-Lead over Nickel
	Threaded Insert Material	Zinc
Threaded Insert Plating Material	Clear Chromate	
Housing Features	Centerline	2.74 mm [.107 in]
	Housing Color	Black
	Housing Material	Nylon or Polyester
Dimensions	PCB Thickness (Recommended)	1.57 mm [.062 in]
Industry Standards	UL Flammability Rating	UL 94V-0
	Approved Standards	UL E28476
Packaging Features	Packaging Method	Tray
	Packaging Quantity	104
Other	Comment	Plugs are preloaded with size 20 DF posted pin contacts
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [D-Sub Standard Connectors](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[DCM37S732N](#) [DAM15P500](#) [DEV09S364GTLF](#) [DEM09P032N](#) [DDM50P732N](#) [DAM15S332N](#) [173109-2218](#) [173109-2466](#) [173109-2436](#)
[173109-2435](#) [56F706-005-LI](#) [56F711-015](#) [015-0341-000](#) [015-0372-008](#) [015-8544-011](#) [017041-0005](#) [020419-0104](#) [012-0515-000](#) [012-9507-](#)
[034](#) [012-9507-114](#) [012-9534-001](#) [020745-0008](#) [609-25P](#) [M24308/2-23Z](#) [M243082310F](#) [M243082410F](#) [M243082411F](#) [M24308/4-21](#)
[CT1A18-11PSA206](#) [CT1N36-5SC](#) [CT2-16S-17PS](#) [CT2-20-15PCAU](#) [CT2-24-12PS](#) [CT2-24-28PSF127A206](#) [CT2-32-9PC](#) [CT6F9767-14-4-](#)
[14S-5PC](#) [CT6FA10SL-4PS](#) [CT7-18-10SC](#) [CT7-18-10SCAU](#) [CT7-18-12SCAU](#) [CT7-18-1PC](#) [CT7-18-1PCAU](#) [CT7-18-21SCAU](#) [M83513/01-](#)
[FC](#) [M83723/76W24619 L/C](#) [M85049/48-3-2F](#) [69001-865](#) [6STD09PCM99B70X](#) [6STD09SCM99B30X](#) [6STD09SCT99S40X](#)